



COMPANY SURGEONS

*Dr. Abbott Skinner, Chf. Med. Officer.....	St. Paul, Minn.
*Dr. Hugo F. Schroeckenstein, Asst. to Chf. Med. Officer.....	St. Paul, Minn.
*Dr. Darrell E. Westover	St. Paul, Minn.
*Dr. John F. Alden	St. Paul, Minn.
*Dr. Ernest R. Anderson.....	Minneapolis, Minn.
*Dr. Victor E. Ekblad	Superior, Wis.
Dr. Milton Finn	Superior, Wis.
Dr. Fred Johnson.....	Superior, Wis.
Dr. E. G. Stack	Superior, Wis.
Dr. Raymond J. Spurzem	Anoka, Minn.
Dr. Wm. T. Nygren.....	Braham, Minn.
Dr. W. W. Will	Bertha, Minn.
Dr. G. E. Larson.....	Cambridge, Minn.
Dr. C. E. Norberg	Cloquet, Minn.
Dr. Gordon C. MacRae.....	Duluth, Minn.
*Dr. C. H. Coombs.....	Cass Lake, Minn.
Dr. R. W. Brockway.....	Grand Rapids, Minn.
*Dr. John B. Evensta.....	Grand Rapids, Minn.
Dr. Clarence Jacobson	Hibbing, Minn.
*Dr. John J. Muller.....	Hibbing, Minn.
Dr. R. L. Christie.....	Long Prairie, Minn.
Dr. Paul J. Keith	Milaca, Minn.
Dr. E. G. Hubin.....	Sandstone, Minn.
*Dr. H. W. Goehrs	St. Cloud, Minn.
Dr. G. H. Goehrs	St. Cloud, Minn.
*Dr. Julian F. DuBois, Jr.....	Sauk Centre, Minn.
*Dr. John C. Grant	Sauk Centre, Minn.
Dr. E. N. Peterson	Virginia, Minn.
Dr. J. Arnold Malmstrom.....	Virginia, Minn.
*Dr. Charles J. Mock	Virginia, Minn.
*Dr. Luther F. Davis.....	Wadena, Minn.
Dr. O. F. Ringle	Walker, Minn.

*Designates also Examining Surgeon.

OPHTHALMOLOGISTS

(Eye Doctors)

Dr. Richard C. Horn.....	Minneapolis, Minn.
Dr. Malcolm A. McCannel	Minneapolis, Minn.
Dr. John E. Power, Jr.	Duluth, Minn.
Dr. T. J. Doyle	Superior, Wis.
Dr. Roger T. Thompson.....	Superior, Wis.
Dr. W. T. Wenner.....	St. Cloud, Minn.

W. T. SLOAN, Asst. Superintendent.
 J. CHRISTIANSON, Chief Dispatcher.
 C. W. HAMMER, Chief Dispatcher.
 J. P. SULLIVAN, Master Mechanic.
 J. A. LEHN, Trainmaster.
 W. R. RICHTER, Trainmaster.
 J. H. GRAY, Traveling Engineer.
 D. S. KUKULL, Traveling Engineer.
 M. L. PURDY, Traveling Engineer.

Scanned from the Dean Ogle Collection

GREAT NORTHERN RAILWAY COMPANY

MESABI DIVISION

TIME TABLE 87

EFFECTIVE 12:01 A.M.

CENTRAL STANDARD TIME

Tuesday, September 8, 1964

R. H. HEMMESCH, Superintendent.
 R. N. WHITMAN, General Manager.

H. J. SURLS,
 General Superintendent Transportation.

Printed in U.S.A.

2 WESTWARD

FIRST SUBDIVISION

EASTWARD

Station Numbers	Car Capacity		SECOND CLASS		FIRST CLASS		Distance from Duluth	Time Table No. 87			Telegraph Calls	Distance from St. Paul	SIGNS	FIRST CLASS		SECOND CLASS	
	Sidings	Other Tracks	407	19	23	Effective September 8, 1964			24	20				408			
						STATIONS									Daily	Daily	Daily

J 139	82		L 4.45Pm	L 7.40Am	2.37	DULUTH	DU	159.97	RKDNXB	A 11.55Am	A 7.45Pm		
			A 4.51Pm	A 7.46Am		BRIDGE SWITCH		157.60		L 11.45Am	L 7.39Pm		

TRAINS BETWEEN ELEVATOR STATION AND DULUTH TERMINAL DEPOT ARE GOVERNED BY NORTHERN PACIFIC, LAKE SUPERIOR DIVISION TIME TABLE

			s 5.00	s 7.55	3.23	ELEVATOR STATION		156.74					
					4.22	SUPERIOR	★	155.75	RKPBXO	s 11.39	s 7.30		
J 136	Yard	5689			5.41	25TH ST.		154.56	PX				
J 131		32			8.40	CENTRAL AVE.		151.57	V				

FIRST CLASS TRAINS BETWEEN CENTRAL AVE. TOWER AND DULUTH TERMINAL DEPOT ARE GOVERNED BY NORTHERN PACIFIC, LAKE SUPERIOR DIVISION TIME TABLE

Station Numbers	Car Capacity	Other Tracks	L		Distance from Duluth	Station Name	Track	Distance from St. Paul	Sign	A		L	
			Time	Time						Time	Time		
J 130	Yard	297	L 9.30Pm	L 8.03Am	8.67	CENTRAL AVE. TOWER	CTC	SU 151.30	RIDNXPJ	A 11.29Am	A 7.13Pm	A 12.12Am	
			9.34	8.05	10.37	SAUNDERS	★	B 149.60	VRIDNXPJ	11.27	7.11	12.08	
J 125			9.42	8.08	13.43	BOYLSTON			PJ	11.24	7.08	12.02Am	
J 121	96	7	9.58	f 8.14	18.54	DEDHAM			P	f 11.18		11.54	
J 113	127	10	10.19	f 8.21	24.71	FOXBORO			P	f 11.10	6.56	11.44	
J 103	139	3	10.49	5.38	36.74	NICKERSON	★	NS 123.23	NP	10.56	6.46	11.26	
J 99		4		s 8.40	40.65	DUQUETTE			P	f 10.52			
J 96		12	11.00	s 8.44	43.18	KERRICK		K 116.79	DP	f 10.48		11.16	
J 91	110	14	11.08	s 8.51	48.93	BRUNO			P	s 10.41		11.08	
J 82	135	25	11.20	s 9.01	67.31	ASKOV		RD 102.66	DP	s 10.31	6.30	10.56	
J 76	134	226	11.28	s 9.11	63.17	SANDSTONE	★	NA 96.80	DINPWX	s 10.22	s 6.24	10.46	
J 67		22	11.48	s 9.20	71.99	HINCKLEY		H 87.98	DP	s 10.11		10.31	
	146	16	11.49	6.14	72.36	HINCKLEY TOWER		HT 87.61	DNPIV	10.08	6.14	10.30	
J 59	167	8	12.02Am	s 9.29	80.21	BROOK PARK			P	s 9.59	6.07	10.17	
			12.03	s 9.30	80.54	BROOK PARK JCT.			PJ	9.58	6.06	10.16	
GA54	16	4	12.12	s 9.36	86.01	HENRIETTE			P	s 9.52		10.08	
GA49	107	28	12.21	s 9.45	91.45	GRASSTON			P	s 9.45	5.57	9.59	
GA43	59	32	12.29	s 9.55	96.72	BRAHAM		RA 63.25	DP	s 9.39	5.52	9.51	
GA40		15	12.34	s 9.59	100.15	STANCHFIELD			P	s 9.34		9.46	
GA38		27	12.39	s 10.03	102.64	GRANDY			P	s 9.30		9.40	
GA33	104	126	12.47	s 10.11	107.52	CAMBRIDGE	★	CG 52.45	DNP	s 9.25	s 5.43	9.32	
GA27		65	12.55	s 10.19	113.17	ISANTI		IS 46.80	DP	s 9.18		9.24	
GA21	97	45	1.04	s 10.27	119.19	BETHEL		BE 40.78	DP	s 9.08	5.34	9.14	
GA15		17	1.13	f 10.34	125.34	CEDAR			P	f 9.02		9.04	
GA 9	82	18	1.21	f 10.39	131.03	ANDOVER			P	f 8.57	5.24	8.55	
G 13			A 1.30Am	A 10.45Am	136.99	COON CREEK JCT.		CN 22.98	JRDNPV	L 8.52Am	L 5.19Pm	L 8.45Pm	

TRAINS BETWEEN COON CREEK JUNCTION AND NORTHTOWN ARE GOVERNED BY NORTHERN PACIFIC TIME TABLE

TRAINS BETWEEN NORTHTOWN AND ST. PAUL ARE GOVERNED BY TWIN CITY TERMINALS TIME TABLE

			A 8.00Pm	A 11.30Am	159.97	ST. PAUL				L 8.10Am	L 4.30Pm		
			4.0	2.26	3.05	Time Over Subdivision				3.03	2.26	3.27	
			32.1	56.3	44.4	Average Speed Per Hour				44.9	56.3	37.2	

Westward trains are superior to eastward trains of the same class.
SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 5 THROUGH 11.

WESTWARD

SECOND SUBDIVISION

EASTWARD 3

Station Numbers	Car Capacity						Distance from Dutch	Time Table No. 87		Telegraph Calls	SIGNS					
	Sidings	Other Trucks						Effective September 8, 1964	STATIONS							
J125							13.43		BOYLSTON		PJ					
Y251	99	2					19.21		5.78 DEWEY		P					
Y249							23.09		3.88 STATE LINE TOWER	S	DNPI					
Y238		45					29.14		6.05 ALFORD		P					
Y236	85	10					33.01		3.87 CARLTON	A	DNPI					
Y229		239					38.97	DOUBLE TRACK	5.96 CLOQUET		KN	DPXV				
Y213	129	95				55.45			16.48 BROOKSTON	★		JPYW				
Y205	187	8				63.31			7.86 PAUPORES			P				
Y195	193	46				73.27			9.96 FLOODWOOD		OD	DP				
Y189	182	3				79.37			6.10 ISLAND			P				
Y178	195	19				89.83			10.46 SWAN RIVER	★		P				
Y168	196					98.78			8.95 PHILBIN			P				
Y161	142	178				106.30			7.52 GUNN			JYPX				
Y159	92	263				109.34			3.04 GRAND RAPIDS	★	GR	DNXPW				
Y157	49	30				118.04			3.70 SEYTON			PX				
Y156	123	9				114.23		1.19 COHASSET			P					
Y145	135	96				123.60		9.37 DEER RIVER		RI	DPX					
Y138	71	15				130.70		7.10 BALL CLUB			P					
Y125	69	22				143.60		12.90 BENA		BA	DP					
Y118	123	4				151.15		7.55 SCHLEY			P					
						153.21		2.06 SOO JCT.			JPV					
Y106	Yard	681				162.69		9.48 CASS LAKE	★	CS	BJRDN KWXPYO					

Westward trains are superior to eastward trains of the same class.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 5 THROUGH 11.

G. N. MESAABI DIVISION

4 WESTWARD THIRD SUBDIVISION EASTWARD

Station Numbers	Car Capacity		SECOND CLASS 523 Daily Ex. Sun.	Distance from Sauk Centre	Time Table No. 87 Effective September 8, 1964			SIGNALS	SECOND CLASS 524 Daily Ex. Sun.
	Sidings	Other Tracks			STATIONS	Telegraph Calls			
K-18	39	63	L 5.45Am	0.14	PARK RAPIDS JCT.	JPX	A 11.30Am		
K-24	53	7.10	6.25	18.58	LONG PRAIRIE	NE D	10.50		
K-32	31	7.40	7.10	26.44	BROWERVILLE	VI D	10.30		
K-36	34	32	8.15	31.82	CLARISSA	RU D	10.15		
K-44	27	8.45	8.15	36.51	EAGLE BEND	GD D	10.01		
K-56	52	9.15	8.45	44.02	BERTHA	BR D	9.40		
K-70	23	30	9.45	56.19	WADENA	WD DIV	9.15		
K-79	27	10.05	9.45	70.44	SEBEKA	SK DW	8.01		
K-91	30	116	10.35	79.17	MENAHGA	MH D	7.30		
K-103	29	11.01	10.35	91.17	PARK RAPIDS	J D	6.55		
K-109	27	11.20	11.01	103.07	NEVIS	N D	6.05		
K-119	32	11.40	11.20	109.32	AKELEY	AY D	5.45		
Y-106	Yard	681	A 12.30Pm	118.81	WALKER	V	5.20		
				120.92	N. P. RY. CROSSING	U			
				140.38	CASS LAKE	JBRK DNWX PYO	L 4.30Am		

WESTWARD FIFTH SUBDIVISION EASTWARD

Station Numbers	Car Capacity		SECOND CLASS 305 Daily Ex. Sun.	Distance from Elk River	Time Table No. 87 Effective September 8, 1964			SIGNALS	SECOND CLASS 306 Daily Ex. Sun.
	Siding	Other Tracks			STATIONS	Telegraph Calls			
G-28	L 7.20Am	0.00	ELK RIVER	ER JRDN W	A 11.25Am		

TRAINS BETWEEN N. P. RY. JCT. AND ELK RIVER ARE GOVERNED BY N. P. RY. TIME TABLE

Station Numbers	Car Capacity	Distance from Elk River	Time Table No. 87 Effective September 8, 1964	SIGNALS
H-20	29 116 s	7.22Am	0.74 N. P. RY. JCT.	IV 11.15Am
H-29	20 s	8.35	19.16 PRINCETON	DX s 10.20
	A	9.10	9.42 PEASE	D s 9.45
		9.20Am	4.62 MILACA	MU JP L 9.30Am
		2.0	Time Over Subdivision	1.55
		16.60	Average Speed Per Hour	17.38

WESTWARD SIXTH SUBDIVISION EASTWARD

Station Numbers	Car Capacity		Distance from Brookston	Time Table No. 87 Effective September 8, 1964			SIGNALS
	Sidings	Other Tracks		STATIONS	Telegraph Calls		
Y213	129	95	0.00	BROOKSTON	JPYW		
YD11	145	5	10.92	BADEN	P		
	145	5	24.99	FERMOY	P		
YA12	144	5	39.88	ONEGA	P		
YB25	Yard	1827	50.82	KELLY LAKE	BRKDNP OJWYX		

WESTWARD FOURTH SUBDIVISION EASTWARD

Station Numbers	Car Capacity		Distance from Dormer Jct.	Time Table No. 87 Effective September 8, 1964			SIGNALS
	Sidings	Other Tracks		STATIONS	Telegraph Calls		
YC8	0.00	DORMER JCT.	PX		
			2.03	SHERWOOD JCT.	JXV		
YC6	80	60	2.26	BUHL	PX		
			8.18	FRAZER YARD	PXV		
YD61	6.14	ST. CLAIR JCT.	JPXV		
YD60	6.61	WILPEN JCT.	JPXV		
YD59	Yard	150	9.19	EMMERT TOWER	PIX		
YB31	9.90	NORTH MITCHELL	PX		
YB30	10.75	RUBY JCT.	JPXV		
YB29	139	11.73	HIBBING	AC PX		
			12.31	SCRANTON	IX BRKDNP WXYJO		
YB25	Yard	1327	15.41	KELLY LAKE	KY		
YD64	14	19.4	KEEWATIN	KW DPX		
YD69	115	113	20.27	MOORE	PX		
YD74	520	25.00	NASHWAUK	NK DPX		
YD76	131	27.08	KEVIN	P		
YD80	375	31.60	MARBLE-CALUMET	CU JDPXV		
YD86	35.99	HOLMAN JCT.	JPI		
YD87	37.01	TACONITE JCT.	NI JPV		
YD88	56	38.84	BOVEY	BY DPX		
YD91	300	41.60	CANISTEO	PXY		
Y161	142	178	46.84	GUNN	JPYX		

WESTWARD SEVENTH SUBDIVISION EASTWARD

Station Numbers	Car Capacity		Distance from Brook Park Jct.	Time Table No. 87 Effective September 8, 1964			SIGNALS
	Sidings	Other Tracks		STATIONS	Telegraph Calls		
J48	59	0.00	BROOK PARK	JP		
			11.72	MORA	MA DP		
J41	89	31	18.82	OGILVIE	GO DP BRD JPX		
J28	90	71	30.92	MILACA	MU		
J14	89	38	45.01	FOLEY	FY DP		
G63	182	58.48	EAST ST. CLOUD	DNPIX		

Westward trains are superior to eastward trains of the same class on the Third, Fourth, Fifth, Sixth and Seventh Subdivisions.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 5 THROUGH 11.

ALL SUBDIVISIONS

1. SPEED RESTRICTIONS GENERAL.

The following speed limits apply to trains and engines operating under the conditions outlined, unless rules or conditions require a further reduction:

50 MPH—Diesel engines light or with caboose only.

35 MPH—Trains or engines on main routes, actuating the points of spring switches;

Trains or engines thru No. 20 turnouts at following locations:

SaundersCrossover	Bridge 29Gantlet
BoylstonCrossover	BrookstonJct.
DedhamSiding	BrookstonEnd Dbl. Trk.
AskovSiding	PauporesSiding
Hinckley Tower.....Siding	FloodwoodSiding
Brook ParkSiding	IslandSiding
Brook Park Jct.....Jct.	Swan RiverSiding
GrasstonSiding	PhilbinSiding
Coon Creek Jct.....Jct.	BadenSiding
Coon CreekCrossover	FermoySiding
BrookstonCrossover	OnegaSiding

30 MPH—On Main lines, when handling following equipment in trains, not in actual service but on own wheels, derricks, cranes, pile drivers, Jordan spreaders, shovels, wedge plows, scale test car, also ore cars series 80000 thru 94250 and air dump cars X-2000 thru X-2096, X-7000 thru X-7049 when such cars are loaded with ore or gravel.

25 MPH—Trains handling logs;
Trains or engines moving in facing point direction at spring switches without facing point lock;
Trains or engines thru No. 15 turnouts at following locations:

Cent. Ave. Tower....Crossover	BoylstonJct.
SaundersJct.	GunnJct.
Br. 1.3End Dbl. Trk.	

20 MPH—Trains handling the following equipment on Branch Lines or on 6 degree or sharper curves of Main Lines: scale test car, ore cars series 80000 thru 94250, air dump cars X-2000 thru X-2096, X-7000 thru X-7049 when such cars are loaded with ore or gravel.

15 MPH—Trains handling the following equipment on Branch Lines or on 6 degree or sharper curves of Main Lines: derricks, cranes, pile drivers, Jordan spreaders, shovels and wedge plows.

Trains or engines moving thru interlockings against the current of traffic on double track.

Trains or engines thru all other turnouts, except equilateral turnouts, and those shown previously in this item.

1(a). Rule 240-W of the Consolidated Code of Operating Rules is modified to permit handling Great Northern cars 60276 thru 60279, 61500 thru 61524 and 61000 thru 61009 in passenger trains at passenger train speeds.

2. MOVEMENT OF ENGINES DEAD IN TRAINS.

Engine 2350 must be handled on rear of freight and mixed trains.

Diesel engines 1 thru 196 or any road switcher unit not equipped with alignment control couplers must be towed as single units. On engines 550 thru 599, coupler alignment control lock blocks must be 'DOWN' when coupled in multiple unit operation.

Following road switcher engines are equipped with alignment control couplers: 200 thru 218; 220 thru 230; 550 thru 599 (lock blocks); 600 thru 699; 700 thru 734; 900 thru 915; 2000 thru 2035 and 3000 thru 3016.

Single unit diesel engines, or multiple unit groups (When such groups consist of road freight, road passenger, or engines with alignment control couplers), when towed dead in freight trains, are to be handled not less than five (5) cars nor more than fifteen (15) cars behind the road engine. There should not be more than five (5) units in a group. Additional such units or groups of units must be separated by not less than five (5) cars. When towing diesel engines dead in trains the following speeds must not be exceeded:

MAXIMUM SPEED	ENGINE NUMBER
50 MPH.....	1 thru 10, 14 thru 16, 24 thru 28, 75 thru 162, 165 thru 170
79 MPH.....	350 thru 375, 500 thru 512, 679, 680, 2350
65 MPH.....	All other diesel engine units

3. Except at points where it is necessary to classify trains, open cars loaded with poles, piling, lumber, timber, pipe, or other lading which might shift, should be placed as close as possible to the head end of train, but not next to engine, caboose, occupied outfit car, passenger car or another unprotected car containing commodities which might be subject to damage. Loaded trailer-on-flat cars and multi-level automobile cars are not included in this category. In double track territory, trains handling such cars must use extreme care to avoid slack running in or out when passing or being passed by other trains. In single track territory, trains handling such cars must be at stop when on siding or other track to meet or be passed by other trains, except when have more cars than siding will hold it is permissible for such trains to pull by each other at restricted speed. Loaded dump cars should not be handled on double track after dark, but if necessary to do so, close watch must be maintained by members of the crew, and if a car dumps its load, train must be stopped at once and protection provided as prescribed by the rules.

Great Northern tie flats in series X-4800 to X-4975 and X-4410, whether loaded or empty, must be handled on rear of train.

4. Brakemen with less than one year of experience should not be used as flagmen except in emergency, and then Superintendent will be notified by wire.

5. Due to limited overhead clearance at tunnels and structures, employees are warned to keep off top of cars of extreme height and width when handled in trains and yards, except in emergency. In absence of previous advice on such cars, wire proper officer for instructions.

6. Trains departing from stations, either from siding or main track in trailing point movement actuating points of spring switches, a member of crew must observe indication of governing signal in opposite direction after rear end of train has passed through switch to ascertain if switch points return to normal position. If this signal indicates Stop and no immediate train movement or other cause is evident, report the fact to Superintendent from first available point of communication.

During and immediately following snow storms or violent wind storms, spring switches must be operated by hand and relined in normal position before heading out through switch in trailing point movement, actuating switch points, to insure switch is in proper operating condition.

7. Facing point locks on hand-operated switches are indicated by a six-inch yellow stripe painted on target staff. Be positive locking device is restored to normal position after using. A running switch must not be made through this type switch.

8. Rule 2 of the Consolidated Code of Operating Rules is modified for Great Northern Railway Company employees to the extent that a watch certificate form is no longer required. Watches of employes will be inspected by Division Officers, Rules Examiners and other designated officers.

Rule 3(C) of the Consolidated Code of Operating Rules is amended as follows: Employees governed by time service rules must not wear wrist watches while on duty unless such watches

are of an approved type. Approved type wrist watches are: Elgin, B. W. Raymond Model, 13/0 size, 23 jewels, Ball Official Standard wrist watch, 1604B, stainless steel, 13/0 Ligne, 21 jewels, Bulova Accutron Railroad Approved Model and Hamilton 505 R. R. Electric Special wrist watch.

9. Regarding Consolidated Code Rule 103. In addition to complying with the provisions of this rule, members of a crew will be governed by the following: When an engine, with or without cars, is about to move over a public crossing not protected by a watchman, by gates or by crossing signals in operation, a member of the crew must be on the ground at the crossing to provide protection. Exception—in the movement of a through yard transfer or of a light engine being handled only by hostlers, it is not necessary for a member of the crew to be on the ground at the crossing.
10. Employees are prohibited from riding or walking on the roof of any moving car except when absolutely necessary in the passing of signals, and then only when they place themselves near the middle of the car.
11. Modifying Rules 7 (A) and 12 of the Consolidated Code of Operating Rules: When movement being made is controlled by hand, flag, or lantern signals, the employes involved will give or relay such signals directly to the engineer. The last paragraph of Rule 7 (A) of the Consolidated Code of Operating Rules is revised as follows: When backing or pushing a train, engine, or cars in response to hand or light signals from a trainman, the disappearance from view of the trainman giving such signals or of his light by which such signals are given, must be regarded as a stop signal, except when movement is under control of a trainman on the leading car that is equipped with back-up air brake hose or pipe.
12. Before picking up cars of peeled pulpwood from industry at any station, conductor must examine lading; if lading is not protected with woven wire to prevent sliding out on sides, or, when wire is not available, with boards and stakes, then car must not be moved from industry. The fact must be promptly reported by wire to the Superintendent.
13. Whistle Signals for Routes at Junctions and Interlockings:

Routes	Whistles
Main Track.....	2 short, 1 long
Diverging route.....	2 long
Siding.....	4 short
Against current of traffic.....	1 long, 1 short
14. The Consolidated Code of Operating Rules, Edition of 1959, in addition to the following instructions will govern Great Northern employes while operating on Minnesota Transfer Railway Co. and St. Paul Union Depot Company trackage:

(a) All trackage of the Minnesota Transfer Railway Company is defined as a system of tracks within yard limits over which movements must be made at restricted speed and are not authorized by time table or train order, but subject to prescribed signals and rules, or special instructions.

The limits of the St. Paul Union Depot Co. property extend from connection with the Northern Pacific Ry. and Great Northern Ry. tracks at Third Street and connection with the CMStP&P-CB&Q R.R. tracks opposite depot roundhouse on the east, to connection with the CGW Ry. and CMStP&P R.R. tracks at Robert Street on the west.

(b) The time table of the St. Paul Union Depot Company is for information only. Employes of railroads using the tracks of this Company will be governed by current time table of their respective companies only as to arriving and departing time of trains.

(c) Where in the rules of the Consolidated Code reference is made to trains, such rules will also apply to yard movements and engines.

(d) Under Rule 15, the use of torpedoes is prohibited.

(e) Under Rule 11, burning fuses must not be used except in case of emergency and then only when held in hand and must be extinguished before leaving.

THE FOLLOWING RULES APPLY ONLY ON THE ST. PAUL UNION DEPOT COMPANY:

(f) There is no superiority of trains within the limits of St. Paul Union Depot Company property.

(g) Within the limits of the St. Paul Union Depot Company property, trains and engines must move at restricted speed and must not exceed ten (10) miles per hour through crossovers, turnouts and puzzle switches.

The entrance to, and all movements on this property, will be made only on authority of hand signals from switch tenders. No train or engine may foul any track or puzzle switch without authority of hand signals from switch tenders in control of such movements, except that short interior switching movements may be made through crossovers connecting shed tracks when authorized by train director.

Any lead or track may be used for the make-up of trains on authority of train director. The movement of trains should be given preference.

(h) When indicated by the ringing of the bell, flashing of headlight, hand or light signal that a train or engine is ready to move, the switch tender in charge of the shed track on which the movement is standing will handle as follows: at west end of station the switch tender will control the movement by hand or light signal; at the east end of station the switch tender will inform the train director, who will route the movement by instructions over the public address system. Switch tenders will be governed by these instructions, relaying such instructions by hand or light signal to the next switch tender in the direction of the movement. Each must receive an acknowledgment before signalling the movement. Signals must not be acknowledged or acted upon unless the signal corresponds with instructions from the train director and is definitely understood.

(i) When backing, the back-up air brake valve on passenger trains must be operated by the conductor, except in the movement of empty equipment it may be operated by a competent trainman or yardman. When practicable, conductors must see that trainmen are stationed so hand or light signals may be used in case of any emergency. When backing a train, the engine brake valve must be in running position. An application of the brakes must be made with back-up air brake valve before starting and it must be known that the brakes are in operative condition. Movement must not be started until the proper signal is given. A running test must be made with the back-up air brake valve before the train has moved 300 feet. If the running test is not made within 300 feet the engineer must stop the train and ascertain cause. The speed of train must not exceed eight (8) miles per hour; and train must be under such control that it can be stopped short of train or obstruction, and short of bumping post on stub tracks.

(j) Headlights must be dimmed while on shed tracks.

15. Unless you can stop clear of public crossings in any town, you will arrange to cut at least one crossing. The law provides that railway employes responsible for blocking crossing more than five (5) minutes are subject to arrest and fine.

FIRST SUBDIVISION

(Main Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Passenger	Freight
Central Ave. Tower and Boylston.....	75 MPH	50 MPH
Boylston and Foxboro.....	60 MPH	40 MPH
Foxboro and Coon Creek Jct.....	79 MPH	60 MPH

2. SPEED RESTRICTIONS.

Duluth Terminal Bridge to G.N. Rices Point and G.N. connection to Seventh Ave. freight house, trains and engines at restricted speed not exceeding	20 MPH
Long lead, west end Sandstone Yard.....	15 MPH

3. TRAIN REGISTER EXCEPTIONS.

All trains register by ticket at Central Ave. Tower and Coon Creek Jct.

Saunders, register is only for trains originating at Allouez and they will register by ticket.

Eastward freight trains will throw off register check at Saunders giving all information called for in train register except arrival and tie up.

4. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

(a) At Boylston, Brook Park, trains for which these points are initial stations may proceed on authority of clearance under which such trains arrive.

(b) Mesabi Division clearance received by first class trains and passenger extras at Minneapolis, and by other trains at Minneapolis Jct., will clear train at Coon Creek Jct. when train order signal indicates proceed.

5. RESTRICTED CLEARANCES.

Superior, bents under Fifteenth St. viaduct will not clear man on side of car or engine.

6. Hinckley, automatic block signal 72.1 governing westward trains, is located on left hand side of main track about 500 feet west of depot.

7. SPEED TEST BOARDS.

Engineers shall test speed of their trains passing following point as compared with Speed Table:

Westward, between MP 76 and MP 77 approximately 4 miles west of Hinckley Tower.

Eastward, between MP 77 and MP 76 approximately 3 miles east of Brook Park.

8. CROSSOVERS ON DOUBLE TRACK.

Facing Point	Trailing Point
Saunders, east crossover	Central Ave.
Boylston	Saunders, at Tower.
	Boylston

9. SPRING SWITCHES WITH FACING POINT LOCK.

Dedhamsiding	Grasstonsiding
Nickersonsiding	Cambridgesiding
Askovsiding	Bethelsiding

Normal position is for main track.

10. SPRING SWITCHES WITHOUT FACING POINT LOCK.

Superior, east switch of Eastward and Westward incoming tracks. Normal position is for incoming tracks and all other roundhouse lead switches, when not in use, must be left lined for roundhouse lead.

Elevator "X", east and west of car unloader on unloading track. Normal position of switch west of unloader is for unloading track.

Normal position of switch east of unloader is for runaround track.

11. DRAGGING EQUIPMENT DETECTOR INDICATOR.

Eastward trains on Signal 15.6 between Boylston and Dedham. Westward trains on Signal 61.1 between Askov and Sandstone.

12. MANUAL INTERLOCKINGS.

Central Ave. TowerN. P. Ry. crossing
Coon Creek Jct.junction with N. P. Ry.

When the route is properly lined for a with-the-current-of-traffic movement from Coon Creek to Minneapolis, the signal aspect displayed on Signal 135.1, Westward approach signal on single main track east of Coon Creek, will be yellow over green. (CMStP&P Rule 240E, Figure 1, Page 104 in the Consolidated Code of Operating Rules). The indication of this signal means approach next signal prepared to proceed on diverging route.

13. MANUAL INTERLOCKINGS WITH DUAL CONTROL SWITCHES.

Sandstoneeast and west yard switch

14. AUTOMATIC INTERLOCKINGS.

Superior
73rd St.,MStP&SSM. RR. Crossing

15. Arrange to stop No. 19 daily, except Sunday, at Hinckley at a point accessible to mail messenger so mail pouches can be placed in RPO car door.

16. Great Northern Transfers going to Great Northern Rices Point Yard will use C&NW track from bridge switch to switch in C&NW main track leading to new connection to Great Northern Rices Point Yard. Authority to use C&NW track will be given by clear signal at Minnesota Draw.

For movement from Great Northern Rices Point Yard to Superior, authority to use C&NW track must be obtained from Minnesota Draw by telephone—from phone located in booth just north of Birch Street between Great Northern and C&NW tracks—before leaving Rices Point Yard.

SECOND SUBDIVISION

(Main Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Freight
Boylston and Mirbat	40 MPH
Mirbat and Gunn	60 MPH
Gunn and Cass Lake	49 MPH

The maximum speed of trains handling ore cars is 50 MPH for trains handling empty ore cars, 30 MPH for trains handling loaded ore cars.

2. SPEED RESTRICTIONS.

Between Home Signals of Interlockings at:..... 20 MPH
Bridge 29, westward.

Cass Lake, on all tracks over footwalk crossing located just west of mainline switch to roundhouse..... 8 MPH

Whistle signal must be sounded as prescribed by rule. Crossing must be cut immediately. When this crossing is blocked by coupling up train, trainmen must remain at the crossing to prevent pedestrians from crawling through the cars.

3. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

At Boylston, Brookston and Gunn, trains for which these points are initial stations may proceed on authority of clearance under which such trains arrive.

At Soo Jct., Soo Line Trains may proceed to Cass Lake without obtaining clearance Form A or train order authority which will be received at Cass Lake.

4. Eastward approach signal to end of double track, Brookston, is a double aspect signal indicating yellow over green.

When route is properly lined for eastward train to proceed from single main track to eastward main track of double track, this aspect will be named: "Approach diverging route" and indications will be "Approach next signal prepared to proceed on diverging route".

This signal aspect is governed by CMStP&P Railway Block and Interlocking Rule 240-E, Figure 1, Page 104 of the Consolidated Code of Operating Rules. This rule will apply to and govern Great Northern train and engine movements at this location. Any aspect other than yellow over green at this location will be governed by Great Northern signal and interlocking rules.

5. Main track switches to the following spur tracks located in CTC territory are not equipped with electric locks:

Mirbat
Wawina

Trains or engines using these tracks must keep main track switches open unless main track is occupied by engine or cars; in addition these tracks must not be used to meet or be passed by other trains or engines.

6. SPEED TEST BOARDS.

Engineers shall test speed of their trains passing following point as compared with Speed Table:

Westward, between MP 86 and MP 87 approximately 4 ½ miles west of Island.

Eastward, between MP 87 and MP 86 approximately 2 miles east of Wawina.

7. Cloquet, derails located near east end storage tracks Nos. 1 and 2 are not provided with derail signs.

Cloquet, when setting out cars on either end of No. 1 track be sure cars are shoved down far enough to clear N. P. Ry. cross-overs.

Cloquet, cars left on G.N. tracks must not be closer than 60 ft. each way from 10th Street crossing east of depot.

8. Grand Rapids, when setting out cars, eastward freight trains will stop and leave train west of west switch; westward trains will stop east of the first public crossing.

Grand Rapids, at Hawkinson Addition Crossing MP 110, trains stopped to make set-outs at Grand Rapids must clear this crossing.

9. Cass Lake, when switching movements are made over Highway 371 crossing just west of depot; engine or cars must not occupy crossing until gates are at stop for highway traffic.**10. International Refinery, Alford, while switching, do not handle cars over drip pans with brakes set as sparks from brakes create a fire hazard.**

Cabooses with fires in stoves not permitted on any of the plant tracks and crews working in the vicinity will refrain from smoking.

Tail hose located in telephone booth must be used on end of cuts shoved to Old No. 1 and Old No. 2 tracks with air coupled into it so that trainmen taking position on rear car of cut being shoved can control the movement over crossing immediately ahead of the unloading rack, as well as being able to stop cut of cars short of end of these two spur tracks.

11. CROSSOVERS ON DOUBLE TRACK.

Facing Point	Trailing Point
State Line, west crossover	State Line, east crossover
Carlton, east crossover	Alford
Cloquet, west crossover	Carlton, west crossover
Brookston, east crossover	Cloquet, east crossover

12. SPRING SWITCHES WITH FACING POINT LOCK.

Cass Lake, east yard switch.

Normal position is for main track.

13. SPRING SWITCHES WITHOUT FACING POINT LOCK.

Cass Lake, west crossover switch to roundhouse lead incoming roundhouse track outgoing roundhouse track

Normal position is for tracks named.

14. DRAGGING EQUIPMENT DETECTOR INDICATOR.

Eastward trains, on signal 30.2 approximately one mile west of Bridge 29.

Westward trains on Signal 28.1 approximately 1 mile east of Bridge 29.

15. MANUAL INTERLOCKINGS.

State Line Tower N. P. Ry. crossing
Carlton N. P. Ry. crossing

16. AUTOMATIC INTERLOCKINGS.

Bridge 29, 2.21 miles east of Alford gantlet
Bridge 29:

Release for westward route on westward track is located in release box at eastward home signal.

Release for eastward route on eastward track is located in release box at westward home signal.

Cranks for hand operation of smashboards are attached by chains to the mechanism.

17. CTC—SOO JCT. TO CASS LAKE.

Telephones for communication with the control operator are located at the east end of CTC section and at the spring switch, east end of Cass Lake Yard, 1000 feet west of west end of CTC section. Westward Soo Line trains will call the operator at Cass Lake on phone for authority to enter G.N. main line. The following will govern in case of failure of communications: Soo Line crew will unlock switch and attempt to line for their movement. If switch will line and signal clears, this will be their authority to leave Soo Jct., and proceed to Cass Lake.

THIRD SUBDIVISION

(Park Rapids Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Freight
Park Rapids Jct. and Cass Lake	30 MPH

2. SPEED RESTRICTIONS.

Between Home Signals of Interlockings at:..... 20 MPH
Park Rapids Jct.
Wadena.

3. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).
Mesabi Division clearance received at Sauk Centre will clear train at Park Rapids Jct.**4. Cass Lake, normal position south wye switch is for east leg of wye.****5. AUTOMATIC INTERLOCKINGS.**

Park Rapids Jct., 0.52 miles west of N. P. Ry. crossing
Wadena, 0.23 miles west of N. P. Ry. crossing

6. Unless otherwise instructed, protection against following trains, as required by Consolidated Code Rule 99, is not necessary on Third Subdivision, between Cass Lake and Park Rapids Jct. Form Z train order is not required on this subdivision. If it becomes necessary to operate a following train when there is still a train on this subdivision, the train ahead must be notified to protect against the following train. If this is not practical, the following train must be notified to protect against the train ahead.**FOURTH SUBDIVISION**

(Gunn-Dormer Jct. Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Freight
Gunn and Emmert	45 MPH
Emmert and Dormer Jct.	30 MPH

2. SPEED RESTRICTIONS.

Between Home Signals of Interlocking at:..... 20 MPH
Emmert Tower.

St. Paul Mine Spur, Third Avenue, Keewatin, trains will not exceed a speed of 12 MPH through the approach circuits of the signal system covering crossing signals for Highway No. 169.

Harrison Mine Spur, Naswauk, trains will not exceed a speed of 12 MPH northbound into the mine or 6 MPH southbound out of the mine through the approach circuits of the signal system covering crossing signals for Highway No. 169 crossing.

AT VIRGINIA.

(a) Between Home Signals of Interlockings at:..... 20 MPH
D. W. & P., Virmount Tower.
D. W. & P., Crescent Ave.

(b) Highway No. 53 crossing, 6th Avenue West, leading to Columbia Mine:
Trains must not exceed a speed of 10 MPH through the approach circuits of this crossing.

(c) Trains and engines must stop before passing over crossing U. S. Highway No. 53 leading to depot, and a member of crew on ground at the crossing will protect movement.

(d) Ninth Ave. and Fourth Street Crossing:

Trains and engines must stop before passing over crossing and a member of crew on ground at the crossing will protect movement.

3. **CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).** At Kelly Lake, trains arriving from Sixth Subdivision (Casco Line) destined to Fourth Subdivision (Gunn Line) may proceed to Keewatin on authority of clearance under which such trains arrive.
4. Between Calumet and Oil Spur, located 1.47 miles west of Bovey, main track will be used jointly by G.N. and DM&IR. Rys. and authority for train movements is controlled by G.N. Ry. and G.N. rules and Special Instructions will govern.
5. Train order authority or clearance Form A not required for transfers originating at Bovey for movement between Taconite Jct. and Canisteo. Rule 93 of the Consolidated Code of Operating Rules will apply. Transfers must obtain permission from train dispatcher before occupying main track.
6. Telephone in service at Buckeye, Canisteo and Danube Mines switch. Crews coming from Buckeye, Canisteo and Danube Mines will communicate with the dispatcher and know that way is clear on the main track before proceeding with train down the descending grade on both legs of the wye.
7. Block signal located at Mesabi Chief Mine spur normally displays indication, Rule 240(B) and governs movements from spur to main track; after lining switch, if no conflicting movement is evident on main track, movement may be made in accordance with signal indication after complying with Rule 518.
8. Trains and engines will run with the current of traffic between Kelly Lake and Emmert Tower without train orders or clearance, and must keep to the left unless otherwise provided.
9. Between Emmert Tower and DM&IR. Jct. east of Scranton, G. N. double track will be used jointly by DM&IR. trains. G. N. rules and special instructions will govern.
10. Between Wilpen Jct. and St. Clair Jct., and between Buhl and Dormer Jct., DM&IR trains will use G.N. main track jointly and be governed by G.N. rules and special instructions. Normal position of switches at Wilpen Jct., St. Clair Jct., and Dormer Jct., is for G.N. 4th Subdivision.
11. Between St. Clair Jct. and Chisholm Jct., main track will be used jointly by G.N. and DM&IR. Rys. and authority for train movements is controlled by DM&IR. Ry. and DM&IR. rules will govern.
12. Train and engine movements from main line on new Hull Crusher Spur over Kelly Lake road crossing must be protected by a member of the crew due to restricted view approaching this crossing.
13. Susquehanna Shaft, necessary to shove all empties under the head frame, which will not clear a man on top or side of ore car. Crews must stop before shoving under the head frame and brakemen will walk by the shaft to a point where they can give signals in shoving empties onto the tail tracks.
- When placing empties for shaft loading, fill the north tail track through the crossover first, as an engine will not go over this crossover. Then fill the south tail track. When placing empties for screener loading, fill the south tail track first, then the north tail track as an engine cannot move through the crossover into the south screener tail track.
14. Boeing crude ore unloading pocket, located five (5) feet east of No. 1 tail track switch, Boeing Mine, open between rails and on north side of track. Use caution when working in vicinity of this pocket and walk on south side of track.
15. Main track Kelly Lake to Dormer Jct. is all yard limit and movements will be governed by Consolidated Code Rule 98. Train order authority or Clearance Form A is not required. Transfers will not be required to display markers Rule 19 or signals Rule 21.
16. Following from DM&IR Ry.:
- Train orders are not required for movement on the Wilpen Branch between Wilpen and Chisholm and between Monroe Jct. and Monroe. Trains will operate under provisions of Rule 98. Crews will contact Yardmaster Mitchell District before making movement on this branch.
- Train orders are not required for movement on the Pillsbury Branch. Trains will operate under provisions of Rule 93.
17. Signal protection in service at Danube Mine Spur switch and crossover from Balkan Mining Company track to Danube Mine Tracks. Movements over this crossing will be governed by dwarf color-light signals, displaying indication Figure 6 of Rule 240-A or Figure 4 of Rule 240-H except eastward color-light signal for Balkan Mining Company will display Figure 8 of Rule 240-A or Figure 2 of Rule 240-H, all of the Consolidated Code. Normal position of switches is for Balkan Mining Company and for G. N. Ry. track from Danube Mine to washing plant. Signals will clear automatically for Balkan Mining Company and for G. N. Ry. from Danube Mine to washing plant. To obtain signal to cross over the Balkan Mining Company track, G. N. Ry. trainmen should make sure there is no approaching conflicting movement, then line all three switches in the route to clear signal before proceeding. After crossover movement has been made, all three switches must be restored to normal position for Balkan Mining Company track and G. N. Ry. washing plant track.
18. Normal position of Gunn Line Switch at East leg of wye, Kelly Lake, will be for Fourth Subdivision.
19. **CROSSOVERS ON DOUBLE TRACK.**
- | | |
|---------------------|-------------------------|
| Facing Point | Trailing Point |
| Hull Crusher | Mahoning |
| Ruby Jct. | Agnew |
| | Scranton |
| | Hibbing, east crossover |
| | Hibbing, west crossover |
| | North Mitchell |
20. **SPRING SWITCHES WITH FACING POINT LOCK.**
- Nashwauk, west north storage track switch.
west south storage track switch.
- Calumet, west new yard switch.
- Canisteo, west new yard switch.
Normal position is for main track.
21. **SPRING SWITCHES WITHOUT FACING POINT LOCK.**
- Kelly Lake, west switch transfer cinder pit track,
Normal position is for mallet cinder pit track.
roundhouse wye tracks.
- Normal position east switch is for mallet cinder pit track,
south switch is for east leg of wye.
west switch is for west leg of wye.
- Kelly Lake, west wye switch,
Normal position is for 4th subdivision.
22. **SEMI-AUTOMATIC INTERLOCKINGS.**
- Emmert TowerDM&IR. Ry. crossing
- Emmert, normal position of spring switch at west end of connection with DM&IR Ry. is lined for Great Northern track. Normal position of spring switch at south end of connection with DM&IR Ry. is lined for DM&IR track to North Mitchell. Signal indications are displayed accordingly. If any route other than the above normal route is to be used, trains must stop at home signal and desired route lined by hand. Signal should then clear in about one minute. If signal does not clear and no conflicting movement is evident, push-button release on home signal should be operated to obtain signal indication.

Calumet, 0.60 miles east of.....Hill Annex Spur

Complete instructions for operation of electric lock and gates at semi-automatic interlocking are located at "Release" boxes.

23. AT VIRGINIA.

G. N. Ry. trains to and from Virginia operate via D. M. & I. R. Ry. tracks between Emmert and Virginia.

24. AUTOMATIC INTERLOCKINGS.

Virginia, 0.47 miles west of.....D. W. & P. Ry. crossing
1.20 miles west of.....D. W. & P. Ry. crossing

FIFTH SUBDIVISION

(Princeton Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Freight
Elk River and Princeton	45 MPH
Princeton and Milaca	20 MPH

2. SPEED RESTRICTIONS.

Between Home Signals of Interlocking at Elk River.... 20 MPH

3. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

At Milaca, trains for which this point is initial station may proceed on authority of clearance under which such trains arrive.

4. SEMI-AUTOMATIC INTERLOCKINGS.

Elk River, 0.74 miles west of.....N. P. Ry. Jct.

5. Unless otherwise instructed, protection against following trains, as required by Consolidated Code Rule 99, is not necessary on Fifth Subdivision, between N.P. Ry. Jct. and Milaca. Form Z train order is not required on this subdivision. If it becomes necessary to operate a following train when there is still a train on this subdivision, the train ahead must be notified to protect against the following train. If this is not practical, the following train must be notified to protect against the train ahead.

SIXTH SUBDIVISION

(Casco Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Freight
Brookston and Kelly Lake	45 MPH

2. DRAGGING EQUIPMENT DETECTOR INDICATOR.

Eastward Trains, on iron mast approximately 6400 feet east of Signal 62.2 about 2.5 miles west of Brookston.

3. Main track switches to the following spur tracks located in CTC territory are not equipped with electric locks:

Arlberg
Casco
Onega

Trains or engines using these tracks must keep main track switches open unless main track is occupied by engine or cars; in addition these tracks must not be used to meet or be passed by other trains or engines.

SEVENTH SUBDIVISION

(Milaca Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Freight
Brook Park and East St. Cloud.....	40 MPH

2. SPEED RESTRICTIONS.

Bridge 46.3, Mora	20 MPH
Bridge 54.2, Quamba.....	20 MPH
Between Home Signals of Interlockings at:	20 MPH
Brook Park.	
East St. Cloud.	

3. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

At Brook Park, trains for which this point is initial station may proceed on authority of clearance under which such trains arrive.

4. MANUAL INTERLOCKINGS.

East St. Cloud.....N. P. Ry. crossing

5. Unless otherwise instructed, protection against following trains, as required by Consolidated Code Rule 99, is not necessary on Seventh Subdivision, between Brook Park and East St. Cloud. Form Z train order is not required on this subdivision. If it becomes necessary to operate a following train when there is still a train on this subdivision, the train ahead must be notified to protect against the following train. If this is not practical, the following train must be notified to protect against the train ahead.

SPEED TABLE

Time Per Mile			Miles		
Min.	Sec.	Per Hour	Min.	Sec.	Per Hour
	46	78.3	1	18	46.2
	47	76.6	1	20	45.0
	48	75.0	1	22	43.9
	49	73.5	1	24	42.9
	50	72.0	1	26	41.9
	51	70.6	1	28	40.9
	52	69.2	1	30	40.0
	53	67.9	1	33	38.7
	54	66.7	1	36	37.5
	55	65.5	1	39	36.4
	56	64.3	1	42	35.3
	57	63.2	1	45	34.3
	58	62.1	1	50	32.7
	59	61.0	1	55	31.3
	0	60.0	2	—	30.0
1	1	59.0	2	10	27.7
1	2	58.1	2	20	25.7
1	3	57.1	2	30	24.0
1	4	56.3	2	40	22.5
1	5	55.4	3	—	20.0
1	6	54.5	3	30	17.1
1	7	53.7	4	—	15.0
1	8	52.9	5	—	12.0
1	9	52.2	6	—	10.0
1	10	51.4	7	—	8.6
1	12	50.0	8	—	7.5
1	14	48.6	9	—	6.7
1	16	47.4	10	—	6.0

Business Tracks not shown as stations on Time Table

Name	Location	Car Capacity	Switch Opens
First Subdivision			
North Central Public Service Spur	2.25 miles east of Coon Creek Jct.	7	W
Old Colony Gas & Oil Co. Spur	0.26 miles west of Andover	10	W
Rural Coop. Power Ass'n Spur	2.42 miles east of Cambridge	6	E
Second Subdivision			
Lindsay Pit	1.69 miles west of Carlton	70	E
Mirbat	5.37 miles east of Floodwood	12	E
Wawina	12.90 miles west of Floodwood	11	E
Cohasset Mill & Lumber Co.	0.37 miles east of Cohasset	9	E
Minn. Power and Light Spur	0.98 miles west of Cohasset	106	E
Chippewa Wood Processing Spur	0.13 miles east of Deer River	16	W
Webster Lumber Co.	5.26 miles west of Schley	17	E
Third Subdivision			
Little Sauk	10.24 miles west of Park Rapids Jct.	5	W
Round Prairie	13.70 miles west of Park Rapids Jct.	12	E & W
Peters Meat Products Spur	0.40 miles west of Long Prairie	10	W
Redwood Rendering Co.	1.61 miles west of Long Prairie	35	E
Midland Co-op. Spur	1.68 miles west of Long Prairie	6	E
Hewitt	4.03 miles west of Bertha	22	E & W
Land O'Lakes Creamery Spur	0.58 miles west of Sebeka	19	W
Dorset	6.57 miles west of Park Rapids	11	E & W
Wilkinson	10.12 miles west of N.P. Ry. Crossing	8	E & W
Fourth Subdivision			
Coal Spur	2.47 miles east of Buhl	3	E
Lucknow	1.97 miles east of Buhl	45	E & W
Elbern Siding	3.45 miles west of Buhl	39	E & W
Service Station Inc. Spur	0.90 miles east of Hibbing	4	E
Oil Track	1.42 miles east of Hibbing	18	E & W
Douglas Shop Spur	2.18 miles east of Emmert	9	W
Wacootah Storage Track	3.67 miles west of Virginia	25	E & W
Keewatin Saw Mill Spur	1.92 miles west of Kelly Lake	14	E
Mid-Range Builders Supply	0.15 miles east of Nashwauk	7	W
Minn. Power & Light Spur	1.09 miles east of Nashwauk	15	E
Ryan and Gillis Spur	0.93 miles west of Kevin	29	W
Marble Spur	0.88 miles west of Calumet	5	W
Oil Spur	1.19 miles east of Canisteo	35	W
Fifth Subdivision			
Zimmerman	9.50 miles west of N.P. Ry. Jct.	15	E & W
Long's Siding	4.05 miles west of Princeton	4	W
Sixth Subdivision			
Arlberg	5.42 miles west of Brookston	17	E
Casco	5.84 miles west of Fermoy	36	E
Seventh Subdivision			
Quamba	5.39 miles west of Brook Park	8	E
Kanabec Hdwe. Co. Spur	1.0 miles east of Mora	5	W
Bock	6.88 miles west of Ogilvie	12	W
R. E. A. Oil Spur	0.5 miles east of Milaca	3	W
Foreston	3.29 miles west of Milaca	29	E & W
Oaks	9.01 miles west of Milaca	26	E & W
Parent	4.30 miles west of Foley	28	E & W

Mine Spurs

Name	Location	Switch Opens
Stevenson, Lamberton, Mahoning Concentrate, Warren	0.53 miles east of Kelly Lake	W
Mahoning, N. Uno, Mahoning Grp IV, So. Agnew, Carmi	0.72 miles east of Kelly Lake	W
Hull Crusher	1.80 miles east of Kelly Lake	W
Morton	1.98 miles east of Kelly Lake	E
Scranton, Alworth	2.42 miles west of North Mitchell	W
Susquehanna, Weggum, Boeing	0.03 miles west of North Mitchell	E
Webb, Albany, Longyear	0.81 miles east of North Mitchell	E
Dunwoody	0.99 miles east of Emmert	W
Chataco	0.74 miles west of Chisholm	W
Elbern	2.87 miles west of Buhl	W
Judson, Michael	1.35 miles west of Buhl	W
Grant	1.22 miles west of Buhl	W
North Shiras	0.78 miles east of Buhl	E
Margaret	0.96 miles east of Buhl	E
Wanless	1.38 miles east of Buhl	E
Kinney, Atkins, Wade	0.68 miles east of Dormer Jct.	E
Elliott Siding	1.18 miles east of Dormer Jct.	E & W
Hanna B, Pilot	2.64 miles west of Virginia	E
Enterprise	0.83 miles west of Virginia	E
Bennett-Russell, Carlz	2.57 miles west of Kelly Lake	E
St. Paul	0.25 miles east of Keewatin	E
Chieftan	0.35 miles west of Moore	W
Mesabi Chief Washer, Aromac, Perry, Mississippi	1.17 miles west of Moore	W
O'Brien	1.57 miles east of Nashwauk	W
Hawkins Fines	0.37 miles east of Nashwauk	E
York, Galbraith	0.15 miles east of Nashwauk	W
Hawkins (MacKilican)	0.13 miles east of Nashwauk	E
Harrison, Harrison Fines	0.78 miles west of Nashwauk	W
Patrick A, Patrick C	2.26 miles west of Nashwauk	W
Hill Annex Creta	1.38 miles east of Calumet	E
Hill Annex Washer	0.60 miles east of Calumet	E
Hill Annex Fines, Hill Trumbull Washer	0.69 miles east of Calumet	E
Hill Spur	0.37 miles west of Calumet	E
Rhude Media Spur	0.57 miles east of Holman Jct.	E
Arcturas	0.25 miles east of Holman Jct.	W
Holman	Taconite Jct.	W
Hunner	0.83 miles west of Bovey	E
Canisteo, Buckeye, Danube	Canisteo	E & W
West Hill	0.20 miles west of Canisteo	E
Jessie	1.60 miles west of Canisteo	W
Greenway	2.42 miles west of Canisteo	W
Tioga	0.24 miles east of Seyton	W

Page 12 (outside rear cover) is blank.