

COMPANY SURGEONS

*Dr. Roscoe C. Webb, Chief Surgeon	Minneapolis,	Minn.
*Dr. Ernest R. Anderson, Assistant Chief Surgeon	Minneapolis,	Minn.
*Dr. H. E. Wheeler	Spokane,	Wash.
*Dr. E. B. Coulter	Spokane,	Wash.
*Dr. Geo. E. Hoxsey	Wenatchee,	Wash.
*Dr. L. F. Wagner	Harrington,	Wash.
*Dr. J. K. Kearns	Ephrata,	Wash.
*Dr. C. O. Mansfield	Okanogan,	Wash.
Dr. J. Farrow	Hillyard,	Wash.
Dr. C. M. Canning	Colville,	Wash.
Dr. Fred M. Auld	Nelson,	B. C.
Dr. H. B. Stout	Pateros,	Wash.
*Designates also Examining Surgeon.		

OPHTHALMIC SURGEONS (Eye Doctors)

Dr. Philip B. GreeneSpokane, Wash.

C. E. Emerson, Chief Dispatcher.

H. J. Surles, Trainmaster.

R. W. Downing, Trainmaster.

T. J. Brennan, Trainmaster.

H. H. Holmquist, Trainmaster.

Scanned from the Dean Ogle Collection

GREAT NORTHERN RAILWAY COMPANY

SPOKANE DIVISION

TIME TABLE 77

Effective 12:01 A. M. Pacific Time

Sunday, January 14, 1951

F. V. PERCIVAL, Superintendent.

I. E. MANION, General Manager.

J. B. SMITH,

General Superintendent Transportation.

_2	W	ÆS'	TWAR	D			F	IRST (ST SUBDIVISION FIRST CLASS						
		ar acity											ă.	Time Table No. 77	alla
							1	45 8. P. & 8.	3	27	5	21 5. P. & S. No. 1 Streamliner	rd from	Effective January 14, 1951	Telegraph Calls
Station Numbers	Sidings	Other Tracks					Streamliner Daily	No. 8 Daily	Daily	Daily	Daily	Streamliner	Distance Hillyard	STATIONS	Telegr
	Yard	<u> </u>			1		L . 5Pm	1		L s.6.05Pm	Daily	Daily	0.00	×HILLYARD	HU
	Yard						11.25		9.10	6.15			8.68	U. P. R. R. CROSSING.	
1478	Yard	644					A .30 L .59	L 9.30Pm	A 9.15 L 9.35	A 6.20 L 7.00	L 8.30Am	L 12.06Am	4.85	SPOKANE	Q
1477	69	28					12.05Am	A 9.35Pm	1	7.04	£ 8.35	A 12.11Am	7.59	O FORT WRIGHT	. Fw
1481		6					12.17		9.52	7.14	£ 8.45		18.95	HIGHLAND	
1486		15		••••••	•••••		12.22 12.27		9.57	7.19	f 8.50		17.21	5.39	
1493	129	- 69							10.06	7.25	£ 8.59		22.60	4.09	NA
1498		39					12.31		10.28	7.30	f 9.04		26.69	ESPANOLA	ļ
1502		50		• • • • • • • • • • • • • • • • • • • •			12.37	•••••	10.35	7.37	f 9.13		88.18	WAUKON	
1508		88		• • • • • • • • • • • • • • • • • • • •	·······	•••••	12.42		10.41	7.44	s 9.20		88.90	EDWALL	WH
1512 1517	70	27 46	· · · · · · · · · · · · · · · · · · ·				12.52		10.52	7.55	? 9.25 ? 9.32	•••••	42.60 48.10	5.50	
1011	E62								10.52				20.10	7.41	
1524	W69	i i	• • • • • • • • • • • • • • • • • • • •				12.59		11.01	8.04	s 9.41		55.51	HARRINGTON	HR
1531	E68	46					1.05		11.08	8.12	9.50		62.23	3.71	_
1535 1539		49 85	••••••	••••••			1.09	•••••	11.12	8.17 8.23	f 9.55	••••	65.94 70.40	DOWNS	<u> </u>
1544		15					1.14	•••••	11.17	8.30	£ 10.01	•••••	75.98	5.58 NEMO.	2
1044	100	10									1 10.00			4.85 ODESSA	<u> </u>
1550		118					1.25		11.30	8.36	s 10.14		80.88	ODESSA	BA BA
1558		25				•••••	1.34	- -	11.41	8.48 9.08	£ 10.27		89.74		<u> </u>
1566 1578		88 158					1.41		11.51	9.08	s 10.37 s 10.47	•••••	97 21 108.88	WARLEN	CK
1580		19					1.56		12.01Am 12.11	9.26	t 10.57		111.68	7.82 STRATFORD	₹ <u>```</u>
														5.82	-
1588		182					.2.01		12.18	9.33	f 11.02		116.97	ADRIAN	
1591	129	20		· · · · · · · · · · · · · · · · · · ·			s 2.12			s 9.50	• 11.08 • 11.18		121.57 126.97	SOAP LAKE	FR
1596	70	58					2.17		s 12.33 12.40	9.57	t 11.26		182.12	8.15 NAYLOR	l FR
1606		15					2.22	•••••	12.40	10.04	f 11.33		187.19	8.07 WINCHESTER	
													<u> </u>	6.14	
1612		104	· · · · · · · · · · · · · · · · · · ·				2.28		12.54	1 3	• 11.43	•••••	143.33	QUINCY 5.13 CRATER	QN
1617 1628		19					2.34 2. 4 3		1.01		f 11.50 s 12.01 Pm	•••••	148.46 154.08	5.60 TRINIDAD	
1632		52					2.56		1.10 1. 2 2		f 12.13		168.37	COLUMBIA RIVER	СМ
1637		83					3.01		1.27		£ 12.18		166.82	8.45 VOLTAGE	
														1.50	
1638		28	••••••				3.09	•••••			12.20		168 32	ROCK ISLAND	RI
1641	Yard	'				•••••	3.15	•••••	1.37 1.43		12.28 12.35	••••	172.34 177.08	4.74 APPLEYARD	WD
	Yard						A 3.20Am	•••••		A 11.05Pm			179.25	2.17 WEHATCHEE	wc
									1.50/1						-
	1						4.05 43.90	.05 32.88	4.50 37.07	5.00 35.85	4.10 41.86	.05 32.88		Time Over Subdivision Average Speed Per Hour	

Westward trains are superior to eastward trains of the same class, except as follows: Nos. 1 and 21 are superior to all trains. Nos. 2 and 22 are superior to all trains, except Nos. 1 and 21. Conditional flag stops.

Nos. 3 and 4 stop at any station between Spokane and Wenatchee to pick up or discharge revenue passengers from or to points south of Shelby, and from or to points east of Havre where Nos. 3 and 4 are scheduled to stop.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 9 THROUGH 16.

46 8. P. & S. No. 4 Daily	7.55 L 7.50 A 7.20	Daily As 8.45Am 8.35 L 8.30 A 7.55 7.49 7.38 7.33 7.27 7.23		22 5. P. & S. No. 2 Streamliner	2 Streamliner Daily A .45Pm .35 L .30 A .20 10.53 0.43 +0.38		Daily 11.00Am 10.50 10.45 10.35	Daily A 5.05Pm 4.55 4.50 4.40	460		BRKDNF TWOIXZY DNPIMVY RKDNP BWXVZ
B. P. & S. No. 4 Daily A 6.50Am L 6.43Am	Daily A 8.05Am 7.55 L 7.50 A 7.20 7.12 6.59 6.54 6.47 6.42 6.34	Daily As 8.45Am 8.35 L 8.30 A 7.55 7.49 7.38 7.33 7.27 7.23	Daily A 6.00Pm f 5.54 f 5.43 f 5.37	S. P. & S. No. 2 Streamliner Daily A 10.55Pm	Streamliser Daily A		Daily A 11.00Am 10.50 10.45 10.35	Daily A 5.05Pm 4.55 4.50	Daily A 2.30Am 2.20 2.15		BRKDNF TWOIXZY DNPIMYZ RKDNP
A 6.50Am L 6.43Am	A 8.05Am 7.55 L 7.50 A 7.20 7.12 6.59 6.54 6.47 6.42 6.34	As 8.45Am 8.35 L 8.30 A 7.55 7.49 7.38 7.33 7.27	A 6.00Pm f 5.54 f 5.43 f 5.37	Daily	Daily A .45pm .35 L .30 A .00 10.53 0.43		A 11.00Am 10.50 10.45 10.35	A 5.05Pm 4.55 4.50	A 2.30Am 2.20 2.15		TWOIXZY DNPIMV: RKDNP
A 6.50Am	7.55 L 7.50 A 7.20 7.12 6.59 6.54 6.47 6.42 6.34	8.35 L 8.30 A 7.55 7.49 7.38 7.33 7.27	f 5.54 f 5.43 f 5.37	2			10.50 10.45 10.35	4.55 4.50	2.20 2.15		TWOIXZ DNPIMV
A 6.50Am	7.50 A 7.20 7.12 6.59 6.54 6.47 6.42 6.34	L 8.30 A 7.55 7.49 7.38 7.33 7.27	f 5.54 f 5.43 f 5.37	2	L .30 A .00 10.53 10.43		10.45 10.35	4.50	2.15		RKDNP
L 6.43Am	A 7.20 7.12 6.59 6.54 6.47 6.42 6.34	7.49 7.38 7.33 7.27 7.23	f 5.54 f 5.43 f 5.37	2	10.53 10.43	••••••	10.35				
3	6.59 6.54 6.47 6.42 6.34	7.38 7.33 7.27 7.23	f 5.43 f 5.37	L 19.48rm	10.43			4.40	2.05		IDNOVS
3	6.54 6.47 6.42 6.34	7.33 7.27 7.23	f 5.37				10.22	4.27	1.52		IDNPY2
	6.42 6.34	7.23	f 5.31	1			10.15	4.20	1.45		P
	6.34				10.32		10.05	4.11	1.36		DNPV
			f 5.26		10,28		9.55	4.05	1.30		P
	6.26	7.17	f 5.19		10,22		9.40	3.54	1.20		P
		7.12	s 5.12		10.17		9.20	3.45	1.10		DPW N
<u> </u>	6.14	7. 00	f 5.05 f 4.58		10.05		9.00	3.29	12 ¹ 52		P IP
. I											
	6.04 5.54	6.51 6.43	s 4.48 f 4.38	······	9.55	• • • • • • • • • • • • • • • • • • • •	8.45 8.32	3.16 3.05	12.16 12.05Am	•••••	DNPV P
	5.49	6.38	f 4.36		9.47 9.42		8.23	2.58	11.58		P
	5.43	6.33	f 4.25		9.36		8.13	2.50	11.50		1PW
	5.35	6.26	f 4.16	 	9.30		8.01	2.40	11.40		P
	-5.28	6.21	s 4.08		9.25		7.51	2.31	11.30		DPN
	5.17	6.13	f 3.54		9.15		7.35	2.16	10.56		P
·	5.09	6.03	s 3.44		9.08		7.20	2.03	10.43		P DNPW
	5.01	1			9.01		7.05			••••••	YXO
	4.53	5.48	f 3.22		8.53		6.50	1.39	10.19		P
	4.48	5.43	f 3.14		8.48		6.40	1.30	10.10		₽¥
	a 436	e 532		 		•••••	6.20		27 9 50	•••••	P DNPW
		1	1		l						P
3	4.18	5.17	f 2.39		8.24	••••	5.59	12.55	9.15		P
	4.11	5.11	s 2.31		8.18		5.45	12.45	9.05		DNPW
	4.05	5.04	f 2.21		8.12		5.36	12,30	8.51		P
	3.55	4. 56	s 2.12		8.04		5.21			,	PW
1	3.43	1	f 1.57	·		•••••					DNJP
	3.38	4.39	f 1.51		7.48		4.50	11.25	8.03		P
1			f 1.49	ļ					7.50		DP
	į.	4.31	l	 	7.40 _460		4.40 28	11.10	7.50 1 7.400		BRKDN
		4.23 T. 4.204m					L 4.3UAm	L II.UUAM	L 7.40m		TWOM RKDN WXBJ
	i						6.30	6.05	6.50		-
	3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	5.09 5.01 4.53 4.48 5.3 5.3 6.4.24 6.4.18 6.4.18 6.4.18 6.4.11 6.4.05 6.3.55 6.3.43 6.3.38 6.3.38 6.3.38 6.3.38 6.3.30 6.3.20 6.3.20 6.3.20 6.3.20	5.09 6.03 5.01 5.56 5.48 5.48 5.43 6 4.48 5.43 6 4.48 5.32 6 4.24 5.22 6 4.18 5.17 6 4.05 5.04 7 3.55 4.56 7 3.30 4.31 7 3.20 4 1.20 4	5.09 6.03 s 3.44 5.01 5.56 s 3.34 4.53 5.48 f 3.22 6 4.48 5.43 f 3.14 5 3.07 6 4.36 s 5.32 s 2.58 6 4.24 5.22 f 2.47 6 4.18 5.17 f 2.39 6 4.05 5.04 f 2.21 7 3.38 4.39 f 1.51 7 3.30 4.31 f 1.57 8 3.30 4.31 f 1.57 8 3.30 4.31 f 1.57 8 3.24 4.25 s 1.35 9 1.30Pm	5.09 6.03 s 3.44 5.01 5.56 s 3.34 5.01 5.56 s 3.34 5.48 f 3.22 5.48 f 3.22 5.48 f 3.22 5.48 f 3.07 5.32 s 2.58 5.32 f 2.47 5.17 f 2.39 5.17 f 2.39 5.11 s 2.31 5.11 s 2.31 s 2.	5.09 6.03 s 3.44 9.08 5.01 5.56 s 3.34 9.01 6.03 s 3.44 9.01 6.03 s 3.34 9.01 6.03 s 3.34 9.01 7.05 s 3.34 9.01 8.53 s 8.48 8.53 8.30 s 3.07 8.48 8.30 s 3.07 8.29 8.35 s 4.18 5.17 f 2.39 8.24 8.35 s 4.18 5.11 s 2.31 8.18 8.40 s 3.51 s 8.18 8.12 8.35 s 4.24 s 2.21 8.04 8.40 s 3.34 4.43 f 1.57 7.52 8.35 s s 1.51 7.48 7.40 8.36 s 3.24 4.20 8.135 7.30 8.43 s 1.30 1.30 1.30 7.30	5.09 6.03 s 3.44 9.08 9.01 6.03 s 3.34 9.01 6.03 s 3.34 9.01 6.03 s 3.34 9.01 6.03 s 3.34 9.01 6.03 8.53	3.	4 5.09 6.03 s 3.44 3.08 7.20 2.03 2 5.01 5.56 s 3.34 9.01 7.05 1.52 3 4.53 5.48 f 3.22 8.53 6.50 1.39 3 4.48 5.43 f 3.14 8.48 6.40 1.30 3 4.48 5.43 f 3.14 8.48 6.40 1.30 3 4.24 5.22 f 2.47 8.29 6.10 1.04 4 4.18 5.17 f 2.39 8.24 5.59 12.55 4 4.11 5.11 s 2.31 8.18 5.45 12.45 5 4.05 5.04 f 2.21 8.04 5.21 12.01pm 6 3.43 4.43 f 1.57 7.52 4.59 11.35 3 3.38 4.39 f 1.51 7.40 4.40 11.10 1 3.24 4.25 s 1.30pm 1.30pm <td>5.09 6.03 s 3.44 9.01 7.05 1.52 10.32 10.43 10.45 10</td> <td>4 5.09 6.03 s 3.44 9.08 7.20 2.03 10.43 2 5.01 5.56 s 3.34 9.01 7.05 1.52 10.32 3 4.53 5.48 f 3.22 8.53 6.50 1.39 10.19 3 4.48 5.43 f 3.14 8.48 6.40 1.30 10.10 3 4.36 s 5.32 s 2.58 s 8.35 6.20 1.13 9.50 3 4.24 5.22 f 2.47 8.29 6.10 1.04 9.24 4 5.17 f 2.39 8.24 5.59 12.55 9.15 4 4.18 5.17 f 2.39 8.18 5.45 12.45 9.05 5 4.05 5.04 f 2.21 8.12 5.36 12.30 8.51 6 3.55 4.56 5 2.12 <</td>	5.09 6.03 s 3.44 9.01 7.05 1.52 10.32 10.43 10.45 10	4 5.09 6.03 s 3.44 9.08 7.20 2.03 10.43 2 5.01 5.56 s 3.34 9.01 7.05 1.52 10.32 3 4.53 5.48 f 3.22 8.53 6.50 1.39 10.19 3 4.48 5.43 f 3.14 8.48 6.40 1.30 10.10 3 4.36 s 5.32 s 2.58 s 8.35 6.20 1.13 9.50 3 4.24 5.22 f 2.47 8.29 6.10 1.04 9.24 4 5.17 f 2.39 8.24 5.59 12.55 9.15 4 4.18 5.17 f 2.39 8.18 5.45 12.45 9.05 5 4.05 5.04 f 2.21 8.12 5.36 12.30 8.51 6 3.55 4.56 5 2.12 <

Westward trains are superior to eastward trains of the same class, except as follows: Nos. 1 and 21 are superior to all trains. Nos. 2 and 22 are superior to all trains, except Nos. 1 and 21.

Conditional flag stops.

Nos. 3 and 4 stop at any station between Spokane and Wenatchee to pick up or discharge revenue passengers from or to points south of Shelby, and from or to points east of Havre where Nos. 3 and 4 are scheduled to stop.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 9 THROUGH 16.

4	sot	JTH	WARD)			SE	COND SUBDIVISION					NO	RTHW	ARD
	Cap	ar acity	THIRD	CLASS	SECOND	CLASS	8	Time Table No. 77	Calls	8		SECOND	CLASS	THIRD	CLASS
ger Sere	_		397	697	-	253	noe from	Effective January 14, 1951	Telegraph C	Distance fron Wenatchee	SIGNS	254		396	698
Station Numbers	Sidings	Other Tracks	Tuesday and Friday	Daily Ex. Sun.		Daily Ex. Sun.	Distance 1 Hedley	STATIONS	Tele	Dists Wens		Daily Ex. Sun.		Tuesday and Friday,	Daily Ex. Sat.
SG 128	Yard	11	L 2.01Pm				0,00	HEDLEY		192.98			•••••	▲ 11.30Am	•••••
SG 128	0	10	1 12.15				4.42	BRADSHAW	<u></u>	188.56				f 11.10	•••••
SG 110	38	88	s 1.00				17.68	18.26 KEREMEOS	K	175.80	D			s 10.30	•••••
	0	10	f 1.10				21.58	3.90 CAWSTON, B. C	 -	171.40				f 10.10	• • • • • • • • • • • • • • • • • • • •
8G 98	0	22	s 1.50				34.50	CHOPAKA, WASH		158.48	w			s 9.35	•••••••
8G 83	0	7	2.35				44.40	NIGHTHAWK		148.58	RKDWY			s 9.05	
SG 71	Yard	243	A 3.10Pm	L 5.00Pm		L 1.30Pm	55.74	OROVILLE	VR	137.24	BPXO	▲ 12.15Pm		L 8.30Am	▲ 4.15Am
WO 182	0	85		5.11		1 1.42	61.49	5.78 CORDELL		131.49		f 12.03Pm			3.55
WO 126	0	84		5.30		t 1.53	66.77	5.28 ELLISFORDE 5.93	 .	126.21		t 11.52			3.40
WO 120	0	71		6.00		s 2.05	72.70	TONÄSKET,	ON	120.28	DPW	a 11.40	· · · · · · · · · · · · · · · ·		3.25
WO 115	0	34		6.10		1 2.15	77.58	JĀNIS		118.48		t 11.30			3.10
WO 110	0	34		6.21		1 226	82.96	BARKER		110.02		1 11.19			2.55
WO 105	0	86		6.32		s 2.37	88.25	5.29 RIVERSIDE		104.73	w	s 11.08	· · · · · · · · · · · · · · · · · · ·		2.40
WO 100	0	85		6.42		t 2.45	92.48	CHEROKEE	ļ. 	100.55	·	t 11.00			2.25
WO 96	66	214		7.00		s 2.57	97.28		MK	95.70	BDPXY	s 10.50			2.00
WO 92	55	92		8.00		s 3.09	101.48	OKANOGAN	KN	91.50	DPX	s 10.35			1.30
WO 87	0	84		8.15		t 3.18	106.41	CHILÎÖWIST		86.57		1 10.20			12.50
WO 88	0	85		8.30		t 3.25	110.34	3.93 MALOTT	<u> </u>	82.64	P	1 10.13			12.30
WO 76	0	85		8.55		1 3.37	116.59	6.25 WAKEFIELD		76.39	w	1 10.00			12.01Am
WO 72	0	34		9.15		t 3.46	121.32	4.73 	 	71.66	P	9.50			11.40
WO 68	0	8		9.23		f 3.52	128.29	CHIEF JOSEPH	ļ	67.69		f 9.42			11.30
WO 65	50	61		10.00		в 3.59	127.99	2.70 BREWSTER 6.08	BR	64.99	DPX	9.35			11.20
WO 59	125	333		10.45		s 4.12	134.07	PATEROS	RO	58.91	DPWX	s 9.20			10.4 5
WO 58	0	84		11.01		t 4.22	139.54	5.47 STARR		53.44	P	t 9.00			10.00
WO 50	0	84		11.15		t 4.29	143.20	3.66 AZWELL		49.78	P	t 8.52			9.40
WO 44	0	85	,,	11.30		1 4.42	148.93	5.73 HUGO		44.05		r 8.40			9.20
WO 39	125	88		12.30Am		s 4.56	154.04		HN	38.94	DPX	8.30			9 .00
	0	78		1.30		s 5.00	155.20	CHELAN FALLS		37.78	X	s 8.19	·····		7.40
WO 82	0	40		1.50		t 5.13	161.05	5.85 STAYMAN	·	81.93	P	1 8.07			7.15
WO 26	0	48		2.10			166.97	5.92 WINESAP		26.01	 	t 7.55			6.55
WO 19	125	107		2.50		698 5.43	174.08	7.11 ENTIAT	NI	18.90	DPWX	7.40			5.43
WO 14	0	89		3.10		t 5.56	179.38	5.30 WAGNERSBURG		13.60	. 	t 7.28			5.20
WO 8	0	81		3.30		f 6.09	185.01	3.68 ZENA		7.97		t 7.17			5.10
WO 3	0	86		3.45		£ 6.19	189.49	≘ ₹ ∰		3.49		t 7.07			4.55
1648	1	1085		A 4.00Am			192.98	4.48 OLDS	wc	0.00	RKDNP B WXJ	L 7.00Am			L 4.45Pm
			3.09	11.00	l	5.00		Time Over Subdivision	-			5.15		3.00	11.00
			17.69	12.77		27.44		Average Speed Per Hour				26.14		18.58	12.29

Northward trains are superior to southward trains of the same class.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 9 THROUGH 16.

so	UTE	IW.	ARD				T	HIRD SUBDIVISION					NORT	HWAR	D 5
		ar acity			THIRD	CLASS	ош	Time Table No. 77	_	а		THIRD	CLASS		
on bers	_				703	701		Effective January 14, 1951	TelegraphCalls	noe from	SIGNS	702	704		
Station Numbers	Sidings	Other Tracks			Tu. Thur. and Sat.	Daily Ex. Mon.	Distance Nelson	STATIONS	Telegr	Distance Dean		Daily Ex. Sun.	Mon. Wed., and Friday		
SA 186					L 6.00Am		0.00	NELSON	вс	185.75	RDNWP		A 3.20Pm		
		T	RAINS E	BETWEE	N TROU	P JCT. A	ND N	ELSON BE GOVERNED BY	' C.	P. RY.	TIME T	ABLE A	ND RUL	ES	
SA 181	0	0			L 6.30Am		5.45	TROUP JUNCTION	 .	180.30	RYPV		▲ 2.45Pm		·····
8A 176	0	27			r 7.00		10.26	SOUTH NELSON		175.49	•••••		1 2.10		•••••
8A 169	0	8			£ 7.45		17.05	8.38 HALL	·····	168.70	•••••	•••••	1 1.40	•••••	•••••
SA 166 SA 159	0	15 16	•••••	•••••	f 8.00	•••••	20.38 27.50	7.12 YMIR.		165.37	w		f 1.25		
SA 109	-	10					27.00	4.86		100.20					
SA 155	0	9			r 8.50		31.86	BOULDER MILL		153.89			1 12.40		
SA 152	0	53			s 9.30	·· - ····	35.15	SALMO	SI	150.60	D	•••••	s 12.30		
SA 148	0	15			1 9.40		37.87	2.87 MEADOWS	·····	147.88			f 12.05Pm		•••••
SA 145 SA 140	0 7	20			f 9.55		40.74	4.08 PARKS	ļ	145.01 140.93			f 11.55		
5A 140	- -	-			1 10.25		41.02	5.60		140.00			1 11.35		
SA 186	0	15			s 10.45	ļ	50.42	FRUITVALE		185.88	w		s 11.10		
SA 180	0	7	· · · · · · · · · · · · · · · · · · ·		t 11.15		55.74	COLUMBIA GARDENS 8.88	ļ	130.01		· · · · · · · · · · · · · · · · · · ·	£ 10.45		
SA 127	0	20			s 11.40		59.57	2.11		126.18		·· · · · · · · · · · · ·	a 10.20		······
8A 126	0	39			f 11.50		61.68	BOUNDARY, U. S	·····	124.07			1 10.05	· • • • • • • • • • • • • • • • • • • •	
SA 116	60	89			s 12.40Pm		70.48	NORTHPORT	NP	115.27	PDYX		<u>s 9.30</u>		
8A 109	0	80			f 1.10		78.76		ļ	106.99	w		£ 8.25		
SA 107	45	0			r 1.20		80.06	DOLOMITE	ļ	105.69	P		f 8.20		
SA 96	0	16	,		f 1.55		90.24	BOSSBURG	ļ	95.51	· · · · · · · · · · · · · · · · · · ·		f 7.50		
SA 93	39	92	· · · · · · · · · · · · · · · · · · ·		1 2.10		94.11	EVANS 9.91		91.64	RKDNW		f 7.35		
SA 82	Yard	200			A 2.50Pm	L 4.40Am	104.02	KETTLE FALLS	MF	81.73	BYXOJP	A 2.30Pm	L 7.00Am		
SA 77	0	13		 		r 5.10	109.43	PALMERS	ļ	76.32		£ 2.00			
SA 73	0	114				s 6.00	112.48		VD	73.27	PD	1.35			
SA 71	0	8				e 6.20	116.28	ORIN		69.47		1 1.05			
SA 67	40					f 6.40	118.98	ARDEN	ļ	66.77	P	1 12.45			
SA 59	0	20				1 7.15	126.37	ADDY	<u> </u>	59.38	•••••	1 12.15Pm			
SA 50	81	120				9.00	135.58	9.21 CHEWELAH	СН	50.17	PDXZW	s 1 <u>1.3</u> 0			
SA 43	40	49				• 10.30	143.15	7.57 VALLEY	VY	42.60	PDYX	• 10.30			
SA 38	0	80				1 11.00	148.39		 .	37.36	P	r 9.30			
SA 34	0	18					151.82	3.43 CLINE	ļ	33.93		f			
SA 88	39	17				r 11.30	153.09	SPRINGDALE		32.66	PW	r 9.05			
SA 25	40	5				r 11.59	161.20	8.11 LOON LAKE		24.55	P	r 8.30			
SA 18	0	68				r 12.30 m	1	6.80 CLAYTON		17.75	P	f 8.00			
SA 18	50	49				s 1.00	173.27	DEER PARK	DE	12.48	PDXW	7.30			
8A 9	0	20				f 1.20	176.86	3.59 DENISON		8.89		r 6.25			
8A 4	40			·······		f 1.40	181.98			3.77	P	r 6.10			
1460	Yard	72				▲ 2.10Pm	185.75	3.77 DEAN	SF	0.00	JRDNX	L 6.00Am			
					8. 50 11.77	9.80 8.60		Time Over Subdivision Average Speed Per Hour				8.30 9.60	8.20 12.48		
		- '												,	<u> </u>

Southward trains are superior to northward trains of the same class.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 9 THROUGH 16.

б	WE:	STV	VARD]	FOURTH SUBDIVISION	ON			E	ASTW	ARD
on the contract of the contrac	Cap				noe from e Falls	Time Table No. 77 Effective January 14, 1951	Telegraph Calls	Distance from Republio	SIGNS			
Station Numbers	Sidings	Other Tracks			 Distand Kettle	STATIONS	Teleg	<u> </u>				
SA 82	Yard	200		 	 0.00	KETTLE FALLS12 10	MF	80.68	ORKDNB JWYXP	 		
SD 12	0	24		 	 12.10	BÖŸĎS 5.34	ļ	68.58		 		
8D 17	0	81		 	 17.44	BARSTOW		63.24		 		
SD 22	0	81		 	 22.67			58.01		 		
SD 24	0	7		 	 24.22	1.55 ORIENT	 	56.46	P	 		
SD 29	0	12		 	 28.55	4.38 GOLDSTAKE		52.13		 		
SD 85	0	18		 	 34.64	LAURIER, WASH	ļ	46.04		 		
SD 46	0	7		 	 45.98	GRAND FORKS, B. C	GR	34.70	Y V	 		
SD 49	0	40		 	 49.06	DANVILLE, WASH		31.62		 		
8D 53	0	11		 	 53.19	4.13 HURLBURT		27.49		 		
8D 59	0	48		 	 59.48	6.29 CURLEW		21.20	w	 		
SD 65	0	88		 	 65.56		·	15.12]		
SD 72	0	18		 	 72.10	POLLARD		8.58		 		
8D 76	0	84		 	 75.78	TORBOY		4.90		 		
8D 81	Yard	88		 	 80.68	REPUBLIC	z	0.00	X B RKD Y	 		
						Time Over Subdivision Average Speed Per Hour	-					

Westward trains are superior to eastward trains of the same class.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 9 THROUGH 16.

	SOT	JTH	WARD)			FI	FTH SUBDIVISION				N	ORTHV	VARD
	Cap	ar acity]	ĭ	ı	1	from	Time Table No. 77	from River			1	1	1
Station Numbers	Sidings	Other Tracks					Distance from Mansfield	Effective January 14, 1951 STATIONS	Distance from Columbia River	SIGNS				
	iš	δË	1									 1	1	
CR 60 CR 55	Yard 0	48 80					0.00 5.40	MANSFIELD 5.40 TOUHEY	60.39 54.99	PXRY P		 		
CR 49	0	50						5.98 WITHROW 5.56 SUPPLEE	49.01 43.45	p	••••••	l		
CR 44 CR 86	0	80 62						6.99		77		1		
CR 31	0	80						9.84		P	•••••	 		•••••
CR 21 CR 16	0	24 35						McCUE 5.58 PALISADES	21.35 15.77	P P		 ł		
1632	Yard	53					60.39	COLUMBIA RIVER	0.00	RPWNJ		 		
								Time Over Subdivision Average Speed Per Hour						

Northward trains are superior to southward trains of the same class.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 9 THROUGH 16.

WI	EST	WA.	RD				SD	KTH SUBDIVISION					EAS	STWAI	RD.	7
Pi	Caj	ar						me Table No. 77	okane	q <u>d</u>	1		-			_
Station Numbers	Sidings	Other Tracks					_	STATIONS	Distances from Spokane	Telegraph Calls	Signs					_
8B90	Yard		1	<u> </u>	1	 	<u> </u>	Moscow	88.90	<u></u>	BRKDYXV				<u> </u>	-
8B82	-	12	 -	-	·	 		VIOLA	80.90							
SB76	18	105	┨	-	-			PALOUSE	74.42	PA	DYXV				 -	
SB71	1	10	1			-	-	GRINNELL	69.56							
8B69		12	·			-		LADOW	67.47							-
	-	-	·			- 	N. P.	& U. P. R. R. CROSSINGS	63.87		м					
SB65	16	22	 		-	-	-	GARFIELD	63.50	GF	DV					-
SB61		9	 	_	-	-		CRABTREE	59.49							
SB57		18	1			-		sokulk	55.87							
	1		1	- 				N. P. R. R. CROSSING	52.35		М					
	-	-		-	-	- 	-	U. P. R. R. CROSSING	52.84		М					—
SB58	11	47	<u> </u>	-			- 	OAKESDALE	51.69	KA	D₹					
8B50	-	18	1			-	- 	GEARY	48.48		<u> </u>			·		
8B45	-	28			 	-	_	FAIRBANKS	48.81							
8B40	28	59	-	-	-		_ !	SPRING VALLEY	38.58		XRYOJ					
SB34	12	17	-]		-	┧	-	810 WAVERLY	82.58	WA	D		······································			
8B30	-	15	-		-	-		WEST FAIRFIELD	28.97							—
8B25	23	16		-		-	_ i	MT. HOPE	23.65	I						-
8B19	11	-	-	-	-		_	FREEMAN	17.95				 		-	—
8B17	- 	18		-	 			VALLEY FORD	15.40					-		—
8B15	18	-	 		 			EXCELSIOR	13.63							-
8B 9	17	-[-			5.76 PARKVIEW	7.87							
8B 8	 		-	_	-			MORAN	6.37				· · · · · · · · · · · · · · · · · · ·			
1	-	┤╌	-	-	-	-	_	INLAND JCT	0.14		JXY		·			
SB. O.	Yar	d Yar	al	-	 	-		SPOKANE	0.00	DS	DNKORYX					
			-					Time Over Subdivision			ZVB				<u> </u>	
		1	<u> </u>		1	1		Average Speed Per Hour	١	l .	<u> </u>	<u> </u>		<u> </u>	<u> </u>	
					Wes	tward tr EE ADDIT	ains are s IONAL SPI	superior to eastward trains ECIAL INSTRUCTIONS PAGE	of the	e same ROUGH	class. 16.					
EA	ST	VAI	RD.					ENTH SUBDIVISIO					N	ESTW	ARI	<u> </u>
	Ca	_		TH	IRD CLA	SS			1	_			THIRD	CLASS		
	Capa							Time Table No. 77	Bine Bine	Call		A =				
		_					96	Effective January 14, 1951	S 28	d d	Signs	95				
n pe	8	P S					Daily		- gg	a de	1	Daily				
Station Numbers	Sidings	Other Tracks					Except Sat. & Sun.	STATIONS	Distances from Spok	Telegraph (Except Sat. & Sun.				
		<u></u>		<u> </u>			1			i	XRKDY	n i		i		_
11	Yard						L 3.00Pm	l 1.50	30.94	CA	VZ	▲ 10.50Am			<u> </u>	
SC31		57		<u> </u>			Af 3.10Pm	l	29.44			Lf10.30Am		<u> </u>	<u>L</u>	
		В	ETWEEN SP	OKANE BRID	GE AND G	BBS, A DIS		1.84 MILES, C.M.ST. P. & P. RY. TI		E AND S	PECIAL INS		WILL GOVE	RN		
SC19	18	[L# 4.10Pm	SPOKANE BRIDGE 5.64 GREENACRES	17.50	 	_ 	A1 9.30Am				
8C13-B		12					1 4.35	0.78	11.86		-	f 9.10			 	
8C13		7					1 4.40	FLORA	11.13	 	X	1 9.00			.	
SC7		7		<u> </u>			£ 5.00	1.03	5.82	-	X	1 8.25				
8C6	27					 	f 5.05	ORCHARD AVE	4.79	 	-	f 8.20			<u> </u>	
8C5							1 5.15	PARKWATER	8.87	·	-	f 8.15			<u> </u>	
SC2		117						u. P. R. R. CROSSING	0.85	-	M				<u> </u>	
8B2	15	- 5						INLAND JCT	0.14		JXY DNKORY					
SB O	Yard	Yard					A 5.30Pm	SPOKANE	0.00	DS	XZVB	L 8.00Am				
							2.80 12.87	Time Over Subdivision Average Speed Per Hour				2.50 10.92				
			Es	stward to	ains are	superior		ward trains of same class ECIAL INSTRUCTIONS PAGE	except	No. 95	is super		. 96.	·		
<u> </u>					S	EE ADDIT	IONAL SP	ECIAL INSTRUCTIONS PAGE	S 9 TH	ROUGH	16.					

8 V	VES'	TW.	ARD				EIGHTH SUBDIVISION	ON				EASTW	ARD
Station Numbers	Capa Capa suipig	Other Appropria					Time Table No. 77 Effective January 14, 1951 STATIONS	Distances from Spring Valley	Telegraph Calls	Signs			
W77	Yard	49			<u> </u>	1	COLFAX	36.73	СО	YXRKD	1]
							U. P. R. R. CROSSING	36.44		М	 		
W65	30	26						24.59					
W60		29					STEPTOE 4.76	19.83					
W55		28					THORNTON	15.27					
							0.57 U. P. R. R. CROSSING	14.70		M			
W46	10	29					ROSALIA	5.75	RO	D₹			
8B40	29	59					SPRING VALLEY	0.00		JXRYO			
							Time Over Subdivision Average Speed Per Hour						

Westward trains are superior to eastward trains of the same class.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 9 THROUGH 16.

SPECIAL INSTRUCTIONS

ALL SUBDIVISIONS

1. INSTRUCTIONS GOVERNING THE OPERATION OF STREAMLINER TRAINS.

CLEARING OF STREAMLINERS.

The time of No. 1 must be cleared by westward first class trains not less than 5 minutes before No. 1 is due to leave the last station where time is shown, and by other westward trains not less than 10 minutes before No. 1 is due to leave the last station where time is shown.

The time of No. 1 must be cleared by eastward first class trains, except No. 2, not less than 10 minutes at all stations, and by other eastward trains not less than 15 minutes.

The time of No. 2 must be cleared by eastward first class trains, except No. 22, not less than 5 minutes before No. 2 is due to leave the last station where time is shown, and by other eastward trains not less than 10 minutes before No. 2 is due to leave the last station where time is shown.

The time of No. 2 must be cleared by westward first class trains, except No. 1, not less than 10 minutes at all stations, and by other westward trains not less than 15 minutes.

Within yard limits, yard engines and light engine movements must clear the main track not less than 10 minutes before Nos. 1, 21, 2 and 22 are due to leave last station where time is shown.

MAXIMUM SPEED OF STREAMLINERS.

Maximum speed of Streamliner trains, consisting of Streamliner cars hauled by Diesel engines, will be designated by distinctive reflectorized roadway signs in the shape of the letter "D".

Except as directly affected by speed restrictions under Items 1 and 2, All Subdivisions, the "D" signs designate zone speed territories and the numerals thereon indicate in miles per hour the maximum permissible speed which will govern until the next zone is reached.

Between Hillyard and Fort Wright, Streamliners will also be governed by speed restriction as indicated under Item 2, First Subdivision.

Where the movement is from a higher to a lower speed zone the zone sign is located approximately one mile from the point where the lower speed becomes effective. When the movement is from a lower to a higher speed zone the zone sign is located at the point where speed may be increased. Zone territories are listed herein for the convenience of employes.

MAXIMUM SPEED EXCEPTIONS:

When a Streamliner is detoured over Great Northern tracks outside of regular Streamliner territory, the Streamliner must not exceed the maximum permissible speed for other passenger trains in the territory operated.

When Streamliner is operated against the current of traffic in double track territory the Streamliner must not exceed the maximum permissible speed for other passenger trains. This does not modify Rule 93.

When Streamliner is handled by steam engine, or when other passenger trains are operated on Streamliner schedule, or when train consists of mixed Streamliner and conventional type equipment, the train must not exceed maximum permissible speed for other passenger trains in territory operated.

In event of failure of the electric straight air brakes, or if electric brakes cannot be used on account of cars not equipped with electric straight air brakes being handled in the train, the automatic air brakes will be used and Superintendent notified. In this event speed of train will not exceed the maximum permissible speed for other passenger trains.

ZONE TERRITORIES AND MAXIMUM SPEED OF STREAM-LINERS.

LINERS.	_				1 1 4 7 7 7 7
	Zone	e Te	rritories	Maximum S	peed MPH
Stations	Betwe	en l	Mile Posts	Maximum S Westward	Eastward
			1470.5		55
	1470.5	"	1472.5		50
Hillyard		44	1473.6		35
Spokane		64	1477.5		20
	1477.5	44	1478.1		12
	1478.1	"	1479.4		30
Ft. Wright	1479 4	"	1479.8		40
	1/70 R	"	1489.1		45
Lyons	1489.1	"	1514.5		75
Canby	1514 5	66	1520.6		60
Bluestem	1520.6	"	1520.7		50
Digestem	1520.7	"	1522.2		50
	1522.2	**	1522.8		45
Harrington		"	1529.0		50
Harrington	1520.0	"	1542.0		55
Lamona	1549.0	66	1542.1		35
Odessa	1542.0	"	1556.7		65
Ouessa	15567	66	1559.0		60
Marlin	1556.7	66	1571.9		65
Marin	1571.9	46	1572.1		55
	1572.1	66	1573.2		65
Wilson Creek		"	1579.1		70
Wilson Creek	1579.1	"	1587.9		75
	1587.9	46	1588.4		70
Adrian		"	1618.3		75
	1618.3	"	1620.7		55
Crater	1010.3	46	1622.8		45
Crater	1622.8	"	1623.6		35
Trinidad		"	1628.5		45
		**	1640.7		60
	1628.5	"	1642.3		35
Rock Island		44	1646.8		60
Malaga	1646.0	46	1650.2		55
Wenatchee		66			45
	1650.2		1653.3	45	45

2. SPEED RESTRICTIONS GENERAL.

(a) Maximum permissible speed of passenger and freight trains, except Streamliners, will be designated by distinctive reflectorized roadway signs set in an upward angle of 45 degrees.

Except as directly affected by speed restrictions prescribed below and other speed restrictions covered by Item No. 2 under individual Subdivisions, the 45 degree signs prescribe the speed territories and the numerals thereon indicate in miles per hour the maximum permissible speed which will govern until the next territory is reached.

When the movement is from a higher to a lower speed territory the 45 degree sign is located approximately one mile from the point where the lower speed becomes effective. When the movement is from a lower to a higher speed territory, the 45 degree sign is located at the point where speed may be increased.

When operating against the current of traffic in double track territory, trains must not exceed the maximum permissible speed prescribed by the 45 degree sign with the current of traffic. This does not modify Rule 93.

When the 45 degree sign has two sets of figures, the numerals preceded with letter "P" apply to passenger trains, except Streamliners, and letter "F" to freight trains.

- (b) When passenger trains are handled by freight engines or when freight cars, except cars equipped with passenger trucks and steel wheels, are handled in passenger trains, the train will not exceed maximum permissible speed for freight trains in the territory operated.
- (c) Speed shown on Speed Limit Plate on engines must not be exceeded.
- (d) Steam engines backing up _______ 20 MPH Steam engines in forward motion running light or with caboose only ______ 35 MPH Diesel and Electric engines light or with caboose only 50 MPH

L			
	Trains handling steam derricks, pile drivers, ditchers, cranes, steam shovels, dozers, etc. on Main Lines	25 MPI	Ŧ
	cranes, steam shovels, dozers, etc. on Main Lines except on 6 degree curves or sharper, and on Branch	15 MPI	J
	Lines Trains handling carload poles or piling on open cars when operating on double track, siding or other adjacent track must stop meeting or being passed by Passenger Trains, for other trains reduce	19 MIFI	1
	speed to	10 MPI	E
	Trains handling ore cars or air dump cars loaded with ore or gravel and scale test car on Main Lines	20 MDI	7
	except on 6 degree curves or sharper, and on Branch	20 MPI	
	Unless conditions require a further speed restriction,	20 MIT	1
	trains or engines moving against the current of	4 F 3 F D T	
	traffic on double track thru interlockings	15 MPI	.1
	points of spring switches	35 MPI	I
	Trains or engines moving in facing point direction at spring switches without facing point lock	25 MPI	E
	Trains or engines thru No. 20 turnouts at:	35 MPI	H
	Hillyard, end of double track east and west end of Fort Wright, end of double track.	yard.	
	Fort Wright, SP&S Junction.		
	Bluestem, end of double track. Lamona, end of double track.		
	Trains or engines thru No. 15 turnouts at:	25 MPI	Ε
	Lyons, east and west siding switch. Galena, east and west siding switch.		
	Espanola, east and west siding switch.		
	Edwall, east and west siding switch. Lamona, east siding switch.		
	Nemo, east and west siding switch.		
	Odessa, east and west siding switch. Irby, east and west siding switch.		
	Wilson Creek, east and west siding switch.		
	Stratford, east and west siding switch.		
	Adrian, east and west siding switch. Ephrata, east and west siding switch.		
	Quincy, east and west siding switch.		
	Trinidad, east and west siding switch. Voltage, east and west siding switch.		
	Wenatchee, east and west crossover switch west	t end o	f
	yard. Trains or engines thru all other turnouts	15 MPI	Ε
3.	MOVEMENT OF ENGINES DEAD IN TRAINS.		
	Class O and larger engines will be placed not to exceed	l 15 car	s
	behind road engine. In electrified zone only class R will be handled on head end, all others near rear.	engine	S
	Class F-8 and smaller engines will be placed next	ahead o	f
	caboose.	م امالت	
	Diesel and Gas-Electric engines 2300-2341 must be ha rear of train.		11
	Not less than five cars will be placed between all enging Trains handling Great Northern steam engines dead	nes. in trai	n
	with side rods on both sides will not exceed 40 MPH;	and with	l-
	out side rods will not exceed 10 MPH. Trains handling foreign line steam engines with side both sides will not exceed speed designated by Superin	rods o	n
	and without side rods will not exceed 10 MPH.		
	Engines that have any of the truck or driving wheels will not be moved in a train without authority of Superin	remove	d
	will not be moved in a train without authority of Superii Trains handling Electric, Diesel and Gas-Electric engin	ntendent es in tov	Ū. ₩
	dood in those will not orgood tollowing concode:		

dead in train will not exceed following speeds: Engine Number 1 to 23-75 to 170-253 to 258-262 to 264, 272

to 277, 301 to 310, 400 to 456

175 to 227-600 to 653

250, 251, 260, 261, 266 to 270, 350 to 365.

500 to 512

252 & 259, 265, 300

2300 to 2324

2325 to 2341

5000 to 5008-B

5010 to 5019

Maximum Speed

50

35

65

75

45

50

60

45

- 4. Under Rule 2, watches that have been examined and certified to by a designated inspector must be used by train dispatchers and yardmen.
- 5. Brakemen with less than one year of experience should not be used as flagman except in emergency, and then Superintendent will be notified by wire.
- 6. When operating snow machines in non-block signal territory, no train should be permitted to follow closer than a station apart; when that cannot be done, they will be blocked not less than thirty minutes apart.
- 7. After severe blizzard or dirt storm, employes on first train over road must exercise care to avoid accident caused by striking drift without first having drifts faced with hand shovels, cutting in far enough to get beyond the hard snow and giving a perpendicular wall to strike against instead of slope or wedgelike shape. When operating snow dozer conductor in charge will ride in the dozer. On snow and dirt dozers every precaution must be taken to see that cage, flangers and wings clear all obstacles when in service and are properly secured when in thru trains, and dozers properly turned. Hand screws must be tightened to raise flanger on dozers as high as possible before making a back-up movement, and must not be released until the dozing work is actually to start. Hand screws holding the cage on dozers must be tightened or chains otherwise fastened except when dozer has air in cylinders and is attended by an employee.
- 8. Loaded dump cars should not be handled on double track after dark, but if necessary to do so, close watch must be kept by trainmen and if a car dumps its load, train must be stopped and protection afforded on the opposite track.
- 9. Omitted.
- 10. Trains 1, 2, 3, 4, 7 and 8 carry 100 ft. of steam hose in two 50 ft. lengths equipped with standard Vapor and engine steam dome connections for emergency use in event of steam failure on train engine and non-steam train line engine furnished to handle train. In case of steam line failure on a car, connect both hoses together to run around such car so can be taken to first terminal, using combination standard Vapor and steam dome connections attached to reel. Car must be drained before proceeding.
- 11. Unless otherwise provided, when passenger trains are operated against the current of traffic on double track or through sidings, conductors shall notify Railway Postal Clerks, trains shall stop at points where U. S. Mail is usually picked up and conductors are responsible for delivery of mail to Postal car.
- 12. Conductors will report by wire all flat spots on wheels of passenger cars. Any cars having flat spots on wheels of more than two and one-half inches long must be set out.
- 13. Due to limited overhead clearance at tunnels and structures, employes are warned to keep off top of cars of extreme height and width when handled in trains and yards, also such standing cars in electrified zone, except in emergency. In absence of previous advice on such cars, wire proper officer for instructions.
- 14. The Railway Company is responsible for proper handling of perishable freight on road and at points where Western Fruit Express Company do not maintain representatives. Conductors on trains handling perishable freight will ascertain from waybills class of service required and light or extinguish heaters and manipulate vents in accordance with current instructions provided for handling perishable freight issued by the National Perishable Freight Committee.
- 15. Placarded loaded tank cars moving in through freight trains must be placed not less than 6th car from engine or caboose; cars placarded "Explosives", "Inflammable", or "Corrosive Liquids", not less than 16th car from road engine, one car from

helper engine and 11 cars from caboose. These cars may be handled second car from engine or caboose in local trains. These cars must not be placed in trains next to each other, next to refrigerators equipped with gas burning heaters, stoves or lanterns, or flat cars loaded with logs, poles, lumber, pipe, rails, iron, steel, and gondola cars with such lading higher than ends, or cars of similar lading that is liable to shift

Carload express shipments of explosives, sealed and placarded, may be handled on passenger trains; LCL shipments may be made in so-called peddler car with messenger in charge when such car is assigned to the handling of express and baggage ex-clusively, provided shipments are accompanied by authorized representative of United States Government while on trains.

Terminals or pick-up points enroute must furnish conductor and engineer Form 250 showing consecutively location in train of all cars placarded "Explosives". At points other than terminals where crews change notice will be transferred from crew to crew.

Further details governing handling of Explosives, Inflammable and Corrosive Liquids may be found in I.C.C. Regulations.

16. Gas-Electric engines must not be fueled while occupied by passengers, or coupled to cars occupied by passengers.

The normal position of a spring switch with facing point lock is identified by a color light type signal displaying a "lunar white" light for train or engine movements in a trailing point direction and for movements in facing point direction when conditions require.

The normal position of a spring switch without facing point lock is identified by a triangular yellow target on switch stand with letter "S" in black, and "lunar white" light in switch lamp in place of green light displayed in both directions thru or over

Trains departing from stations, either from siding or main track in trailing point movement actuating points of spring switches, a member of crew must observe indication of governing signal in opposite direction after rear end of train has passed thru switch to ascertain if switch points return to normal position. If this signal indicates Stop and no immediate train movement or other cause is evident report the fact to Superintendent from first available point of communication.

During and immediately following snow storms or violent wind storms, spring switches must be operated by hand and relined to normal position before heading out through switch in trailing point movement, actuating switch points, to insure switch is in

proper operating condition.

INDICATORS AT SPRING SWITCHES.

A Switch Indicator, consisting of a single yellow light unit (normally dark) and a switch-key-controller mounted on an iron mast located at clearance point of a siding, must be operated by a member of the crew who, together with engineer, must observe and be governed by its indication before fouling main track or making movement from siding to main track thru a spring switch in automatic signal territory, unless the movement is made immediately after an opposing train has passed the switch and Automatic Signal at leaving end of siding indicates "Proceed".

If Indicator displays a yellow light when switch-key-controller is operated, train or engine movement to main track may be made immediately in accordance with train rights and operating rules. Display of yellow light must continue until leading wheels have passed clearance point.

If Indicator does not display a yellow light when switch-keycontroller is operated, train or engine movement to main track may be made in accordance with train rights and operating rules, after operating spring switch by hand; waiting three minutes and taking every precaution to provide proper pro-

To operate Switch Indicator, insert switch key in controller and turn clockwise toward "R", hold a few seconds and remove key. If yellow light is displayed and intended movement is not made, insert switch key in controller and turn counter-clockwise to-ward "N" to restore signal system to normal condition to avoid delay to trains on main track.

Switch-key-controller must never be operated toward "N" after having been operated toward "R" if intended movement to

main track is to be made.

- 18. DRAGGING EQUIPMENT DETECTOR INDICATOR consists of a single white light unit (normally dark) with a circular background mounted on signal or other mast. When white light is displayed, train must be stopped and inspected for drag-ging equipment. Notify Superintendent from first available point of communication.
- 19. Facing point locks on hand operated switches are indicated by a six inch yellow stripe painted on target staff. Be positive locking device is restored to normal position after using. A running switch must not be made thru this type switch.
- 20. Under Rule 24, engine number only will be displayed in indicators on engines so equipped. This will also apply when our engines are operating over Northern Pacific tracks. Between Klamath Falls and Chemult, Southern Pacific rules will govern.
- 21. Rule 204(A) prescribes that copies of train orders will be furnished the rear trainman, such orders will only be furnished on trains designated: Nos. 1, 2, 3, 4, 7, 8, 9, 10, 28, 29, 30, 355, 358, 359, 360 and sections thereof; also extra passenger train whether operated as section of regular train or as a passenger extra.
- 22. Air hose on Diesel and Electric engines must be hooked up in hose fastener when not in use.
- 23. Before leaving any engines terminal, enginemen will make proper tests and inspections of water glasses, gauge cocks, water column and injectors, and will not leave the terminal unless all these are in proper working order. Should enginemen on steam engines find that the water is not in sight in water glass, and if water cannot be raised to bottom gauge cock or water glass by opening throttle, on oil burning engines the fire must be extinguished immediately, and on coal burning engines the fire must be knocked out or smothered to the extent there will be no damage done to the crown sheet. water can be raised to the bottom gauge cock or water glass the water level should be built up by use of the pump, or injector, or

Should the low water alarm whistle blow, on any engine so equipped, enginemen will immediately ascertain where the water level is in the boiler by blowing out water glasses and the water column, and being sure that water glass mounting valves are open and if water cannot be raised to the bottom gauge cock or water glass by opening throttle, enginemen will be governed by

instructions in the preceding paragraph.

24. ON ENGINES, PASSENGER, FREIGHT AND ORE CARS EQUIPPED WITH ROLLER BEARINGS, EMPLOYES WILL **BE GOVERNED AS FOLLOWS:**

Roller bearing failures on cars or engines equipped with roller bearings in the journal boxes may be due to lack of oil. If the box is not blazing, the oil plug in the cover should be removed and engine or valve oil added. Oil must never be added to a box that is blazing. After the oil has been added and plug replaced, the train should proceed at reduced speed and care exercised until it is apparent that the box will run cool. If fire develops in roller bearing box on any equipment, it must be closely watched, train moved slowly, and Superintendent notified from first available point of communication, who will prescribe for the movement.

Some engines and cars equipped with roller bearings have heat indicators or stench bombs inserted in the housing of boxes which release a strong pungent odor in the event of excessive journal box temperatures. When this odor is detected train must be stopped at once and box located. Compare the temperature of this box with the other boxes on the same engine or car, check the oil level, and if there is no evidence of overheating, train may proceed, but if the box is overheating, proceed only as instructed in the preceding paragraph.

Ore cars equipped with roller bearings have box cover painted orange, four inch white stripe full length of car beneath stencilled name, "GREAT NORTHERN", and "TIMKIN ROLLER BEARINGS" stencilled in black across center of white stripe. Cars or engines equipped with roller bearings must not be allowed to stand alone, even on level track, without brakes adequately applied.

NCY RED HEADLIGHT will be imported by or night when a train is disabled or nergency application of air brakes or actor find it necessary to stop train a might cause accident, over-running and waiting points, end of double ng train observing display of emergatop before passing and be governed operating on adjacent track, ascertain hen proceed at restricted speed until NCY RED REAR END LIGHT is of ntrol—Portable Manual Control—and ed, must be displayed by day or night a running at speed less than 18 MPH. Internatically functions in this manner, ing at speed above 18 MPH and movin which it might be overtaken by and during foggy and stormy weather, and with emergency switch and emercially with emergency switch and emercially with emergency switch and emercially and the most of train of the passed of the pas
y or night when a train is disabled mergency application of air brakes netor find it necessary to stop train might cause accident, over-running and waiting points, end of doubt and train observing display of emerstop before passing and be govern operating on adjacent track, ascertate hen proceed at restricted speed un NCY RED REAR END LIGHT is netrol—Portable Manual Control—at ed, must be displayed by day or night running at speed less than 18 MP atomatically functions in this manual in which it might be overtaken and during foggy and stormy weather and the section prescribed by rule. IN ANY WAY RELIEVE ENGIN FROM RESPONSIBILITY OF COMPAND 102. The properties of train run; when switch rear; when on siding to be pass in another train operating on adjace

Portable light must be removed before coupling to rear of such

Oscillating white light on engines will be displayed in addition to standard headlight governed by Rules 17 and 17(B). In case of headlight failure it can be used as emergency headlight or as a focus light by push button control if desired.

Enginemen and trainmen on trains and engines equipped with oscillating emergency red lights must familiarize themselves with the operation of the lights.

26. Omitted.

27. Rule D-97 is in effect on this division.

28. Trains handling flat or skeleton cars loaded with logs must stop at appropriate locations immediately before passing over through truss bridges or through tunnels and make thorough inspection of all cars of logs in their train, making certain train and lading are in safe condition before proceeding. Extra stops en route will be made for this purpose when in the judgment of the conductor it is necessary.

Trainmen must maintain watch behind their trains for logs that

may have rolled off cars and if main track is fouled take prompt

action to protect trains.

On double track, conductors must notify train dispatcher when logs are to be handled and the log train must be at stop when being passed by other trains, except that when two trains handling logs are passed, either one should stop until the other train has pulled by whether on siding or double track.

On single track, trains handling logs must be at stop when meeting or being passed by passenger and freight trains, except when there are more cars than siding will hold, it is permissible for log train to pull by such trains at restricted speed.

In electrified zone and double track territory, logs must be secured to cars by chains or cables, except between Hillyard and Fort Wright.

Unless conditions require further speed restrictions, trains handling logs must not exceed 25 MPH.

29. Red signs on frost boxes of water and oil tanks. In case of emergency, close large valve in frost box.

EMERGENCY TELEPHONES. Spokane, when stopped by Stop-indication at automatic block signal 1475.3, telephone before blocking street crossings— Fort Wright, east end bridge 274 Booth
Fort Wright, west switch Booth

Lamona, east of water tank	Booth
end double track	Booth
Wilson Creek, west switch	Booth
Middle of siding	
Ephrata, east wye switch	Booth
Trinidad, water tank	Booth
West switch	
Gravel spur	Pole booth
Appleyard, east lead switch	Pole booth
Wayside	
Clayton	
Loon Lake	
Springdale	
Grays	
Addy	
Arden	
West Kettle Falls	Booth
Evans	
Marble	
Orient Danville—1 mi. west	Customa office
CurlewMillwood Transfer track	Dooth
Flora Jet.	
Greenacres	
Spokane Bridge	Booth
Coeur d'Alene, MP 32	
Gibbs	
Rock Creek Bridge	Booth

FIRST SUBDIVISION

(Main Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS. Other

	Between	Passenger	Freigh	ıŧ
	Hillyard and Lyons			
	Twong and Wanatahaa	GE MINIT	40 1/11	÷
	Lyons and Wenatchee	OD MPH	40 MP1	1
2.	SPEED RESTRICTIONS.			
,	Spokane, all trains approach crossover east	of bridge	270. an	ď
	crossover west of Howard Street at restricte		,	_
			~ 3.6TOT	•
	Spokane, over scissors crossover S-2		5 MPI	
	Spokane, public crossing Howard Street		12 MPI	£
	other public crossings		20 MP	Ħ
	Bridge 270, Spokane, R, SP&S E-1, Z-6			
	Bridge 273, Spokane, Q-1, S-1, N-3, SP&S E			
	R, SP&S Z-6		10 MP	1
	Bridge 274, Fort Wright, Q-1, R, S-1, N-3,			
	SP&S E-1, Z-6		20 MPI	Ι
	Between Galena and East Galena:			
	All trains on straight track		15 MP3	Ŧ
	on curves and public crossing			
	Ephrata, 2.2 miles east of, Army Air Depot s			
	Between Home Signals of Interlocking at:		20 MP	Ε
	Spokane, U.P.R.R. Crossing.			_
	_ ,	TD LOVO		
- 3.	ENGINE RESTRICTIONS ON INDUSTRY	IKAUKS.		

Engines heavier than O class not permitted on following tracks: Between Galena and East Galena, and on spur track serving Army Northwest Air Depot Yard at Galena. Ephrata, 2.2 miles east of, Army Air Depot Spur, south of siding.

TRAIN REGISTER EXCEPTIONS.

Hillyard, First class trains and passenger extras register by Spokane, first class trains and trains originating or terminating

at passenger station will register and receive clearance. Appleyard, register is for second and inferior class trains; pas-

senger extras will register by ticket. Wenatchee, register is for first class trains, Nos. 253-254 and passenger extras.

5. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B). Spokane, clearance issued and signed by the Superintendent will confer the same authority to a first class train as though received at its initial station.

6. RESTRICTED CLEARANCES.

In electrified zone all wires must be considered alive unless a clearance has been obtained from operator at Skykomish Sub-

Appleyard, and between Appleyard and Wenatchee, high voltage electric wires over tracks will not clear man on top of cars. Train and engine men must keep off top of cars and engines passing thru this territory, except in emergency, then use ex-

The following overhead wires crossing our track and trolley in electrified zone, do not have standard clearance of 27 ft. from top of rail:

Over Lead track _____21'.

- 7. Double track extends between Hillyard and Fort Wright, except over bridge 274 and S.P.&S. Jct. which is governed by interlocking signals.
- Spokane, Trent avenue crossing protected by watchmen between hours 7:00 A.M. and 11:00 P.M. daily, outside these assigned hours a member of crew must be on ground at crossing to protect movement.
- Spokane, City Ordinance prohibits sounding engine whistle within city limits, except to prevent accident not otherwise avoidable, or to signal an interlocking, or to communicate with a flagman.
- Fort Wright, instructions for operation of electric switch locks Military Spur and west siding switch posted in iron box locked with switch lock.
- Malaga, westward train holding main track meeting eastward train will not pass signal battery box just west of depot until opposing train arrives.
- 12. Wenatchee, westward trains moving from W-O Line lead to First Subdivision and required to wait for westward trains on First Subdivision shall stop east of sign reading "Wait Here". For further details and push button operation see instructions posted in iron box locked with switch lock.

13. SPEED TEST BOARDS.

Engineers shall test speed of their trains passing following points as compared with Speed Table:

Between MP 1492 and MP 1493 just east of Galena,

Eastward, Between MP 1612 and MP 1613 two miles west Winchester, Between MP 1644 and MP 1645 just west Malaga.

14. CROSSOVERS ON DOUBLE TRACK.

Facing point.

Trailing point. MP 1473.14 west of Hillyard. MP 1476 east of UP. RR. crossing, Spokane. MP 1476.69 on Br. 269, Spo-MP 1477.12 east of Br. 270,

MP 1477.22 east of Br. 270, Spokane. MP 1477.61 (Scissors) on Br. 273 west of Spokane passenger depot. 350' east of depot, Harring-

Spokane. MP 1477.61 (Scissors) on Br. 273 west of Spokane passenger depot. MP 1478.41 west of Br. 273, Spokane. 3200' west of depot, Mohler. 2000' west of depot, Downs.

15. SPRING SWITCHES WITH FACING POINT LOCK.

Lyons, east and west siding switch. Galena, east and west siding switch. Espanola, east and west siding switch. Edwall, east and west siding switch. Lamona, east siding switch. Nemo, east and west siding switch. Odessa, east and west siding switch. Irby, east and west siding switch. Wilson Creek, east and west siding switch. Stratford, east and west siding switch. Adrian, east and west siding switch.

Ephrata, east and west siding switch. Quincy, east and west siding switch. Trinidad, east and west siding switch. Voltage, east and west siding switch. Appleyard, east switch long lead.

east crossover switch long lead. Wenatchee, east and west crossover switch west end of yard. Normal position is for main track.

16. SPRING SWITCHES WITHOUT FACING POINT LOCK.

Hillyard, east end yard, connection of east yard lead to track

Normal position is for track No. 5.

17. DRAGGING EQUIPMENT DETECTOR INDICATORS.

Westward, on signal; 1623.8 approximately two miles east Trinidad. 1625.7 just east Trinidad. Eastward, on signal; 1623.8 approximately two miles east Trinidad. 1621.8 approximately one mile west Crater.

18. MANUAL INTERLOCKINGS.

Whistle signals for routes: Spokane, UP RR. crossing: Main track ______ 1 long.
GN-SI Ry Transfer No. 1 _____ 1 long, 1 short.
GN-SI Ry Transfer No. 2 _____ 2 long, 1 short. Fort Wright:

19. MANUAL INTERLOCKINGS WITH DUAL CONTROL SWITCHES.

Hillyardend of double track east and west end of yard, Interlocking includes interlocked switches at east end of yard (end of double track, yard lead, and safety switch); at west end of yard (end of double track, yard lead and spike yard lead) and the single main track between them electrically controlled by operator at depot. The "home signal limits" (Rule 605) of this interlocking for train and engine movements on main track extend from the westward home signals at east end of yard to eastward home signals at west end of yard. Trains and engines receiving a proceed indication of the governing home signal will proceed, regardless of class, in accordance with Rule 605, observing all governing signal indications.

Instructions for operation of Electric Locks and Releases posted in iron boxes locked with a switch lock. Whistle signals for routes west end of yard: Eastward trains. To yard1 long, 1 short. Westward trains, To westward main track long.

20. AUTOMATIC INTERLOCKINGS.

Bluestem dual control switch end of double track. Lamona dual control switch end of double track. Interlockings operate automatically for all movements with following exceptions: Lamona, when movement is to be made from double track to siding, siding switch must not be lined until engine is within home signal limits. Lamona, eastward train moving out of siding immediately after westward train has passed, must operate switch release push button located on eastward home signal to line route for eastward

Bluestem, westward train moving out of siding immediately after eastward train has passed, must operate switch release push button located opposite switch to line route for westward main track.

21. SWITCH INDICATOR.

Ephrata, indicator located at Army Air Depot Spur and Morrison-Knudson Spur.

Member of crew who is to line switches for train or engine movement from the spur to main track must first operate switch key controller in accordance with Item 17 Page 11 of this time table.

- 22. Normal position of the switch on the siding at Adrian, connection with the Northern Pacific is for the Great Northern.
- 23. Emergency water for Diesel boilers available at: Lamona, Wilson Creek, Ephrata.
- Emergency water for Diesel radiators available at: Edwall, Harrington, Lamona, Wilson Creek, Ephrata, Quincy, Columbia River.

SECOND SUBDIVISION

		(Oroville Line)	
1.	MAXIMUM	PERMISSIBLE SPEED FOR TRAINS	

Between Wenatchee and O	Proville	Passenger 35 MPH	

Oroville and Hedley 25 MPH 25 MPH 2. SPEED RESTRICTIONS.

on curves ______ 20 MPH

ENGINES RESTRICTIONS.

Engines heavier than class indicated are prohibited: Between Wenatchee and Riverside, O-4.
Between Riverside and Oroville, F-8, H-4.
Between Oroville and Hedley, G-3, G-4 and 1600 H.P. Diesel.

Nighthawk-Keremeos, trains will not pass International Border without permission of Customs and Immigration Inspectors.

Emergency water for Diesel radiators available at: Oroville,

Pateros, Chelan, Entiat.

THIRD SUBDIVISION

(Kettle Falls-Nelson Lines)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Troup Jct. and South Nelson	20 MPH
Kettle Falls and Dean	30 MPH
SDEED DESTRICTIONS	

Northport, wye tracks 8 MPH
Dolomite, spur track 10 MPH
Chewelah, thru town limits 8 MPH

3. ENGINE RESTRICTIONS. Engines heavier than class indicated are prohibited:

Between Dean and Kettle Falls R-1. Between Kettle Falls and Northport M.

Between Northport and Nelson 1600 H.P. Diesels in single or multiple units.

Northport wye O engines prohibited.

4. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B). (a) Great Northern clearance received at Nelson will clear train

at Troup Jct. (b) Kettle Falls, all trains must secure clearance.

- Troup Jct., northward trains must stop clear of junction switch before entering Canadian Pacific main track and know track is
- 6. Northport-Waneta, trains will not pass International Border without permission of Customs and Immigration Inspectors.

SWITCH INDICATORS.

Dean, indicator for movements from Spokane division Third sub-division to Kalispell division Fourth subdivision.

Member of crew who is to line switches must first operate push button "R" for route desired and hold few seconds. Both trainman and engineer must observe and be governed by indicator before lining switches or fouling main track.

Push buttons and instructions for their operation are posted in

iron box locked with a switch lock.

8. Emergency water for Diesel radiators available at Northport.

FOURTH SUBDIVISION

(Republic Line)

1.	MAXIMUM	PERMISSIBL	E SPEED FOR	TRAINS.	
	Between				
	Kettle Falls	and Republic			20 MPH

2. SPEED RESTRICTIONS.

3. ENGINE RESTRICTIONS.
F-8 and 1600 H.P. Diesels in single or multiple units heaviest permitted.

- Kettle Falls, normal position of junction switch is for Third Subdivision.
- 5. Laurier-Danville, trains will not pass International Border without permission of Customs and Immigration Inspectors.
- 6. Emergency water for Diesel radiators available at Republic.

FIFTH SUBDIVISION

(Mansfield Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS. Between

2. SPEED RESTRICTIONS. Trains handling steam derrick, over bridges...... 5 MPH

3. ENGINE RESTRICTIONS. F-8 and 1600 H.P. Diesels in single or multiple units heaviest permitted.

- 4. Columbia River, normal position of junction switch is for siding on First Subdivision.
- 5. Emergency water for Diesel radiators available at: Mansfield. Palisades.

SIXTH SUBDIVISION

(Moscow Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

2. SPEED RESTRICTIONS. Trains handling steam derrick, over bridges. 5 MPH
Bridge 23.2 Mt. Hope, 2 miles west of 8 MPH
Moscow, thru city limits 10 MPH

3. ENGINE RESTRICTIONS.

G-3 and 1600 H.P. Diesels in single or multiple units heaviest permitted.

4. RESTRICTED CLEARANCES.

Spokane, bridge 1.5 will not clear man on top or sides of cars or engines. Train and engine men must keep off top or side of cars and engines while passing over bridge, except in emergency and then use extreme caution.

- 5. Bridge 23.2, 2 miles west of Mt. Hope, trains or engines must stop before crossing bridge.
- Emergency water for Diesel radiators available at: Moscow, Garfield.

SEVENTH SUBDIVISION

(Coeur d'Alene Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between

Spokane and Coeur d'Alene 25 MPH

2. SPEED RESTRICTIONS.

Trains handling steam derrick over bridges 5 MPH
Spokane, Crestline St., UP and CMStP&P RR crossings 15 MPH
Millwood, public crossing 4 MPH
Coeur d'Alene, thru City limits, at restricted speed.

3. ENGINE RESTRICTIONS.

G-3 or 1600 H.P. Diesels in single or multiple units heaviest permitted.

4. RESTRICTED CLEARANCES.

Between Spokane and Coeur d'Alene, train and engine men must keep off top and sides of cars and engines, except in emergency and then use extreme caution account restricted side and overhead clearance at various points.

5. Coeur d'Alene, trains and engines must stop before passing over 11th Street and Mullan Avenue crossings and movement must be protected by flagman on the ground at the crossing.

 Coeur d'Alene, trains and engines must stop and sound two blasts of engine whistle before proceeding over Diamond Drill Crossing.

 Operation between Spokane Bridge and Coeur d'Alene, is joint with CMStP&P RR and their Time Table and Special Instructions govern.

tions govern.

Trains leaving Spokane will be cleared thru Great Northern dispatcher to Spokane Bridge and will be cleared at Spokane Telegraph office by CMStP&P RR dispatcher for movement from Spokane Bridge to Coeur d'Alene. Trains leaving Coeur d'Alene will be cleared by Great Northern dispatcher for movement from Spokane Bridge to Spokane and by CMStP&P RR dispatcher at their office in Coeur d'Alene for movement from Coeur d'Alene to Spokane Bridge.

8. MANUAL INTERLOCKINGS.

Inland Jct. 0.71 miles east of,..... UP and CMStP&P RR crossings

 Emergency water for Diesel radiators available at: Coeur d'Alene.

EIGHTH SUBDIVISION

(Colfax Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between

Spring Valley and Colfax 25 MPH

2. SPEED RESTRICTIONS.

Trains handling steam derrick over bridges...... 5 MPH

3. ENGINE RESTRICTIONS.

G-3 or 1600 H.P. Diesels in single or multiple units heaviest permitted.

4. RESTRICTED CLEARANCES.

Colfax tunnel will not clear man on top or sides of cars and engines. Between Spring Valley and Colfax, train and engine men must keep off top and sides of cars and engines, except in emergency and then use extreme caution account restricted side and overhead clearances at various points.

5. Colfax, trains and engines while switching or moving in and out of depot must use extreme care in passing over North and Last Streets account restricted view.

6. SEMI-AUTOMATIC INTERLOCKINGS.

7. RAILROAD CROSSING PROTECTED BY GATES.

Thornton, 0.57 miles west of _____UP RR crossing Normal position is stop for Great Northern.

 Emergency water for Diesel radiators available at: Colfax, Rosalia.

WATCH INSPECTORS

A. F. BensonNewport,	Wash.
H. H. Trowbridge5012 No. Market, Spokane (Hillyard),	Wash.
H. J. March	
Nelson Jewelry Co408 Riverside Avenue, Spokane,	Wash.
Funk's Jewelry StoreWenatchee,	Wash.

SPEED TABLE

Time	Per Mile Miles	Time	Per Mile Miles
Min.	Sec. Per Hou	Min.	Sec. Per Hour
1 1 1 1 1 1 1 1	40 90.0 41 87.8 42 85.7 43 83.7 44 81.8 45 80.0 46 78.3 47 76.6 49 73.5 50 72.0 51 70.6 52 69.2 53 67.9 54 66.6 55 65.4 56 64.2 57 63.1 58 62.0 60.0 1 59.0 2 58.0 3 57.1 4 56.2 5 55.3 6 75.3 6 52.9 10 51.4	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	12 50.0 14 48.6 16 47.4 18 46.1 20 45.0 22 43.9 24 42.9 26 41.9 28 40.9 30 40.0 33 38.7 36 37.5 39 36.4 42 35.3 45 34.3 500 32.7 55 31.3

BUSINESS TRACKS NOT SHOWN AS STATIONS ON TIME TABLE

Name	Location	Capaci- ty Cars	Switch Opens	Name	Location	Capaci- ty Cars	Switch Opens
Subdivision No. 1 Fort Wright Military Spur Highland Rock Quarry East Galena	8.2 miles east of Galena	38 72	West East	Subdivision No. 4 West Kettle Falls	4.71 miles west of Kettle Falls, Lafferty Transportion Co. Spur incl. Deer Park Lbr.		
	U. S. Army Yard At Galena-U. S. Depot Yard 2.2 miles east of Ephrata		West West	Harter Lumber Co	Co. Spur	137 10 3	West Both East
Morrison-Knudsen Spur Sand Pit Gravel Spur Keokuk Metals	U. S. Army Yard 1.5 miles west of Ephrata 1.23 miles west of Trinidad 2.9 miles west of Trinidad 1.3 miles west of Voltage	22 30 70	East Both Both West	Spokane-Portland Cement	1.1 miles east of Boyds 2.5 miles east of Laurier 3.4 miles east of Grand Forks	12 10 2	East Both East
	Private Yard	10	East West	Smelting Co. Spur	1.1 miles east of Grand Forks. 0.4 miles west of Grand Forks 1.25 miles west of Torboy	12 3 5	West East East
Larabee Industry	3.41 miles north of Tonasket 1.11 miles south of Barker 5.1 miles north of Entiat 3.5 miles north of Entiat 1.4 miles south of Wagnersburg 2.02 miles north of Olds	20 17 2 10 6 10 2 60	Both Both Both South South South South	Ringo Longwill. Seabury. Jefferson. Dale. Clifton. Ochlare. Jacobsen's Spur	3.22 miles west of Moscow 3.79 miles west of Viola 1.39 miles west of Sokulk 2.39 miles west of Geary 3.49 miles west of Spring Valley 4.55 miles west of Spring Valley 5.03 miles west of Spring Valley 5.03 miles west of Mt. Hope 1.5 miles west of Parkview 1.25 miles west of Moran 2.27 miles west of Moran	12 7 5 11 4 5 3 5 1 23	Both West East Both Both East West East West East Both
Porto Rico Spur Baskins Spur Salmo Gravel Spur Archibald Spur Benton Spur Ross Work Spur Kootenai Industry Stroh Spur Hudson's Spur Kanes Spur Harpers Spur	5.33 miles north of Northport. 3.3 miles south of Northport. 4.1 miles south of Northport. 4.5 miles south of Northport. 1.3 miles south of Marble, in-	1 2 10 15 3 6 9 3 5 3 10 5	North South South South Both Both South South South South South North	Subdivision No. 7 Winton Lumber Co	1.5 miles west of Coeur d'Alene 2.6 miles west of Coeur d'Alene 8.46 miles west of Coeur d'Alene 2.14 miles east of Greenacres 1.24 miles west of Flora 1.17 miles west of Flora	16 35 5 12 4 8 3 22 3 11 8	West Both Both West East West East West East West
Hendrix Cut	3.1 miles south of Addy 3.0 miles north of Chewelah	251 3 12 19 8 40	South South South Both North North	Blackwell	5.65 miles west of Colfax 1.92 miles east of Steptoe 2.95 miles west of Thornton 4.34 miles east of Rosalia 2.1 miles east of Rosalia 2.59 miles east of Spring Valley	6 14 4 12 7 11	West Both East Both West East

