COMPANY SURGEONS

*Dr. Roscoe C. Webb, Chief SurgeonMinneapolis, Minn.
*Dr. Ernest R. Anderson, Assistant Chief SurgeonMinneapolis, Minn.
*Dr. E. B. CoulterSpokane, Wash.
Dr. Joseph ThaylerHillyard, Wash.
*Dr. G. R. KingstonWenatchee, Wash.
*Dr. L. F. Wagner
Dr. J. E. McNamaraWilson Creek, Wash.
*Dr. J. F. KearnsEphrata, Wash.
*Dr. C. O. MansfieldOkanogan, Wash.
Dr. R. V. Kinzie
Dr. C. M. CanningColville, Wash.
Dr. Richard GrunbergKettle Falls, Wash.
*Dr. Fred M. AuldNelson, B. C.
Dr. H. B. StoutPateros, Wash.
*Designates also Examining Surgeon.

OPHTHALMIC SURGEONS (Eye Doctors)

Dr. Philip B. Greene	Spokane, Wash.
Dr. C. K. Miller	Wenatchee, Wash.

C. E. Emerson, Chief Dispatcher.
D. L. Manion, Trainmaster.
W. J. Barke, Trainmaster.
T. J. Brennan, Trainmaster.
H. H. Holmquist, Trainmaster.

Scanned from the Dean Ogle Collection

GREAT NORTHERN RAILWAY COMPANY

1. 1. 2. 5 -

SPOKANE DIVISION

TIME TABLE

84

Effective 12:01 A. M. Pacific Time

Sunday, October 18, 1953

F. V. PERCIVAL, Superintendent. T. A. JERROW, General Manager. A. W. CAMPBELL, General Superintendent Transportation

2	V	VES	TWAR	D			F	FIRST	SUBDI	VISION	<u>ر</u>				
	Cor	Car pacity			1	-		Fľ	RST CLA	ASS			,	Time Table No. 84	1
		1			('		1	45	3	27	5	21	from	Effective October 18, 1953	ph Calls
Station Number	Bidings	H			· · /		Streamliner	S. P. & S. No. 3		•		8. P. 4 8. No. 1 Pressinger	Distance Hillyard		- 5
	Bild	Other Tracks			· · · · · ·		Daily	Daily	Daity	Daily	Daily	Daily		STATIONS	Pe H
1469	Yard	18184	·	1		1	L 11.15Pm		L 8.00Pm		1	1	0.00	×	BU
1472	1 1				.[[]	11.25	1	8,10	5.45		/	8.68	3.68	
							A 11 30	- 0.150-	A 8.15	A 5,50Pm	- 0.301	10.04		5	
1478 1477		1 644 26				······		L 9.15Pm n.A. 9.21Pm			L 8.30Am 1 8.35	n LL 2.06Ann AL 2.1 Ann		2.74 2.74 2.74	Q FW
1481	1 1				[12.05Am	A 7.6110	9.05 9.16	[8.45	A 12.11m	18.95	6.36 HIGHLAND	
1486		15					12.22	1	9.10	!	8.50	[17.31	3.26 LYONS	
1498		69					12.27		9.26	!	1 8.58	!	32.00	5.39	NA
1496	180	89			· · · · · ·	······	12.31	<i>'</i>	9.30	·'	1 9.04	[]	26.60	4.09	
1502		50		[1	······································	12.31	[]	9.30	[!	1 9.04	[······]	36.00 38.18	8.44 WAUKON	
1508	1 1	88				l	12.42	[]	9.35	[!	s 9.20	1	88.90	5.73 EDWALL	WB
1512		37			!		!	//		!	[!]]	43.00	3.70 CANBY	
1517	70	46					12.52	!	9.49	!	1 9.32		48.10	8.50	
1524	E62 W69	95		[]	· · · · ·	('	12.59	(<u> </u>	9.57	[]	9. 42		85.61	7.41 HARRINGTON	HB
1581	1 1		[[l	1.05	[9.57	[]	9 .42 1 9.50	[]	63.33	6.73	-
1585		49			!	[1.09	[]	10.04	[]	9.55	[]	85.94	3.71 DOWNS	
1589	1 1	85			!	[!	1.14	[]	10.13		10.01	[]	70.40	4.46 2	
1544	185	18	······		[]		1.20	[]	10.18		10.07	[]	75.98	5.55	
1550	185	118			/	· · · · · · · · · · · · · · · · · · ·	1.25	(,	10.23		s 10.15		\$9.88	4.85 ODESSA	54
1550	1 1	25	[[′	[]	[!	1.25	[]	10.23	[]	t 10.15	<u> </u>	60.74		
1566		88		[!	[]	[!	1.41	<u>(</u>	10.31		s 10.34	[]	97.81	7.47 MARLIN	
1878	164	152		!			1.48	[]	10.44		 10.43 		103.83	WILSON CREEK	CK
1580	129	19		·······		'	1.56	[]	10.51		1 10.53		111.65	7.83	·
1588	141	182		······		· · · · · ·	2.01		10.56		10.59		116.97	5.81 ADRIAN	
1591	1 1	20	['	[!	[]	['		[]	0.50	[]	■ 11.06		131.57	4.60 SOAP LAKE	
1596		58	[[!	[]	/!	s 2.12	[]	s .15	[]	11.0011.16		126.07	5.40 EPHRATA	FR
1601	70	7	 '	!	[]		2.17	()	11.21		11.22		199.12	LIS NAYLOR	
1606	69	56	'	<u></u> /			2.22	[]	11.27		t 11.28		187.19	5.07 WINCHESTER	
1612	114	242	['			<u> </u>	2.28		11.34		• 11.37		143.83	6.14 QUINCY	QN
1617	1 1	1.	[!	[!	[]	[!	2.35	[11.34	[]	11.43		148.46	5.13 CRATER	
1628		19	[!	[!		[!	2.45	[]	11.41	[]	11.4511.52		154.06	5.60 TRINIDAD	
1682		59	[!	l!	[]	!	2.58	[]	12.05Am		t 12.03Pm		163.87	5.31 COLUMBIA RIVER	
1687	126	88	!	······'	·····		3.03	[]	12.10		1 2.07		166.53	3.45 VOLTAGE	
1638	0	43	('	······			ľ l	[]			1 12.10		168.82	1.50 ROCK ISLAND	RI
1641		64	[!	[]	[]		3.11	[12.19		1 12.10		173.84	4.02 MALAGA	MA
			[!	[!	[]		3.17	[]	12.19		I2.25		177.08	4.74 APPLEYARD	WD
1648	Yard	1085	[!	[]		[]	A 3.25Am		A 12.30Am		A 12.30Pm		179.25	2.17 WENATCHEE)	wc
[]	()	('	'										l	Time Over Subdivision	
	1	()	1 /	[]			4.10 43.02	.06 27.40	4.30 39.84	.15 19.40	4.00 43.60	.05 32.88	1	Average Speed Per Hour	
·	Westward trains are superior to eastward trains of the same class, except as follows:														

Westward trains are superior to eastward trains of the same class, except as follows: Nos. 1 and 21 are superior to all trains. Nos. 2 and 22 are superior to all trains, except Nos. 1 and 21. Conditional flag stops. Nos. 3 and 4 stop at any station between Spokane and Wenatchee to pick up or dis-charge revenue passengers from or to points Great Falls and East where Nos. 3 and 4 are scheduled to stop. SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 9 THROUGH 17.

				FI	RST SU	JBDIVI	SION				EA	STWAI	RD 3
Time Table No. 84	a	FIRST CLASS							SECOND CLASS				
Effective October 18, 1953	Distance from Wenatchee	46 S. P. & S. No. 4	4	28	6	22 5. P. & 5. No. 2 Streaminer	2		472	486			SIGN
STATIONS	Dist Wen	Daily	Daily	Daily	Daily	Daily	Streamliner Daily		Daily	Daily			
HILLYARD) 3.68 	179.25			A.s. 8. 5Am			A 11.30Pm		A 12.30Pm				BRKD
3.68 	175.57		7.25	8.05			11.20		12.20 I 2.20	A 7.15m 7.00		· · · · · · · · · · · · · · · · · · ·	TWOIX DNPIM
1.17 SPOKANE 2.74 FORT WRIGHT	174.40	A. 6.35km	L 7.20 A 6.50	L 8.00Am	a 5.30Pm	▲ 10.35Pm	L 11.15 A 10.45		12.15	6.55			RKDN
FORT WRIGHT	171.66	L 6.28Am	6.45			L 10.28Pm	1		12.10Pm	6.45			IDNPY
6.36 HIGHLAND 8.26	165.30		6.35		5.11		10.30		11.57	6.32			Р
LYONS 5.39	162.04		6.30		5.05		10.25		11.51	6.25			Р
FAIRCHILD	156.65	·····	6.25		f 4.59		10.20		11.43	6.17			DNP
4.09 ESPANOLA 6.44	152.56		6.20		f 4.52		10.16	·····	11.37	6.10	•••••		Р
	146.07	•••••	6.14		f 4.44		10.10		11.28	6.00			Р
EDWALL 8.70	140.85		6.09		s 4.38		10,05		11.20	5.50	•••••		DPW
	186.65 181.15	· • • • · · · · • • • • • • • • • • • •	5.59		t 4.26		9.54		11.00	5.35			P IP
7.41 HARRINGTON	123.74		5.50		• 4.17		9.45		10.45	5.23			DNP
6.72 MOHLER	117.02		5.43		4.09		9.36		10.32	5.13			P
8.71 DOWNS	118.81		5.38		4.03		9.31		10.25	5.07			P
8.71 	108.85		5.33				9.25		10.17	4.59			iPw
6.58 	103.20		5.27		3.50		9.19		10.07	4.50			P
4.85 ODESSA	98.42		5.22		 3.43 		9.14		9.47	4.40			DPN
8.91 IRBY	89.51		5.12		1 3.29		9.04		9.35	4.26			P
7.47 MARLIN	82.04		5.04		s 3.21		8.56		9.24	4.15			P
WILSON CREEK	75.42		4.57		s 3.13		8.49		9.15	4.05			DNI YX
6TRATFORD	67.60		4.50		f 3.03		8.41		9.02	3.48			<u> </u>
5.82 ADRIAN 4.60	62.28		4.45		1 2.56		8.35		8,55	3.41			PV
SOAP LAKE 8.40	87.68	• • • • • • • • • • • • • • • • • • • •		[s 2.50					•••••			P
EPHRATA 8.15	52.28		s 4.35		s 2.42		s 8.25	•••••	8.42	3.28	•••••		DNI
NAYLOR 5.07	47.18	•••••	4.23		f 2.30		8.17	••••••	8.35	3.20	•••••	•••••	Р
WINCHESTER	42.06	·····	4.19	·····	<u> </u>	<u></u>	8.13		8.28	3.13			P
6.14 QUINCY 5.13 CRATER			4.14		a 2.18		8.08		8.20	3.05	•••••	•••••	DNP
	80.79		4.07		2.08		8.02		8.05 7.50	2.45	•••••	•••••	P
9.81 COLUMBIA RIVER	25.19 15.88		3.59	•••••	2.01		7.54	•••••	7.50	2.30		•••••	P m
8.45 VOLTAGE	1		3.47 3.42		1 1.46 1 1.41	••••	7.42 7.37		7.30 7.20	2.05 1.55			JP P
1.50													
4.02	10.93	•••••		•••••	f 1.39		7 20	•••••	710	1 45	•••••		DP
	6.91 9.17		3.34	•••••	f 1.32 486 s 1.25	•••••	7.30		7.10	1.45 L 1.30P m	•••••		DN BRKDI
2.17 WENATCHEE	2.17 00.0	•••••	3.29	• • • • • • • • • • • • • • • •			7.25		L 7.00Am	L L.SUIM			TWO RKDI
Time Over Subdivision			L 3.25Am		L 1.20Pm		L 7.20Pm						WXB
Average Speed Per Hour		.07 23.49	4.10 43.02	.15 19.40	4.10 41.85	.07 23.49	4.10 43.02		5.30 32.19	5.45 30.80			

Westward trains are superior to eastward trains of the same class, except as follows: Nos. 1 and 21 are superior to all trains. Nos. 2 and 22 are superior to all trains, except Nos. 1 and 21. Conditional flag stops. Nos. 3 and 4 stop at any station between Spokane and Wenatchee to pick up or dis-charge revenue passengers from or to points Great Falls and East where Nos. 3 and 4 are scheduled to stop.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 9 THROUGH 17.

4	SOT	JTH	WARD)			SE	COND SUBDIVISION					NO	RTHW	ARD
	С Сар	ar acity			THIRD	CLASS	8	Time Table No. 84	Calls	в		THIRD	CLASS		
ber	5				397	697	Ance from ey	Effective October 18, 1953	Telegraph C	Distance from Wenatchee	SIGNS	396	698		
Station Numbers	Sidings	Other Tracks			Mon.; Wed. and Friday.	Daily Ex. Sun.	Distance Hedley	STATIONS	Teles	Dista		Mon., Wed. and Friday.	Daily Ex. Sat.		
SG 128	Yard	11		•••••	L 12.01Pm		0,00			192.98		A11.30Am			
8G 110	88	88			s 1.00		17.68	17.68 	ĸ	175.80	D	s 10.30			
	0	10			1 1.10		21.58	3.90 CAWSTON, B. C		171.40		10.10			
8G 98	0	22			s 1.50		84.50	12.92 CHOPAKA, WASH		158.48		s 9.35			
8G 88	0	7		· • • • • • • • • • •	 2.35 		44.40	9.90 NIGHTHAWK 11.84		148.58	RKDY	s 9.05			•••••
8G 71	Yard	248		<u></u>	<u></u> Δ 3.10Pm	L 3.20Pm	55.74	ORÖVILLE	VR	187.24	BPXO	L 8.30Am	A 1.30A m		<u></u>
WO 182	0	85				3.35	61.49	5.75 CORDELL		181.49			1.10		
WO 126	0	84				3.50	66.77	5.28 ELLISFORDE		126.21			12.50		
WO 12 0	0	71				4.15	72.70	5.98 Tonasket	ON	120.28	DP		12.30		
WO 115	0	84				4.30	77.58	4.88 JAN15 5.48	 .	115.45			12.05Am		
WO 110	0	84				4.45	82.96	BARKER	<u></u>	110.02			11.50	·····	
WO 105	0	86				5.00	88.25	5.29 RIVERSIDE		104.78			11.30		-
WO 10 0	0	85				5.15	92.48	4.18 CHEROKEE		100.55			11.15		
WO 96	66	214				5.45	97.28	4.85 ••••••••••••••••••••••••••••••••••••	мк	95.70	BDPXY		11.00		
WO 92	55	92				6.45	101.48	4.20 OKANOGAN	KN	91.50	DPX		10.10		
WO 87	0	84				7.05	106.41	4.98 CHILLOWIST		86.57			9.20		
WO 88	0	85				7.20	110.34	8.93 MALOTT		82.64	P		9.05		
WO 76	0	85				7.40	116.59	6.25 WAKEFIELD		76.89	r		8.45		
WO 72	0	84				8.00	121.82	4.73 MONSE		71.66	Р		8.30		
WO 68	39	67				698 8.15	125.29	8.97 CHIEF JOSEPH		67.69	P		697 8.15		
WÓ 65	50	61				8.45	127.99	2.70 Brewster	BR	64.99	DPX		8.00		
WO 59	125	335				9.15	184.07	6.08 Pateros	RO	58.91	DPX		7.25		
WO 58	0	86				9.30	189.54	5.47 STARR		58.44	P	·	6.45		V
₩O 50	0	84	•••••••••••			9.30	148.20	8.66 AZWELL		49.78	r P		6.30		•••••
WO 44	0	85				10.00	148.98	6.73 HUGO		44.05	<u> </u>	[6.15		
WO 80	125	88				10.45	154.04	8.11 Chelan	HN	88.94	DPX		6.00		
	0	78				11.00	155.20	1.16 CHELAN FALLS		87.78	x		5.40		
WO 82	0	40				11.20	161.05	5.85 Stayman			P		5.13		
WO 32	0	48		••••••		11.20	166.97	5.92 WINESAP		8 1.98 26.01	r		4.45	••	
WO 19	125	107				12.15Am		7.11 ENTIAT	NI	18.90	DPX		4.25		
WO 14	0	89				12.30	179.88	5.30 WAGNERSBURG		18.60	~		3.40		
WO 8	0	81				12.50	185.01	5.68 ZENA		7.97			3.25		
THE											·····				•
WO 8 1648	0 Yard	66 1085	•••••	•••••	••••	I.05	189.49 192.98	4.48 et allos	wc	8.49 0.00	RKDNP BWXJ		3.10 L 3.00Pm	····	
									<u> </u>				J.007m		
					3.09 17.69	9.55 14.83		Time Over Subdivision Average Speed Per Hour				8.00 18.58	10.30 13.07		

Northward trains are superior to southward trains of the same class.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 9 THROUGH 17.

SO	UTI	IWA	RD				T	HIRD SUBDIVISION					NORT	HWAR	D 5
		ar aoity			THIRD	CLASS	а	Time Table No. 84		E		THIRD	CLASS		
Station Numbers	5				703	701	Distance from Nelson	Effective October 18, 1953	TelegraphCalls	ance from h	SIGNS	702	704		
Stat Nun	Sidings	Other Traok			Tu. Thur. and Sat.	Daily Ex. Mon.	Dist	STATIONS	Teleg	Dietanc Dean		Daily Ex. Sun.	Mon, Wed., and Friday		
SA 186					l. 6.00Am		0.00		BC	185.75	RDNWP		a 3.20Pm		
TRAINS BETWEEN TROUP JCT. AND NELSON BE GOVERNED BY C. P. RY. TIME TABLE AND RULES															
SA 181	0	0			l 6.30Am		5.45	TROUP JUNCTION.		180.30	RYPV		▲ 2.45Pm		
SA 176	0	27	•••••		6.55	•••••	10.26	4.81 SOUTH NELSON 6.79		175.49	· · · · · · · · · · · · · · · · · · ·	•••••	2.10	•••••	•••••
SA 169	0	8		•••••	7.25	•••••	17.05			168.70	•••••	•••••	1.40	•••••	•••••
SA 166	0	15	•••••	•••••	7.40 8.05	•••••	20.88 27.50			165.87	·····w	••••	1.25	•••••	•••••
SA 159	0	<u> </u>			8.05		27.00	4.36		158.28			12.57		
SA 155	0	9	•••••		8.20		81.86	8.29	 	158.89		••••••	12.40	••••••	
SA 152	0	58			9.00	•••••	85.15	SALNO 2.72	81	150.60	D	•••••	12.30	•••••	•••••••
SA 148	0	15		• • • • • • • • • • • • • • • • • • • •	9.10 9.25	•••••	87.87 40.74	ERIE 2.87 MEADOWS		147.88	•••••	••••••••••	12.05Pm	•••••	•••••
SA 145 SA 140	0	20 7	** ** ** ** ** * * *	•••••	9.25	••••••	44.82	4.08 PARKS		145.01 140.93	•••••	•••••	11.55 11. 35		•••••
								5.60					-		
SA 186	0	33	•••••••••••	•••••	10.45	•••••	50.42	5.32	·····	135.83	w	•••••	11.10	•••••	
SA 130	0	7	•••••••••••••	•••••	11.15	•••••	55.74	8.88 WANETA B.O.	·····	180.01 126.18	Р	••••	10.45	•••••	
SA 127 SA 126	0	7 89	•••••	•••••	.40 .50	*******	59.57 61.68	WANETA, B. C 2.11 BOUNDARY, U. S	 	120.18	P	•••••	10.20 10.05	•••••	••••
SA 120 SA 116	60	89	•••••	•••••	12.40Pm	••••••••••	70.48	8.80 NORTHPORT	NP	115.27	PDYX	** ** *** *** ***	9.30		
								8.28							
SA 109	0	80	•••••	• • • • • • • • • • • • • • •	1.10	•••••	78.76	MARBLE.		106.99	W	•••••	8.25	•••••	••••
SA 107 SA 96	45	0	• • • • • • • • • • • • • • •	•••••	1.20 1.55	•••••	80.06 90.24	DOLOMITE 10.18 BOSSBURG	 	105.69 95.51	P	•••••	8.20 7.50	•••••	•••••
SA 90	39	16 92	•••••	•••••	2.10	•••••••••••	94.11	8.87 EVANS		91.64	ХР	** ** ** ** ***	7.30		•••••••••
SA 82	Yard	343	•••••		A 2.50Pm		104.02	9.91 Kettle Falls	MF	1	RKDNW BYXOJPZ	A 2.30Pm			••••••
								8.50	·						
SA 77 SA 78	0	18 115		•••••		5.10 6.00	109.43 112.48	8.05	VD	76.82 78.27	PD	2.00 1.35	•••••	•••••	
SA 78	40	0		•••••	• • • • • • • • • • • • • • •	6.40	112.98	6.50 ARDEN	VD	66.77	P	1.35	•••••	•••••	•••••
SA 59	0	20	•••••		•••••	7.15	126.87	7.39 ADDY		59.38	-	12.45 12.15Pm	•••••		
								9.21							
SA 50	81	135			•••••	9.00 702	185.58	CHEWELAH	CH	50.17		11.30 701	••••	•••••	•••••
SA 48 SA 88	4 0 0	49 80		•••••	•••••	10.30 .00	148.15 148.89	VALLEY 5.24 GRAYS	VY	42.60 87.86	PDYX P	10.30 9.30	•••••	•••••	
SA 86	0	18				11.00	151.82	8.43 CLINE	[88.93	-	06.7	•••••	•••••	
SA 33	89	17				11.30	158.09	1.27 Springdale		82.66	PW	9.05			
SA 25						11.59	161.20	8.11 LOON LAKE		24.55	P	8.30			
BA 20 BA 18	40 0	5 62			•••••	11.39 12.30Pm		6.80 CLAYTON		24.00 17.75	P	8.30 8.00	** ** * * * * * * * * *	• • • • • • • • • • • • •	
SA 18	50	49				1.00	178.27		DE	12.48	PDXW	7.30			
SA 9	0	20				1.20	176.86	8.59 DENISON		8.89	P	6.25			
8A 4	40	0				1.40	181.98	5.12 WAYSIDE		8.77	P	6.10			
1460	Yard	72			•••••	.A. 2.10Pm	185.75	8.77 DEAN	sf	0.00	JRDNX	l 6.00 4			
					8.50 11.77	9.80 8.60		Time Over Subdivision Average Speed Per Hour				8.80 9.60	8.20 12.48		

Southward trains are superior to northward trains of the same class.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 9 THROUGH 17.

EASTWARD FOURTH SUBDIVISION WESTWARD б THIRD CLASS THIRD CLASS Car Capacity Time Table No. 84 Calls from Distance from Kettle Falls Effective October 18, 1953 393 Telegraph 394 Distance f Republic SIGNS Station Number Sidings Other Tracks Mon., Wed and Fri. STATIONS Mon., Wed. and Fri. ORKDNB JWYXPZ A 0.00 KETTLE FALLS MF 4.10Pm SA 82 200 L 5.00A 80.68 Vard 5.20 4.70 KETTLE 75.98 Р 3.45 8D 5 ŋ 137 5.45 3.15 12.10 BOYDS 68.58 8D 12 0 24 5.34 BARSTON 2.55 8D 17 0 81 6.05 17.44 63.24 5.28 DULWICH SD 22 81 6.30 22.67 58.01 2.40 0 1.55 6.40 ORIENT 56.46 Р 2.30 SD 24 0 7 24.22 4.88 GOLDSTA SD 29 0 12 7.00 28.55 52.18 2.10 7.30 34.64 AURIER, WASH 46.04 P 1.50 SD 85 0 18 GRAND FORKS, 8.15 45.98 GR 84.70 1.10 SD 46 0 5 GRAND FORKS JCT 8.20 33.21 1.01 8D 47 47.47 YV 0 4 DANVILLE. W 12.55 8.30 Р SD 49 0 18 49.08 81.62 4.13 HURLBURT 8.45 58.19 27.49 12.35 SD 53 0 11 6.29 CURLEW ΡW 12.15P SD 59 0 62 9.05 59.48 21.20 6.08 MALO 11.55 SD 65 88 9.20 65.56 15.12 0 SD 72 0 18 9.40 73.10 POLIĂR 8.58 11.35 9.50 TORBOY 11.20 8D 76 25 75.78 4.90 n REPUBLIC XBRKDY A 10.10A Z 0.00 L | 1.00A **SD 81** 80.68 Yare 125 Time Over Subdivision Average Speed Per Hour 5.10 15.61 5.10 15.61 Westward trains are superior to eastward trains of the same class. SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 9 THROUGH 17. NORTHWARD SOUTHWARD FIFTH SUBDIVISION Car Capacity from River Time Table No. 84 from Distance fi Mansfield Effective October 18, 1953 Distance f Columbia SIGNS Station Sidings Other STATIONS MANSFIELD 60.39 PXRY CR 60 48 0.00 Yard 5.40 TOUHEY **CR 55** 5.40 54.99 Р 80 0 5.98 Withrow CR 49 11.88 49.01 0 50 5.5 P **CB 44** 0 80 16.94 48.45 6.99 DOUGLAS CB 36 28.98 86.46 PD 0 62 5.27 Р CR 81 0 80 29.20 LSTOW 81.19 9.84 McCUE **CB 21** 24 89.04 21.85 Р 0 5.58 PALISADE **CB 16** 0 85 44.62 15.77 P 10.32 BON SPUR 230 CR 5 0 54.94 5.45 PWJ 60.89 COLUMBIA RIVER 53 0.00 1682 Yard Time Over Subdivision Average Speed Per Hour Northward trains are superior to southward trains of the same class.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 9 THROUGH 17.

TIONAL SPECIAL INSTRUCTIONS PAGES 9

W	EST	ſWA	RD					ST	XTH SUBDIVISION					EA	STWA	RD 7
	Ī	Car	1	. <u> </u>	1	1		1	me Table No. 84]			
8 A	1-		-1		-		_		ffective October 18, 1953	Spok	traph	Signs				
Station Numbers	Sidingo	Other			-	-	-	-1	STATIONS	Distances from Spokane	Telegraph Calls					-
8B90	Ya	1		•••••	•	••••••••••••••	••• •••••••	••••		95.03	мо	BRKDYXV			·····	·····
SB82 SB 76	1	0 1: 8 10		•••••	• • • • • •		•••		8.00 VIOLA 6.48 PALOUSE	87.03			•••••	[·····	·····	
8B71		0 10		•••••					4.86 GRINNELL	80.55 75.69	PA	DYXV				
8B69		0 1							2.09 	73.60						
<u></u>	<u></u>	<u></u>	<u></u>	<u></u>	<u> </u>	<u></u>		N. P.	3.60 & U. P. R. R. CROSSINGS 0 37	70.00	·····	M	<u></u>	<u></u>	<u></u>	·····
8B65	1	1		••••		•••	••••		GARFIELD	69.63	G₽	D	•••••	•••••	•••••	
8B61 8B57		0 1		•••••	•	••	•••		CRABTREE 3.60 Sokulk	65.62 62.02	•••••	•••••	•••••			
				· · · · ·					3.52 N. P. R. R. CROSSING	58.50		M	•••••			
									0.01 U. P. R. R. CROSSING	58.49		м				
<u>8858</u>	1	1 4	<u>/</u>	••••		<u></u>	<u></u>		0.65 OAKESDALE	57.84	<u>K</u> A	DV	<u> </u>	<u></u>	<u></u>	·····
8B50	1	0 1	s 	•••••					3.21 GEARY 4.67	54.63		••••••				·····
8B45		0 2		• • • • •	• • • • • • • • • • • • • • • • • • • •	•••••••••••••••••••••••••••••••••••••••	••• ••••••		FAIRBANKS 5.23	49.96			•••••			
8B40 8B34	2	8 51 8 2:		••••		•			SPRING VALLEY 6.10 Waverly	44.73 38.63		XRYOJ D	•••••	•••••		•••••
SB30									2.93 WEST FAIRFIELD	35.70						
<u></u>	<u> </u>	<u></u>			<u>.</u>	<u> </u>	<u> </u>		2.60 U. P. R. R. JUNCTION	33.10		v		<u> :</u>		
SC2		B		U. P.	R. R. JCT.	AND U. P. F	R. CROSSI	•	NCE OF 32.25 MILES, U. P. R. R. TIN	NE TABL	E AND S	VM	TRUCTIONS	WILL GOVE	RN.	
						OPERA				1	ENTH SU				<u> </u>	<u> </u>
SB. O.	Ya	rd Ya	d			1		1		0.00	DS	DNKORYX				I
	-	-	-			-			Time Over Subdivision			ZVB				
					I	We	itward tr		Average Speed Per Hour uperior to eastward trains	of th	e same	class.		1	<u> </u>	I
						S	EE ADDIT	IONAL SP	ECIAL INSTRUCTIONS PAGE	5 9 TH	ROUGH	17.				
EA	ST	WA	RD					SEVI	ENTH SUBDIVISIO	N				W	ESTW	ARD
	c				TH	IRD CL	ASS		m: m 11 N. 04					THIRD	CLASS	
	Cap	acity						96	Time Table No. 84	ee okane	ph and ne Calls	Signs	95			
on beri	5	ця				****_ =			Effective October 18, 1953	Spo	grap	0.6.00	Daily			
Station Number	Sidinge	Other Traoka		1				Daily Except Sun.	STATIONS	Distance from Spo	Telegra, Telephoi		Except Sun.			
SC32	Yard	Yard						L 3.00Pm	COEUR d'ALENE	80.94		XRKDY PVZ	A 10.50A			1
SC81	0	57						Af 3.10Pm	1.50 GIBBS	29.44		٧Z	Lf10.30Am			
'		<u> </u>	ETWEEN	SPO	KANE BRI	GE AND G	IBBS, A DIS	TANCE OF 1	1.94 MILES, C.M. ST. P. & P. RY. TIN	IE TABL	EANDS	PECIAL INS	TRUCTIONS	WILL GOVE	RN	<u></u>
3C19	18	0						L# 4.10Pm	SPOKANE BRIDGE	17.50		v	A 1 9.30A			
8C18-B	0	12						t 4.35	5.64 GREENACRES	11.86			. 1 9.10			
8C18	0	7					•••••	t 4.40	0.73 FLORA 5. 3 1	11.13		x	f 9.00			
8C7 8C6	0	7				•••••		1 5.00	MILLWOOD 1.03	5.82		X	t 8.25		ŀ	
8C6 3C5	287 0	0	•••••				•••••	1 5.05 1 5.15	ORCHARD AVE 1.42 PARKWATER	4.79 3.87			f 8.20			
SC2	0	117	· · · · · · · · · · · · ·					ر ۱ <i>.</i> د 	2.52 U. P. R. R. CROSSING	0.85		`vм				
вв о	Yard							▲ 5.30Pm	0.85 SPOKANE	0.00	D8	DNKORY XZVB	L 8.00A			
					·			2.30 12.87	Time Over Subdivision Average Speed Per Hour		-		2.50 10.92			
			<u> </u>	Eas	tward to	ains are	superior			i	No P	i is super		96		<u> </u>
l	Eastward trains are superior to westward trains of same class except No. 95 is superior to No. 96. SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 9 THROUGH 17.															

8 W	/ES	TW	ARD			EIGHTH SUBDIVISI	EASTWARD						
	Ca Capa	ur loity				Time Table No. 84 Effective October 18, 1953	e from Alley	h Calle	Signs				
Station Numbers	Sidings	Other Tracks				STATIONS	Distances from Spring Valley	Telegrap					
W77	Yard		1 1	1			36.73 36.44	C 0	YXRKD M		1		
W65	80	26				11-85 Steptoe	24.59						
₩60	0	29				4.76 CASHUP 4.56							
₩55 	0	28 							 М			•••••	
₩46	10	29			 •••••••		5.75	RO	DV				
SB40	28	59	· · · · · · · · · · · · · · · · · · ·		 ••••	SPRING VALLEY	0.00		JXRYO				
						Time Over Subdivision Average Speed Per Hour							

Westward trains are superior to eastward trains of the same class.

E ADDITIONAL SPECIAL INSTRUCTIONS PAGES 9 THROUGH 17.

ALL SUBDIVISIONS

1. INSTRUCTIONS GOVERNING THE OPERATION OF STREAMLINER TRAINS.

CLEARING OF STREAMLINERS.

The time of No. 1 must be cleared by westward first class trains not less than 5 minutes before No. 1 is due to leave the last station where time is shown, and by other westward trains not less than 10 minutes before No. 1 is due to leave the last station where time is shown.

The time of No. 1 must be cleared by eastward first class trains, except No. 2, not less than 10 minutes at all stations, and by other eastward trains not less than 15 minutes.

The time of No. 2 must be cleared by eastward first class trains, except No. 22, not less than 5 minutes before No. 2 is due to leave the last station where time is shown, and by other eastward trains not less than 10 minutes before No. 2 is due to leave the last station where time is shown.

The time of No. 2 must be cleared by westward first class trains, except No. 1, not less than 10 minutes at all stations, and by other westward trains not less than 15 minutes.

Within yard limits, yard engines and light engine movements must clear the main track not less than 10 minutes before Nos. 1, 21, 2 and 22 are due to leave last station where time is shown.

MAXIMUM PERMISSIBLE SPEED OF STREAMLINERS. Streamliner trains will be so designated in column with schedule number.

Maximum permissible speed of Streamliner trains will be designated by distinctive reflectorized roadway signs set in an upward angle of 45 degrees as prescribed in Item 2(b)-SPEED RESTRICTIONS GENERAL-ALL SUBDIVISIONS.

2. SPEED RESTRICTIONS GENERAL.

ZONE TERRITORIES AND MAXIMUM PERMISSIBLE SPEED OF PASSENGER TRAINS, INCLUDING STREAMLINERS, OPERATING VIA ROUTES INDICATED BELOW:

Stations			Maximum S Westward	
Diations		d 1470.5	50	55
	1470.5 "	1472.5		50
Hillyard				35
Hillyaru	1479 6 4			20
Spokane	1473.0	14//.0		12
	1477.5 " 1478.1 "	14/0.1		30
	14/0.1	14/ 3.4		
Ft. Wright	14/ 3.4	14/0.0		40
	1479.8 "	1403.1	45	45
Lyons	1489.1 "	1514.5	79	7 9
Canby	1514.5 "	1520.6	60	60
Bluestem	1520.6 "			60
Didestein	1520.7 "			60
	1522.2 "			50
Harrington				60
Training to L	1527.0 "	1529.0		55
	1529.0 "			65
Lamona	1542.0 "	1542.1	65	35
Odessa		1556.7	65	65
040004	1556.7 "	1559.0	60	60
	1559.0 "	1569.2		65
Marlin		1569.7		50
	1569.7 "	1571.9		65
	1571.9 "	1572.1		55
	1572.1 "			65
Wilson Creek .	1573.2 "	1579.1		70
	1579.1 "	1587.9		79
	1587.9 "	1588.4		70

Adrian15	88.4	and	1614.8	79	79
Quincy16			1618.3		60
	18.3		1620.7		55
	20.7		1622.8		45
	22.8		1623.6		35
Trinidad16			1628.5		45
	28.5		1640.7		60
Rock Island16			1642.3		35
Malaga16			1646.8		60
Wenatchee16			1649.9		55
	49.9 51.2		1651.2 1653.3		35 45

(a) Where Automatic Block and Interlocking Rules and Signal Indications require movement at RESTRICTED SPEED, such movements must be made prepared to stop short of train, obstruction, or switch not properly lined and on the lookout for broken rail or anything that may require the speed of a train to be reduced, but not exceeding 15 MPH or as much slower as necessary and where conditions require the movement must be controlled so stop can be made in time to avoid accident.

(b) Maximum permissible speed of passenger, freight and mixed trains, including Streamliners, will be designated by distinctive reflectorized roadway signs set in an upward angle of 45 degrees. Except as directly affected by speed restrictions prescribed in Items 1 and 2—ALL SUBDIVISIONS—and other speed restrictions covered by Item 2 under individual Subdivisions, the 45 degree signs designate zone speed territories and the numerals thereon indicate in miles per hour the maximum permissible speed which will govern until the next zone sign is reached.

When the movement is from a higher to a lower speed zone, the zone sign is located approximately one mile from the point where the lower speed becomes effective. At the end of this one mile is located a reflectorized angular Restricting Sign, yellow background with black stripes, indicating the point where lower speed becomes effective. Lower speed to govern until entire train passes next zone sign.

When the movement is from a lower to a higher speed zone, the 45 degree sign is located at the point where speed may be increased.

When operating against the current of traffic in double track territory, trains must not exceed the maximum permissible speed prescribed by the 45 degree sign with the current of traffic. This does not modify Rule 93.

The 45 degree sign has two sets of figures. The numerals pre-ceded with letter "P" apply to passenger trains, including Streamliners, and letter "F" to freight and Mixed trains.

(c) When passenger trains, including Streamliners, are handled by Deisel engines, Electric engines, passenger or freight steam engines, the train will not exceed the maximum speed authorized by Speed Limit Plate on engines, and will be governed by the 45 degree signs where a lower speed is prescribed.

When freight cars, except cars equipped with steel wheels, air signal and steam heat lines, are handled in passenger trains, including Streamliners, the train will not exceed maximum permissible speed for freight trains in the territory operated.

(d) Speed shown on Speed Limit Plate on engines must not be exceeded.

(e) Steam engines backing up	20 MPH
Steam engines in forward motion running light or	
with caboose only	85 MPH
Diesel and Electric engines light or with caboose only	50 MPH
Trains handling, not in actual service, derricks, pile ditchers, cranes, shovels, Jordan spreaders, wedge plows	
On Main Lines	
Except on six degree curves or sharper and on.	
Branch lines	15 MPH

Trains handling ore cars or air dump cars loaded with ore or gravel and scale test car on Main Lines	30 MPH
except on 6 degree curves or sharper, and on Branch Lines	20 MPH
Unless conditions require a further speed restriction, trains or engines moving against the current of traffic on double track thru interlockings	15 MPH
Trains or engines moving on main routes actuating points of spring switches	
Trains or engines moving in facing point direction at spring switches without facing point lock	
Trains or engines thru No. 20 turnouts at: Hillyard, end of double track east and west end of	85 MPH
Fort Wright, end of double track. Fort Wright, SP&S Junction.	-
Bluestem, end of double track. Lamona, end of double track.	
Lamona, east siding switch. Wilson Creek, west siding switch. Stratford, east and west siding switch.	
Adrian, east and west siding switch. Quincy, east and west siding switch.	
Voltage, east siding switch. Malaga, east and west switch.	
Appleyard, #1 switch east lead. Appleyard, #2 crossover switch.	
Trains or engines thru No. 15 turnouts at: Lyons, east and west siding switch.	25 MPH
Nemo, east and west siding switch. Odessa, east and west siding switch.	
Ephrata, east and west siding switch. Trinidad, east and west siding switch.	
Voltage, west siding switch. Wenatchee, east and west crossover switch wes	t end of

wenatchee, east and west crossover switch west end of yard.

On single track, trains containing such cars must be at stop when on siding or adjacent track when meeting or being passed by other trains, except when there are more cars than siding will hold, it is permissible for such train to pull by other train at restricted speed.

8. MOVEMENT OF ENGINES DEAD IN TRAINS.

Class O and larger engines will be placed not to exceed 15 cars behind road engine. In electrified zone only class R engines will be handled on head end, all others near rear.

Class F-8 and smaller engines will be placed next ahead of caboose.

Diesel and Gas-Electric engines 2302-2341 must be handled on rear of train.

Not less than five cars will be placed between all engines.

Trains handling Great Northern steam engines dead in train with side rods on both sides will not exceed 40 MPH; and without side rods will not exceed 10 MPH.

Trains handling foreign line steam engines with side rods on both sides will not exceed speed designated by Superintendent; and without side rods will not exceed 10 MPH.

Engines that have any of the truck or driving wheels removed will not be moved in a train without authority of Superintendent. Trains handling Electric, Diesel and Gas-Electric engines in tow dead in train will not exceed following speeds:

Engine Number

Maximum Speed

1 to 28, 75 to 170, 247 to 249, 253 to 259, 262 to 265.		
1 to 28, 75 to 170, 247 to 249, 253 to 259, 262 to 265, 307 to 317, 400 to 468	50	MPH
175 to 232, 271 to 274, 276 to 279, 550 to 572, 600 to		
655		MPH
250, 251, 260, 261, 266 to 270, 275, 280, 281, 350 to		
365, 500 to 512	75	MPH
2302 to 2324	50	MPH
2325 to 2339	60	MPH
5000 to 5008	45	MPH
5010 to 5019	55	MPH

4. ELECTRIC BRAKES.

In event of failure of the electric straight air brakes, or if electric brakes cannot be used on account of cars not equipped with electric air brakes being handled in the train, the automatic air brake will be used.

Between terminals, if engineer finds electric brakes not operating properly he shall immediately change brake valve over to automatic air brake operation and open circuit breaker to electric brake circuits. After changing from electric straight air brake operation to automatic air brake operation the train will be handled with automatic air to the next terminal where standing terminal air brake test can be made by carmen. Terminal brake tests should then be made with electric straight air and with automatic air and train may be handled with electric straight air if brakes function properly during terminal test.

5. Before leaving any engine terminal enginemen will make proper tests and inspections of water glasses, gauge cocks, water column and injectors, and will not leave the terminal unless all these are in proper working order.

Should enginemen on steam engines find that the water is not in sight in water glass and if water cannot be raised to bottom gauge cock or water glass by opening throttle, on oil burning engines the fire must be extinguished immediately and on coal burning engines the fire must be knocked out or smothered to the extent there will be no damage done to the crown sheet. If water can be raised to the bottom gauge cock or water glass, the water level should be built up by use of the pump, or injector, or both.

Should the low water alarm whistle blow, on any engine so equipped, enginemen will immediately ascertain where the water level is in the boiler by blowing out water glasses and water column, and being sure that water glass mounting valves are open and if water cannot be raised to the bottom gauge cock or water glass by opening throttle, enginemen will be governed by instructions in the preceding paragraph.

- 6. Under Rule 24, engine number only will be displayed in indicators on engines so equipped. This will also apply when our engines are operating over Northern Pacific tracks. Between Klamath Falls and Chemult, Southern Pacific Rules will govern.
- 7. When two or more Diesel or Electric engine units are coupled together the numerals and suffix letter, where provided, of the leading unit will be illuminated at all times when in service. The numerals and suffix letter of trailing units must not be illuminated. The numerals and suffix letter of the leading unit only will be

The numerals and suffix letter of the leading unit only will be used in train orders as prescribed by Consolidated Code Rule 206.

- 8. Gas-Electric engines must not be fueled while occupied by passengers, or coupled to cars occupied by passengers.
- 9. Air hose on Diesel and Electric engines must be hooked up in hose fastener when not in use.
- 10. EMPLOYES WILL BE GOVERNED AS FOLLOWS ON EN-GINES, PASSENGER AND FREIGHT CARS EQUIPPED WITH ROLLER BEARINGS:

Roller bearing failures on cars or engines equipped with roller bearing journal boxes may be due to lack of oil or grease. If the box is not blazing, the oil plug in the cover should be removed and engine or valve oil added. Oil must never be added to a box that is blazing. Grease lubricated roller bearing boxes have grease plugs locked with metal strap which must be cut off with chisel before plug can be removed. After the oil has been added and plug replaced, the train should proceed at reduced speed and care exercised until it is apparent that the box will run cool. If fire develops in roller bearing box on any equipment, it must be closely watched, train moved slowly, and Superintendent notified from first available point of communication, who will prescribe for the movement.

Some engines and cars equipped with roller bearings have heat indicators or stench bombs inserted in the housing of boxes which release a strong pungent odor in the event of excessive journal box temperatures. When this odor is detected, train must be stopped at once and box located. Compare the temperature of this box with other boxes on the same engine or car, check the oil level, and if there is no evidence of overheating, train may proceed, but if the box is overheating proceed only as instructed in the preceding paragraph.

Ore cars and covered hopper cars equipped with roller bearings have the lettering "TIMKEN ROLLER BEARINGS" stencilled beneath the lettering "GREAT NORTHERN" on each side of the car.

Cars and engines equipped with roller bearings must not be allowed to stand alone, even on level track, without brakes being adequately applied.

11. COOLING AND STEAM BOILER WATERING FACILITIES FOR DIESEL ENGINES ARE PROVIDED AT THE FOLLOW-ING INTERMEDIATE STATIONS:

FIRST SUBDIVISION

LAMONA	Boiler a	nd	radiato	r.
WILSON CREEK	"	"	"	
QUINCY	"	"	"	
EDWALL	Radiato	r o	nly.	
HARRINGTON			"	
EPHRATA	. "		"	
COLUMBIA RIVER	. "		""	
ODESSA	**		**	
TRINIDAD	66		**	

SECOND SUBDIVISION

OROVILLE	Radiator only.
OMAK	Boiler and Radiator.
PATEROS	Radiator only.
CHELAN	
ENTIAT	66 66

THIRD SUBDIVISION

NORTHPORTRadiator only.

FOURTH SUBDIVISION

REPUBLICRadiator only.

FIFTH SUBDIVISION

SIXTH SUBDIVISION

MOSCOWRadiator only. GARFIELD

SEVENTH SUBDIVISION

COEUR D'ALENERadiator only.

EIGHTH SUBDIVISION

COLFAXRadiator only. ROSALIA

12. Trains 1, 2, 3, 4, 7, 8, 11, 12, 19, 20, 23 and 24 carry 100 ft. of steam hose in two 50 ft. lengths equipped with standard vapor and engine steam dome connections for emergency use in event of steam failure on train engine and non-steam train line engine furnished to handle train. In case of steam line failure on a car, connect both hoses together to run around such car so can be taken to first terminal, using combination standard Vapor and steam dome connections attached to reel. Car must be drained before proceeding.

- 13. Under Rule 2, watches that have been examined and certified to by a designated inspector must be used by train dispatchers and yardmen.
- 14. Brakemen with less than one year of experience should not be used as flagmen except in emergency, and then Superintendent will be notified by wire.
- 15. When operating snow machines in non-block signal territory, no train should be permitted to follow closer than a station apart, when that cannot be done, they will be blocked not less than thirty minutes apart.
- 16. After severe blizzard or dirt storm, employes on first train over road must exercise care to avoid accident caused by striking drift without first having drifts faced with hand shovels, cutting in far enough to get beyond the hard snow and giving a perpendicular wall to strike against instead of slope or wedgelike shape. When operating snow dozer, conductor in charge will ride in dozer. On snow and dirt dozers every precaution must be taken to see that cage, flangers and wings clear all obstacles when in service and are properly secured when in thru trains, and dozers properly turned. Hand screws must be tightened to raise flangers on dozers as high as possible before making a back-up movement, and must not be released until the dozing work is actually to start. Hand screws holding the cage on dozers must be tightened or chains otherwise fastened except when dozer has air in cylinders and is attended by an employe.
- 17. Loaded dump cars should not be handled on double track after dark, but if necessary to do so, close watch must be kept by trainmen and if a car dumps its load, train must be stopped and protection afforded on the opposite track.
- 18. Unless otherwise provided, when passenger trains are operated against current of traffic on double track or through sidings, conductors shall notify Railway Postal Clerks; trains shall stop at points where U. S. Mail is usually picked up and conductors are responsible for delivery of mail to Postal car.
- 19. Conductors will report by wire all flat spots on wheels of passenger cars. Any cars having flat spots on wheels of more than two and one-half inches long must be set out.
- 20. Due to limited overhead clearance at tunnels and structures, employes are warned to keep off top of cars of extreme height and width when handled in trains and yards, also such standing cars in electrified zone, except in emergency. In absence of previous advice on such cars, wire proper officer for instructions.
- 21. The Railway Company is responsible for proper handling of perishable freight on road and at points where Western Fruit Express Company does not maintain representatives. Conductors on trains handling perishable freight will ascertain from waybills class of service required and light or extinguish heaters and manipulate vents in accordance with current instructions provided for handling perishable freight issued by the National Perishable Freight Committee.
- 22. Placarded loaded tank cars handled in through freight trains shall not be nearer than 6th car from engine, occupied caboose or passenger car.

Cars placarded "Explosives", "Inflammable", "Corrosive Liquids", or "Poison Gas" handled in through freight trains, local and mixed trains, shall not be nearer than 16th car from engine, occupied caboose or passenger car.

When length of train will not permit handling of cars as prescribed above—ANY PLACARDED CAR, loaded with above commodities—shall be placed near middle of train, but not nearer than 2nd car from engine, occupied caboose or passenger car.

When switching such cars in terminal yards they must be separated from engine by at least one non-placarded car. When placarded cars described above are handled in freight trains made up in "blocks" or classifications, placarded car or cars shall be placed near middle of the "block" or classification, but not nearer than 6th car from engine, occupied caboose or passenger car. When such placarded cars are placed in trains they must not be placed next to each other, next to refrigerators equipped with gas-burning heaters, stoves or lanterns, or next to loaded flat cars, or gondola cars containing lading higher than ends of car that is liable to shift.

Carload express shipments of explosives, sealed and placarded, may be handled on passenger trains; LCL shipments may be made in so-called peddler car with messenger in charge when such car is assigned to the handling of express and baggage exclusively.

Terminal or pick-up points enroute must furnish conductor and engineer Form 250 showing consecutively location in train of all cars placarded "Explosives". At points other than terminals where crews change, notice will be transferred from crew to crew.

Employes will be guided by further instructions governing handling of loaded tank cars, Explosives, Inflammables, Corrosive Liquids, and Poison Gas found in I. C. C. Regulations and Consolidated Code Rules 726(C) and 808.

23. The normal position of a spring switch with facing point lock is identified by a color light type signal displaying a "lunar white" light for train or engine movements in a trailing point direction and for movements in facing point direction when conditions require.

The normal position of a spring switch without facing point lock is identified by a triangular yellow target on switch stand with letter "S" in black and "lunar white" light in switch lamp in place of green light displayed in both directions thru or over the switch.

Trains departing from stations, either from siding or main track in trailing point movement actuating points of spring switches, a member of crew must observe indication of governing signal in opposite direction after rear end of train has passed thru switch to ascertain if switch points return to normal position. If this signal indicates Stop and no immediate train movement or other cause is evident report the fact to Superintendent from first available point of communication.

During and immediately following snow storms or violent wind storms, spring switches must be operated by hand and relined to normal position before heading out through switch in trailing point movement, actuating switch points, to insure switch is in proper operating condition.

INDICATORS AT SPRING SWITCHES.

A Switch Indicator, consisting of a single yellow light unit (normally dark) and a switch-key-controller mounted on an iron mast located at clearance point of a siding, must be operated by a member of the crew who, together with engineer, must observe and be governed by its indication before fouling main track or making movement from siding to main track thru a spring switch in automatic signal territory, unless the movement is made immediately after an opposing train has passed the switch and Automatic Signal at leaving end of siding indicates "Proceed".

If Indicator displays a yellow light when switch-key-controller is operated, train or engine movement to main track may be made immediately in accordance with train rights and operating rules. Display of yellow light must continue until leading wheels have passed clearance point.

If Indicator does not display a yellow light when switch-keycontroller is operated, train or engine movement to main track may be made in accordance with train rights and operating rules, after operating spring switch by hand; waiting three minutes and taking every precaution to provide proper protection.

To operate Switch Indicator, insert switch key in controller and turn clockwise toward "R", hold a few seconds and remove key. If yellow light is displayed and intended movement is not made, insert switch key in controller and turn counter-clockwise toward "N" to restore signal system to normal condition to avoid delay to trains on main track.

Switch-key-controller must never be operated toward "N" after having been operated toward "R" if intended movement to main track is to be made.

- 24. Facing point locks on hand operated switches are indicated by a six inch yellow stripe painted on target staff. Be positive locking device is restored to normal position after using. A running switch must not be made thru this type switch.
- 25. DRAGGING EQUIPMENT DETECTOR INDICATOR consists of a single white light unit (normally dark) with a circular background mounted on signal or other mast. When white light is displayed, train must be stopped and inspected for dragging equipment. Notify Superintendent from first available point of communication.
- 26. Rule 204(A) prescribes that copies of train orders will be furnished the rear trainman, such orders will only be furnished on trains designated: Nos. 1, 2, 3, 4, 7, 8, 9, 10, 27, 28, 29, 30, and sections thereof; also, extra passenger train whether operated as section of

regular train or as a passenger extra.

27. OSCILLATING EMERGENCY RED HEADLIGHT will be immediately displayed by day or night when a train is disabled or stopped suddenly by an emergency application of air brakes or when engineer and conductor find it necessary to stop train due to some defect which might cause accident, over-running clearance point at meeting and waiting points, end of double track or junction.

Engineer of an approaching train observing display of emergency red headlight must stop before passing and be governed by conditions existing. If operating on adjacent track, ascertain and if safe for passage, then proceed at restricted speed until train is passed.

OSCILLATING EMERGENCY RED REAR END LIGHT is of two types—Automatic Control—Portable Manual Control—and except as otherwise provided must be displayed by day or night each time train stops or is running at speed less than 18 MPH. Automatic Control type automatically functions in this manner. However, when train running at speed above 18 MPH and moving under circumstances in which it might be overtaken by another train or engine and during foggy and stormy weather, light may be operated manually with emergency switch and employes to afford other protection prescribed by rule.

THE USE OF EMERGENCY RED HEADLIGHT AND REAR END LIGHT DOES NOT IN ANY WAY RELIEVE ENGINE-MEN AND TRAINMEN FROM RESPONSIBILITY OF COM-PLYING WITH RULES 99 AND 102.

Emergency red rear end light must be extinguished: when standing at origin and terminus stations of train run; when switching being performed from rear; when on siding to be passed by another train; and, when another train operating on adjacent track is approaching from rear, but not until it is known such train is not on same track.

Portable light must be removed before coupling to rear of such car.

Oscillating white light on engines will be displayed in addition to standard headlight governed by Rules 17 and 17(B). In case of headlight failure it can be used as emergency headlight or as a focus light by push button control if desired.

Enginemen and trainmen on trains and engines equipped with oscillating emergency red lights must familiarize themselves with the operation of the lights.

- 28. Rule D-97 is in effect on this division.
- 29. Trains handling flat or skeleton cars loaded with logs must stop at appropriate locations immediately before passing over through-truss bridges or through tunnels and make thorough inspection of all cars of logs in their train, making certain train and lading are in safe condition before proceeding. Extra stops en route will be made for this purpose when in the judgment of the conductor it is necessary.

Trainmen must maintain watch behind their trains for logs that may have rolled off cars and if main track is fouled take prompt action to protect trains.

On double track, conductors must notify train dispatcher when logs are to be handled and the log train must be at stop when

being passed by other trains, except that when two trains handling logs are passed, either one should stop until the other train has pulled by whether on siding or double track. On single track, trains handling logs must be at stop when meeting or being passed by passenger and freight trains, except when there are more cars than siding will hold, it is permissible for log train to pull by such trains at restricted speed. Unless conditions require further speed restrictions, trains handling logs must not exceed 25 MPH.

- 30. Red signs on frost boxes of water and oil tanks. In case of emergency, close large valve in frost box.
- 31. Canadian Maintenance of Way flagging Rules 40 through 49 found on pages 216 through 220 in the Consolidated Code are in effect in Canada.

32. EMERGENCY TELEPHONES.

Spokane, when stopped by Stop-indication at automatic block signal 1475.3, telephone before blocking street crossings— Fort Wright, east end bridge 274 ______ Booth Fort Wright, west switch ______ Booth Highland Quarry ______ Pole Booth Bluestem, end double track ______ Booth Lamona, east of water tank _____Booth end double track _____Booth Wilson Creek, middle of sidingBooth Ephrata, east wye switchBooth Trinidad, water tank ______ Booth West switch ______ Booth Gravel spur _____Pole booth Appleyard, east lead switchPole booth WaysideBooth DennisonBooth ClaytonBooth Loon LakeBooth SpringdaleBooth GraysBooth AddyBooth Arden Booth EvansBooth MarbleBooth Orient _____Booth Danville—1 mi. west _____Customs_office CurlewBooth Millwood Transfer trackBooth CardersBooth Flora Jct.Booth Spokane BridgeBooth Coeur d'Alene, MP 32Booth GibbsBooth

FIRST SUBDIVISION

(Main Line)

1.	MAXIMUM PERMISSIBLE SPEED FOR 7	RAINS.	
	Between	Passenger	Freight
	Hillyard and Lyons	45 MPH	35 MPH
	Lyons and Wenatchee	79 MPH	50 MPH

2. SPEED RESTRICTIONS.

Spokane, public crossing Howard Street	12 MPH
other public crossings	20 MPH
Bridge 270, Spokane, R, SP&S E-1, Z-6	
Bridge 273, Spokane, Q-1, S-1, N-3, SP&S E-1	20 MPH
R, SP&S Z-6	10 MPH
Bridge 274, Fort Wright, Q-1, R, S-1, N-3,	
SP&S E-1, Z-6	20 MPH
Between Fairchild and Geiger Field:	
All trains on straight track	15 MPH
on curves and public crossings	8 MPH
Ephrata, 2.2 miles east of, Air Base Washington spur	
Between Home Signals of Interlocking at:	20 MPH
Spokane, U.P.R.R. Crossing.	

8. ENGINE RESTRICTIONS ON INDUSTRY TRACKS.

Engines heavier than O class not permitted on following tracks: Between Fairchild and Geiger Field, and on spur track serving Fairchild Air Force Base Yard at Fairchild. Ephrata, 2.2 miles east of, Air Base Washington Spur, south of

siding.

4. TRAIN REGISTER EXCEPTIONS.

Hillyard, First class trains and passenger extras register by ticket.

Spokane, first class trains and trains originating or terminating at passenger station will register and receive clearance.

Appleyard, register is for second and inferior class trains; passenger extras will register by ticket.

Wenatchee, register is for first class trains, Nos. 253-254 and passenger extras.

5. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

Spokane, clearance issued and signed by the Superintendent will confer the same authority to a first class train as though received at its initial station.

6. RESTRICTED CLEARANCES.

In electrified zone all wires must be considered alive unless a clearance has been obtained from operator at Skykomish Substation.

Appleyard, and between Appleyard and Wenatchee, high voltage electric wires over tracks will not clear man on top of cars. Train and engine men must keep off top of cars and engines passing thru this territory, except in emergency, then use extreme caution.

The following overhead wires crossing our track and trolley in electrified zone, do not have standard clearance of 27 ft. from top of rail:

- Double track extends between Hillyard and Fort Wright, except over bridge 274 and S.P.&S. Jct. which is governed by interlocking signals.
- 8. Spokane, Trent avenue crossing protected by watchmen between hours 7:00 A.M. and 11:00 P.M. daily, outside these assigned hours a member of crew must be on ground at crossing to protect movement.
- Spokane, City Ordinance prohibits sounding engine whistle within city limits, except to prevent accident not otherwise avoidable, or to signal an interlocking, or to communicate with a flagman.
- 10. Fort Wright, instructions for operation of electric switch locks Military Spur and west siding switch posted in iron box locked with switch lock.
- 11. Wenatchee, westward trains moving from W-O Line lead to First Subdivision and required to wait for westward trains on First Subdivision shall stop east of sign reading "Wait Here". For further details and push button operation see instructions posted in iron box locked with switch lock.
- 12. Normal position of the switch on the siding at Adrian, connection with the Northern Pacific is for the Great Northern.

14	Le contra de la cont		
13.	Appleyard, Yard lead switch and crossovers main track to yard lead are located as follows: #1 switch designating the east lead200 ft. west of Br. 361. #2 crossover switch-100 feet west of MP 1647. #3 crossover switch-at culvert 1647.60. Wenatchee: #1 crossover, one mile east of depot. #2 crossover, 800 ft. east of depot. #3 crossover, 670 ft. west of depot. #4 crossover, 685 ft. west of depot. #5 crossover, 685 ft. west of depot. Olds crossover, 3 miles west of depot. Crossovers 1, 2 and 4 are trailing point, and 3, 5 and Olds are facing point for eastward trains.		MANUAL I Spokane, 1. Fort Wright Whistle sign Spokane, UI Main track GN-SI Ry T GN-SI Ry T Fort Wright Main Track Main Track Siding GN MANUAL SWITCHES
	SPEED TEST BOARDS. Engineers shall test speed of their trains passing following points as compared with Speed Table: Westward, Between MP 1492 and MP 1493 just east of Fairchild, Eastward, Between MP 1612 and MP 1613 two miles west Winchester, Between MP 1644 and MP 1645 just west Malaga.		Hillyard Interlocking (end of dou end of yard and the sing by operator The "home train and e westward he signals at w
15.	CROSSOVERS ON DOUBLE TRACK. Facing point. Trailing point. MP 1473.14 west of Hillyard. MP 1476.69 on Br. 269, Spo- kane. MP 1477.22 east of Br. 270, Spokane. MP 1477.61 (Scissors) on Br. 278 west of Spokane passen- ger depot. MP 1478.41 west of Br. 273, Spokane.		Trains and e ing home sig with Rule 60 Instructions in iron boxe Whistle sign Eastward tr To main tra To yard Westward to To westward To eastward
16.	 S60' east of depot, Harring- ton. SPRING SWITCHES WITH FACING POINT LOCK. Lyons, east and west siding switch. Fairchild, east and west siding switch. Espanola, east and west siding switch. Edwall, east and west siding switch. Lamona, east siding switch. Odessa, east and west siding switch. Irby, east and west siding switch. Stratford, east and west siding switch. Stratford, east and west siding switch. Stratford, east and west siding switch. Ephrata, east and west siding switch. Ephrata, east and west siding switch. Ephrata and west siding switch. 	21.	AUTOMATI Bluestem Interlocking lowing excep Lamona, wh siding, sidin home signal Lamona, eas westward tra ton located main track. Bluestem, w after eastwy push button main track.
	Trinidad, east and west siding switch. Voltage, east and west siding switch. Malaga, east and west siding switch. Appleyard, east switch long lead. east crossover switch long lead. Wenatchee, east and west crossover switch west end of yard. Normal position is for main track.	22.	SWITCH IN Rock Island, Ephrata, inc Morrison-Kn Member of c ment from t
17.	SPRING SWITCHES WITHOUT FACING POINT LOCK. Hillyard, east end yard, connection of east yard lead to track No. 5. Normal position is for track No. 5.		controller in
18.	DRAGGING EQUIPMENT DETECTOR INDICATORS. Westward, on signal; 1623.8 approximately two miles east Trinidad. 1625.7 just east Trinidad.		
	1640.1 just west Rock Island.	1.	MAXIMUM

NTERLOCKINGS.

Spokane, 1.17 miles east of,
Fort Wright
Whistle signals for routes:
Spokane, UP RR. crossing:
Main track
GN-SI Ry Transfer No. 11 long. 1 short.
GN-SI Ry Transfer No. 2
Fort Wright:
Main Track GN Ry
Main Track SP&S Ry1 long, 1 short.
Siding GN Ry
MANUAL INTERLOCKINGS WITH DUAL CONTROL
SWITCHES.
Hillyardend of double track east and west end of yard,
Interlocking includes interlocked switches at east end of yard
(end of double track, yard lead, and safety switch); at west
end of yard (end of double track, yard lead and spike yard lead)
and the single main track between them electrically controlled
by operator at depot.
The "home signal limits" (Rule 605) of this interlocking for train and engine movements on main track extend from the
train and engine movements on main track extend from the
westward home signals at east end of yard to eastward home
signals at west end of yard.
Trains and engines receiving a proceed indication of the govern-
ing home signal will proceed, regardless of class, in accordance
with Rule 605, observing all governing signal indications.
Instructions for operation of Electric Locks and Releases posted
in iron boxes locked with a switch lock.
Whistle signals for routes west end of yard:
Eastward trains.
To main track
To yard
Westward trains.

d main track1 long. 1 main track2 long, 1 short.

C INTERLOCKINGS.

dual control switch end of double track. dual control switch end of double track. s operate automatically for all movements with folptions:

hen movement is to be made from double track to ag switch must not be lined until engine is within limits.

stward train moving out of siding immediately after ain has passed, must operate switch release push buton eastward home signal to line route for eastward

westward train moving out of siding immediately ard train has passed, must operate switch release a located opposite switch to line route for westward

NDICATOR.

indicator located at Alcoa Spur.

dicator located at Air Base Washington Spur and udson Spur.

rew who is to line switches for train or engine movethe spur to main track must first operate switch key accordance with Item 23 Page 12 of this time table.

SECOND SUBDIVISION

(Oroville Line)

PERMISSIBLE SPEED FOR TRAINS.

Between	Passenger	Freight
Wenatchee and Janis	35 MPH	35 MPH
Janis and Oroville	35 MPH	30 MPH
Oroville and Hedley	25 MPH	25 MPH
Orovine and neurey	20 111 11	20 MI II

Eastward, on signal;

1623.8 approximately two miles east Trinidad. 1621.8 approximately one mile west Crater. 1480.2 just west Ft. Wright.

2. SPEED RESTRICTIONS. H-4 engines, on straight track ______ 80 MPH on curves _____ 20 MPH

3. ENGINES RESTRICTIONS.

Engines heavier than class indicated are prohibited: Between Wenatchee and Janis, O-4 and 1600 H.P. Diesels, not more than 2 units coupled.

Between Janis and Oroville, F-8, H-4 and 1600 H.P. Diesels, single unit.

Between Oroville and Hedley, G-3, G-4 and 1600 H.P. Diesel single units.

Additional units must be separated not less than five cars.

. Nighthawk-Keremeos, trains will not pass International Border without permission of Customs and Immigration Inspectors at Oroville.

THIRD SUBDIVISION

(Kettle Falls-Nelson Lines)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Troup Jct. and South Nelson	15 MPH
South Nelson and Kettle Falls	20 MPH
Kettle Falls and Dean	80 MPH

 2. SPEED RESTRICTIONS.
 8 MPH

 Northport, wye tracks
 8 MPH

 Dolomite, spur tracks
 10 MPH

 Between Northport and Troup Jct., trains handling logs
 15 MPH

3. ENGINE RESTRICTIONS.

Engines heavier than class indicated are prohibited:

Between Dean and Kettle Falls R-1 and multiple unit diesels. Between Kettle Falls and Northport M, 1600 H.P. Diesel double units.

Between Northport and Nelson 1600 H.P. Diesels single units. Additional units must be separated not less than five cars. Northport wye O engines prohibited.

- 4. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B). (a) Great Northern clearance received at Nelson will clear train at Troup Jct.
 - (b) Kettle Falls, all trains must secure clearance.
- 5. Troup Jct., northward trains must stop clear of junction switch before entering Canadian Pacific main track and know track is clear.
- 6. Northport-Waneta, trains will not pass International Border without permission of Customs and Immigration Inspectors.
- 7. SWITCH INDICATORS.

Dean, indicator for movements from Spokane division Third subdivision to Kalispell division Fourth subdivision.

Member of crew who is to line switches must first operate push button "R" for route desired and hold few seconds. Both trainman and engineer must observe and be governed by indicator before lining switches or fouling main track.

Push buttons and instructions for their operation are posted in iron box locked with a switch lock.

FOURTH SUBDIVISION

(Republic Line)

- 1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS. Between

Between Kettle Falls and Boyds, 1600 H.P. Diesels double units, heaviest permitted.

Between Boyds and Republic, F-8 and 1600 H.P. Diesel single units.

Additional units must be separated not less than five cars.

- 4. Kettle Falls, normal position of junction switch is for Third Subdivision.
- 5. Laurier-Danville, trains will not pass International Border without permission of Customs and Immigration Inspectors.

FIFTH SUBDIVISION

(Mansfield Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS. Between

Columbia River and Mansfield 20 MPH

- ENGINE RESTRICTIONS.
 F-8 and 1600 H.P. Diesels single units heaviest permitted. Additional units must be separated not less than five cars.
- 3. Columbia River, normal position of junction switch is for siding on First Subdivision.

SIXTH SUBDIVISION

- 8. ENGINE RESTRICTIONS.

G-3 and 1600 H.P. Diesels multiple units heaviest permitted.

4. RESTRICTED CLEARANCES.

Spokane, bridges 1.3, 1.5 and 1.6 will not clear man on top or sides of cars or engines. Train and engine men must keep off top or side of cars and engines while passing over bridges, except in emergency and then use extreme caution.

- 5. Operation between U.P. R.R. Crossing on Seventh Subdivision and U.P. R.R. Junction, 2.60 miles west of West Fairfield, is joint with U.P. R.R. and their timetable and special instructions will govern.
- Trains leaving Spokane will be cleared at Spokane Telegraph office for operation east of U.P. R.R. Junction and cleared at N.P. Crossing by U.P. R.R. dispatcher for movement U.P. R.R. Crossing on Seventh Subdivision to U.P. R.R. Junction, 2.60 miles west of West Fairfield. Trains leaving U.P. R.R. Junction for movement over Union Pacific line will be cleared by U.P. R.R. dispatcher at Fairfield on the U.P. R.R.

Trains will register at N.P. Crossing by ticket.

Normal position of U.P. R.R. Junction switch is for Great Northern main track.

Telephone in booth near U.P. R.R. Junction to enable Great Northern crews to call the operator at Fairfield.

SEVENTH SUBDIVISION (Coour d'Alone Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS. Between

Spokane and Coeur d'Alene 25 MPH

8. ENGINE RESTRICTIONS.

Between Spokane and Spokane Bridge, 1600 H.P. Diesels in multiple units heaviest permitted.

Between Spokane Bridge and Coeur d'Alene, 1600 H.P. Diesel, single unit, heaviest permitted.

Additional units must be separated not less than 5 cars.

4. RESTRICTED CLEARANCES.

Bridges C 7.7, 7.8 and 7.9 3200 feet west Millwood, restricted side clearance.

- 16
- 5. Coeur d'Alene, trains and engines must stop before passing over 11th Street and Mullan Avenue crossings and movement must be protected by flagman on the ground at the crossing.
- 6. Coeur d'Alene, trains and engines must stop and sound two blasts of engine whistle before proceeding over Diamond Drill Crossing.
- 7. Operation between Spokane Bridge and Coeur d'Alene, is joint with CMStP&P RR and their Time Table and Special Instructions govern.

Trains leaving Spokane will be cleared thru Great Northern dispatcher to Spokane Bridge and will be cleared at Spokane Telegraph office by CMStP&P RR dispatcher for movement from Spokane Bridge to Coeur d'Alene. Trains leaving Coeur d'Alene will be cleared by Great Northern dispatcher for movement from Spokane Bridge to Spokane and by CMStP&P RR dispatcher at their office in Coeur d'Alene for movement from Coeur d'Alene their office in Coeur d'Alene for movement from Coeur d'Alene to Spokane Bridge.

8. MANUAL INTERLOCKINGS.

be governed by dwarf signal located at base of westward twoarm interlocking home signal.

EIGHTH SUBDIVISION

(Colfax Line)

- 1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS. Retween __ 25 MPH
- Spring Valley and Colfax
- 2. ENGINE RESTRICTIONS. G-3 or 1600 H.P. Diesels single units heaviest permitted. Additional units must be separated not less than five cars.
- 3. RESTRICTED CLEARANCES. Colfax tunnel and bridges 71.6, 72.3 and 72.4 will not clear man on top or sides of cars and engines.
- 4. Colfax, trains and engines while switching or moving in and out of depot must use extreme care in passing over North and Last Streets account restricted view.
- 5. SEMI-AUTOMATIC INTERLOCKINGS. Colfax. 0.29 miles west of Normal position is stop for Great Northern. Instructions for operation are posted in box locked with a switch lock.
- 6. RAILROAD CROSSING PROTECTED BY GATES. Thornton, 0.57 miles west of...... UP RR crossing Normal position is stop for Great Northern.

WATCH INSPECTORS

A. F. Benson	Wash.
H. H. Trowbridge	Wash.
H. J. March	Wash.
Nelson Jewelry Co	Wash.
Davis Jewelers	Wash.

SPEED TABLE

Time Min.	Per Mile Miles Sec. Per Hour	Time Per Mile Miles Min. Sec. Per Hour
<u>Min.</u> 1	Sec. Per Hour 40 90.0 41 87.8 42 85.7 43 83.7 44 81.8 45 80.0 46 78.8 47 76.6 48 75.0 49 78.5 50 72.0 51 70.6 52 69.2 58 67.9 54 66.6 55 65.4 56 64.2 57 63.1 58 62.0 59 61.0 — 60.0	$\begin{tabular}{ c c c c c c } \hline Min. & Sec. Per Hour \\ \hline 1 & 12 & 50.0 \\ \hline 1 & 14 & 48.6 \\ \hline 1 & 16 & 47.4 \\ \hline 1 & 18 & 46.1 \\ \hline 1 & 20 & 45.0 \\ \hline 1 & 22 & 48.9 \\ \hline 1 & 24 & 42.9 \\ \hline 1 & 26 & 41.9 \\ \hline 1 & 28 & 40.9 \\ \hline 1 & 50 & 82.7 \\ \hline 1 & 55 & 81.8 \\ \hline 2 & & 80.0 \\ \hline 2 & 10 & 27.7 \\ \hline 2 & 20 & 25.7 \\ \hline 2 & 80 & 24.0 \\ \hline 2 & 40 & 22.5 \\ \hline 3 & & 20.0 \\ \hline \end{tabular}$
1 1 1 1	2 58.0 8 57.1 4 56.2	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$
1 1	2 58.0 8 57.1 4 56.2 5 55.8 6 54.5	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$
1 1 1 1	7 58.7 8 52.9 9 52.1 10 51.4	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$

BUSINESS TRACKS NOT SHOWN AS STATIONS ON TIME TABLE

				-		-	
Name	Location	Capaci- ty Cars	Switch Opens	Name	Location	Capaci- ty Cars	Switch Opens
Highland Rock Quarry Geiger Field. Fairchild Air Force Base Air Base, Washington Olson Spur. Sand Pit. Gravel Spur. Kackuk Matala	 1.0 mile west of Fort Wright 1.0 mile east of Highland 8.2 miles east of Fairchild At Fairchild-U. S. Depot Yard 2.2 miles east of Ephrata 1.5 miles west of Ephrata 1.23 miles west of Trinidad 1.3 miles west of Voltage Private Yard 1.1 miles west of Rock Island 6,610 feet long and yard 	Yard 22 30 70	West East West Both Both West East West	Matneys Spur Spokane-Portland Cement Co. Spur Talisman Mining Co Brinkman Spur Consolidated Mining and Smelting Co. Spur H. T. Jebbis Spur	 1.02 miles west of West Kettle Falls 2.72 miles west of West Kettle Falls 1.1 miles east of Boyds 2.5 miles east of Laurier 3.4 miles east of Grand Forks. 1.1 miles east of Grand Forks. 1.4 mile west of Grand Forks. 1.25 miles west of Torboy 	10	Both East Both East West East East
Larabee Industry Thornton Spur Tunk Creek Spur Constructors Track Ribbon Cliff Spur Entiat Rock Spur Springland Orchard Spur Olds Washing Plant Welch Spur (Friday Pack Co.)	 mile south of Cordell 5 mile north of Ellisforde 41 miles north of Tonasket 1.11 miles south of Barker 0.64 mile north of Chief Joseph. 5.1 miles north of Entiat 3.5 miles north of Entiat 1.4 miles south of Wagnersburg 2.02 miles north of Olds 1.6 miles north of Olds 	10 3 60 13	Both Both Both Both South South South North North	Subdivision No. 6 Estes Ringo Longwill. Seabury. Jefferson Mt. Hope Industrial Spur Old West Fairfield	 3.22 miles west of Moscow 3.79 miles west of Viola 1.39 miles west of Sokulk 2.39 miles west of Geary 3.49 miles west of Spring Valley 2.93 miles west of Waverly 	5 11 4 15	Both West East Both East Both Both Both
Baskins Spur Salmo Gravel Spur. Archibald Spur. Benton Spur Ross. Work Spur. Kootenai Industry. C. M. & S. Co. Industry. Stroh Spur. Hudson's Spur Kanes Spur. Harpers Spur.	 3.6 miles north of Ymir 1.9 miles south of Ymir 1.75 miles south of Salmo 1.0 miles south of Erie 2.0 miles south of Meadows 3.2 miles north of Columbia Gardens 0.4 mile south of Waneta 0.5 mile south of Waneta 5.33 miles north of Northport 3.3 miles south of Northport 4.1 miles south of Northport 4.5 miles south of Northport 	15 3 6 9 3 23 3 10 5 17	South North South South Both Both Both South South South North	Atlas Post Falls Liberty Lake. Carders Vera Industrial Spur. Includes True's Oil Spur. Opportunity. Apple Center West Apple Center Dishman.	1.5 miles west of Coeur d'Alene 2.6 miles west of Coeur d'Alene 8.46 miles west of Coeur d'Alene 8.46 miles west of Coeur d'Alene 2.14 miles east of Greenacres. 1.24 miles west of Flora 1.17 miles west of Flora	$ \begin{array}{c} 28 \\ 5 \\ 6 \\ 12 \\ 4 \\ 8 \\ 3 \\ 22 \\ 3 \\ 11 \\ \end{array} $	West Both East Both East West East East West East West East West
Hendrix Cut. Blue Creek. Alloy Industry.	 1.3 miles south of Marble, in- cluding trackage of Spokane- Portland Cement Co., Pri- vate Yard	251 3 19	South South Both North South North	Subdivision No. 8 Manning. Blackwell. Stoneham Balder	5.65 miles west of Colfax 1.92 miles east of Steptoe 2.95 miles west of Thornton 4.34 miles east of Rosalia 2.59 miles east of Spring Valley	6 14 4 12	West Both East Both East
WENATCHEE 648 APPLEYARD MALAGA ROCK ISLAND COLUMBIA RIVER 607 COLUMBIA RIVER 607	QUINCY 1305 WINCHESTER HAYLOR EPHRATA SOAP LAKE ADRIAN STRATFORD	WILSON CREEK 1281	MARLIN	DOWHS AMONA AMONLER MONLER	BLUESTEM 2333 BLUESTEM 2333 CANBY EDWALL EDWALL ESPANOLA FAIRCHILD 2454	Z FORT WRIGHT	BOKANE 1876
RULING GR. 170 160 150	ADE on EASTWARD 1.0% on WESTWARD 1.0% on WESTWARD 140 130 120 11	1	00 9	0 80 70 60	50 40 30 20	MiLi	<u>ES</u> 0

Pages 18, 19, 20 are blank.