

COMPANY SURGEONS

- *Dr. Abbott Skinner, Chief Medical Officer,
Office CA 4-7408—Home MI 8-2650,
1360 Lowry Medical Arts Bldg.St. Paul, Minn.
- *Dr. Charles T. Eginton, Asst. to Chief Medical Officer,
Office CA 4-7408—Home MI 9-5473,
1360 Lowry Medical Arts Bldg.St. Paul, Minn.
- *Dr. Hugo F. Schrockenstein,
Office CA 4-7408—Home CA 6-6906,
1360 Lowry Medical Arts Bldg.St. Paul, Minn.
- *Dr. Darrell E. Westover,
215 Lowry Medical Arts Bldg.St. Paul, Minn.
- *Dr. John F. Alden,
1151 Lowry Medical Arts Bldg.St. Paul, Minn.
- Dr. D. A. Burlingame, Roentgenologist,
Lowry Medical Arts Bldg.St. Paul, Minn.
- *Dr. Ernest R. Anderson,
Office FE 2-7508—Home TA 4-2871,
1849 Medical Arts Bldg.Minneapolis, Minn.

*Designates also Examining Surgeon.

OPHTHALMIC SURGEONS
(Eye Doctors)

- Dr. Edward P. Burch,
852 Lowry Medical Arts Bldg.St. Paul, Minn.
- Dr. Donald C. Sterner,
852 Lowry Medical Arts Bldg.St. Paul, Minn.
- Dr. Malcolm A. McCannel,
325 Doctors Bldg.Minneapolis, Minn.
- Dr. Richard C. Horns,
1137 Medical Arts Bldg.Minneapolis, Minn.

WATCH INSPECTORS

- Christensen, Herbert B., Inc.
144 East Fifth Street
Saint Paul, Minnesota
- C. J. & H. W. Anderson
1466 University Avenue
Saint Paul, Minnesota
- A. T. Veilleux
894 Rice Street
Saint Paul, Minnesota
- O. H. Arosin Co.
414 Robert Street
Saint Paul, Minnesota
- Pomerleau and Son
227 East Hennepin Avenue
Minneapolis, Minnesota
- Gustafson, Oscar P. Co.
410 Nicollet Avenue
Minneapolis, Minnesota
- Kavchar Jewelry
2218 Central Ave. N. E.
Minneapolis, Minnesota
- R. R. & J. F. Berens
20 East Lake Street
Minneapolis, Minnesota

D. W. HARTUNG,
Chief Dispatcher.

A. R. McKEEN,
Trainmaster.

J. H. BOYD,
Trainmaster.

F. L. HENRY,
Trainmaster.

J. G. TOOMEY,
Asst. Superintendent.

GREAT NORTHERN RAILWAY COMPANY

TWIN CITY TERMINALS

WILLMAR DIVISION

TIME TABLE 336

Effective 12:01 A. M. Central Time.

Sunday, April 24, 1960

E. S. PINKERTON, Gen. Supervisor Terminals.

H. J. SURLES, Superintendent.

R. N. WHITMAN, General Manager.

A. W. CAMPBELL,
General Superintendent Transportation.

Printed in U.S.A.

2 WESTWARD.

FIRST SUBDIVISION—ST. PAUL TO LYNDALE JCT.

FIRST SUBDIVISION—ST. PAUL TO LYNDALE JCT.

WEST

Time Table No. 336		FIRST CLASS																FIRST CLASS															
Effective April 24, 1960																																	
STATIONS																																	
AUTOMATIC SIGNALS	SAINT PAUL	871	781	923	55	3	873	27	925	783	57	11	849	875					9	879	7	31	929										
		N. Pas. No. 53	C. & G. W. No. 14	C. & G. W. No. 27	G. N. No. 24	G. N.	N. Pas. No. 1	G. N.	C. & G. W. No. 21	C. & G. W. No. 6	G. N. No. 20	G. N.	C. & G. W. No. 401	N. Pas. No. 23					G. N.	N. Pas. No. 3	G. N.	G. N.	C. & G. W. No. 23										
		Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily					Daily	Daily	Daily	Daily	Daily										
		L 5.55pm	L 7.10pm	L 7.35pm	L 8.00pm	L 8.30pm	L 8.40pm	L 9.30pm	L 2.35pm	L 4.25pm	L 4.30pm	L 5.30pm	L 6.15pm	L 7.15pm					L 8.15pm	L 8.50pm	L 8.55pm	L 9.10pm	L 10.40pm										
		1.39	5.58	7.13	7.38	8.03	8.33	8.43	9.33	2.38	4.28	4.33	5.33	6.18	7.18				8.18	8.53	8.58	9.13	10.43										
	MINNEAPOLIS	10.57	A 6.25pm	A 7.35pm	A 8.00pm	A 8.22pm	A 8.52pm	9.05 9.15	9.55 10.03	A 2.55pm	A 4.50pm	A 4.52pm	A 5.50pm	A 6.40pm	7.40 7.45				8.35 9.05	9.15 9.35	9.17 9.30	9.35 9.40	11.00pm										
	FIRST STREET	10.82					A 9.17pm							A 7.46pm					A 9.37pm														
	LYNDALE JCT.	12.17					A 10.07pm											A 9.09pm		A 9.33pm	A 9.43pm												

EASTWARD.

FIRST SUBDIVISION—LYNDALE JCT. TO ST. PAUL

FIRST SUBDIVISION—LYNDALE JCT. TO ST. PAUL

EA

Time Table No. 336		FIRST CLASS																FIRST CLASS															
Effective April 24, 1960		870	10	32	874	8	924	838	58	12	928	58	788	28				784	876	4	878	930											
STATIONS		N. Pas. No. 23	G. N.	G. N.	N. Pas. No. 4	G. N.	C. & N. W. No. 22	C. & N. W. No. 100	G. N. No. 23	G. N.	C. & N. W. No. 24	G. N. No. 19	C. & N. W. No. 13	G. N.				C. & N. W. No. 3	N. Pas. No. 2	G. N.	N. Pas. No. 48	C. & N. W. No. 48											
STATIONS		Daily	Daily Ex. Sat.	Daily	Daily Ex. Sat.	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily				Daily Ex. Sat.	Daily	Daily	Daily	Daily											
AUTOMATIC SIGNALS	SAINT PAUL.....	12.17	A 6.40am	A 6.45am	A 7.00am	A 7.15am	A 7.30am	A 8.22am	A 11.20am	A 1.45pm	A 2.00pm	A 3.55pm	A 7.45pm	A 8.35pm	A 9.55pm				A 10.25pm	A 10.35pm	A 10.40pm	A 10.50pm	A 10.50pm										
	WESTMINSTER ST. TOWER.....	10.78	6.27	6.32	6.42	7.02	7.17	8.12	11.13	11.32	1.52	3.42	7.32	8.22	9.42				10.12	10.22	10.27	10.32	10.42										
	MINNEAPOLIS.....	1.40	6.15	6.20	6.30	6.50	7.05	8.00am	L 11.01am	L 11.20am	L 1.40pm	L 3.30pm	L 7.20pm	L 8.10pm	9.30 9.20				L 10.00pm	10.10 10.02	L 10.15pm	L 10.20pm	L 10.30pm										
	FIRST STREET.....	1.38	L 6.08am			L 6.38am														L 10.01pm													
	LYNDALE JCT.....			L 5.59pm	L 6.18pm		L 6.55pm							L 9.15pm																			

WESTWARD TRAINS ARE SUPERIOR TO EASTWARD TRAINS OF THE SAME CLASS.

WESTWARD.

SECOND SUBDIVISION
MINNEAPOLIS AND NORTHTOWN

EASTWARD.

FIRST CLASS				FIRST CLASS			
11	57	3	55	56	12	58	4
G. N.	G. N. No. 20	G. N.	G. N. No. 24	G. N. No. 23	G. N.	G. N. No. 19	G. N.
Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily
L 5.55pm	L 5.00pm	L 9.00pm	L 8.27pm	A 11.15pm	A 1.35pm	A 7.15pm	A 10.05pm
5.56	5.01	9.01	8.28	11.14	1.34	7.14	10.03
5.58	5.03	9.03	8.30	11.12	1.32	7.12	10.01
A 6.04pm	A 5.09pm	A 9.09pm	A 8.36pm	L 11.06pm	L 1.26pm	L 7.06pm	L 9.55pm

WESTWARD TRAINS ARE SUPERIOR TO EASTWARD TRAINS OF THE SAME CLASS.

MAXIMUM PERMISSIBLE SPEED.

Between	Passenger	Freight
St. Paul and Minneapolis.....	55 M.P.H.	30 M.P.H.
First St. North, Minneapolis, and Lyndale Junction.....	30 M.P.H.	30 M.P.H.
Northtown and Van Buren St. N. E.....	45 M.P.H.	30 M.P.H.
Van Buren St. N. E. and Harrison St. N. E.....	30 M.P.H.	30 M.P.H.
Minneapolis Jct. and First St. North, Minneapolis.....	30 M.P.H.	30 M.P.H.

SPEED RESTRICTIONS.

ST. PAUL UNION DEPOT PROPERTY.

Trains or Engines heading in or out	Passenger	Freight
Back up movement.....	10 M.P.H.	10 M.P.H.
	8 M.P.H.	8 M.P.H.

SPEED RESTRICTIONS—Continued.

Between	Passenger	Freight
Trains and engines on track between east end of freight tracks, St. Paul and connection with Depot tracks, commonly known as Thumb-Up.....	5 M.P.H.	30 M.P.H.
Eastward train and engine movements, on eastward passenger track, with or without cars, between Jackson St. overhead bridge and Third Street, St. Paul.....	30 M.P.H.	30 M.P.H.
East End Stone Arch Bridge and Minneapolis.....	30 M.P.H.	30 M.P.H.
Minneapolis Passenger Station, all tracks between MHI Pond Bridge, First St. North, C. & N. W. Ry. crossing, and CB&Q RR. crossing.....	Restricted Speed	R
Minneapolis Passenger Station wye track.....	8 M.P.H.	8 M.P.H.
For movements between Home Signals of Interlocking at Mulberry Street:		
With the current of traffic on Main Tracks.....	30 M.P.H.	30 M.P.H.
Against the current of traffic on main tracks and on other than main tracks.....	15 M.P.H.	15 M.P.H.
Unless conditions require a further speed restriction, trains or engines moving against current of traffic on double track through interlockings, or making diverging movements through switches and crossovers.....	15 M.P.H.	15 M.P.H.

SPECIAL INSTRUCTIONS FIRST AND SECOND SUBDIVISIONS ON
PAGES THREE AND FOUR.

ARD. FIRST SUBDIVISION—ST. PAUL TO LYNDALE JCT.

FIRST SUBDIVISION—ST. PAUL TO LYNDALE JCT.

WESTWARD. 2

FIRST CLASS														FIRST CLASS																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
871	781	923	55	3	873	27	925	783	57	11	849	875						9	879	7	31	929																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										

D. FIRST SUBDIVISION—LYNDALE JCT. TO ST. PAUL

FIRST SUBDIVISION—LYNDALE JCT. TO ST. PAUL

EASTWARD.

able 36		FIRST CLASS														FIRST CLASS																		
		870	10	32	874	8	924	838	56	12	928	58	788	28					784	876	4	878	930											
24, 1960	ON S	M. Pas. No. 25	G. N.	G. N.	M. Pas. No. 4	G. N.	C. S. & Q. No. 27	C. S. & W. No. 400	G. N. No. 23	G. N.	C. S. & Q. No. 24	G. N. No. 19	C. S. & W. No. 13	G. N.	C. S. & W. No. 8	M. Pas. No. 2	G. N.	M. Pas. No. 64	C. S. & Q. No. 48															
																				Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily
AUL	ST. TOWER	12.17	A 6.40am	A 6.45am	A 7.00am	A 7.15am	A 7.30am	A 8.22am	A 11.20am	A 11.45am	A 2.00pm	A 3.55pm	A 7.45pm	A 8.35pm	A 9.55pm	A 10.25pm	A 10.35pm	A 10.40pm	A 10.50pm	A 10.50pm														
																					10.79	6.27	6.32	6.42	7.02	7.17	8.12	11.13	11.32	1.52	3.42	7.32	8.22	9.42
OLIS	REXT	1.40	L 6.15	L 6.20	L 6.30	L 6.50	L 7.05	L 8.00am	L 11.01am	L 11.20am	L 1.40pm	L 3.30pm	L 7.20pm	L 8.10pm	9.30	L 10.00pm	10.10	L 10.15pm	L 10.20pm	L 10.30pm														
																					6.10	6.05	6.25	7.00	L 8.00am	L 11.01am	L 11.20am	L 1.40pm	L 3.30pm	L 7.20pm	L 8.10pm	9.20	10.00pm	10.10
JOT		1.38	L 6.08am			L 6.38am																												
																																	L 5.59pm	L 6.18pm

WESTWARD TRAINS ARE SUPERIOR TO EASTWARD TRAINS OF THE SAME CLASS.

D. SECOND SUBDIVISION
MINNEAPOLIS AND NORTHTOWN EASTWARD.

CLASS		FIRST CLASS			
3	55	56	12	58	4
G. N.	G. N. No. 24	G. N. No. 23	G. N.	G. N. No. 19	G. N.
Daily	Daily	Daily	Daily	Daily	Daily
L 9.00am	L 8.27am	A 11.15am	A 1.35pm	A 7.15pm	A 10.05pm
9.01	8.28	11.14	1.34	7.14	10.03
9.03	8.30	11.12	1.32	7.12	10.01
A 9.09am	A 8.36am	A 11.06am	L 1.26pm	L 7.06pm	L 9.55pm

STWARD TRAINS ARE SUPERIOR TO EASTWARD TRAINS OF THE SAME CLASS.

MAXIMUM PERMISSIBLE SPEED.

Between	Passenger	Freight
St. Paul and Minneapolis	55 M.P.H.	30 M.P.H.
First St. North, Minneapolis, and Lyndale Junction	30 M.P.H.	30 M.P.H.
Norhtown and Van Buren St. N. E.	45 M.P.H.	30 M.P.H.
Van Buren St. N. E. and Harrison St. N. E.	30 M.P.H.	30 M.P.H.
Minneapolis Jct. and First St. North, Minneapolis	30 M.P.H.	30 M.P.H.

SPEED RESTRICTIONS.

ST. PAUL UNION DEPOT PROPERTY.

Between	Passenger	Freight
Trains or Engines heading in or out	10 M.P.H.	10 M.P.H.
Back up movement	5 M.P.H.	5 M.P.H.

SPEED RESTRICTIONS—Continued.

Between	Passenger	Freight
Trains and engines on track between east end of freight tracks, St. Paul and connection with Depot tracks, commonly known as Thomas-Up	5 M.P.H.	5 M.P.H.
Eastward train and engine movements, on eastward passenger track, with or without cars, between Jackson St. overhead bridge and Third Street, St. Paul	30 M.P.H.	30 M.P.H.
East End Stone Arch Bridge and Minneapolis	30 M.P.H.	30 M.P.H.
Minneapolis Passenger Station, all tracks between MBI Fund Bridge, First St. North, C. & N. W. Ry. crossing, and C&N RR. crossing	Restricted Speed	Restricted Speed
Minneapolis Passenger Station wye track	8 M.P.H.	8 M.P.H.
For movements between Home Signals of Interlocking at Mulberry Street:		
With the current of traffic on Main Tracks	30 M.P.H.	15 M.P.H.
Against the current of traffic on main tracks and on other than main tracks	15 M.P.H.	15 M.P.H.
Unless conditions require a further speed restriction, trains or engines moving against current of traffic on double track through interlockings, or making diverging movements through switches and crossings	15 M.P.H.	15 M.P.H.

SPECIAL INSTRUCTIONS FIRST AND SECOND SUBDIVISIONS ON
PAGES THREE AND FOUR.

SPECIAL INSTRUCTIONS.

1. PASSENGER TRACKS:

Two right hand main tracks between Third Street, St. Paul, and St. Anthony Park.
Two left hand main tracks between St. Anthony Park and West end of Mill Pond Bridge.

FREIGHT TRACKS:

Two left hand main tracks between Third Street, St. Paul, and St. Anthony Park.
Two right hand main tracks between St. Anthony Park and Union Yard puzzles.

PASSENGER AND FREIGHT TRACKS:

Both main tracks between First Street North, Minneapolis, and Northtown, via Minneapolis Junction.

Five main tracks designated below between First Street North, Minneapolis, and Lyndale Junction:

- No. 1, Switching lead—north track.
- No. 2, Westward track for G. N. passenger and freight trains.
- No. 3, Eastward track for G. N. passenger and freight trains.
- No. 4, Westward track for freight trains and M. & St. L. Ry. passenger trains.
- No. 5, Eastward track for freight trains and M. & St. L. Ry. passenger trains.

Trains using freight tracks Nos. 4 and 5 shall stop before passing over the Holden Street crossing and will not proceed until proper signal is received from switchtender.

ROUTING OF TRAINS AND ENGINES.

2. Switchtenders will route trains and engines at Minneapolis Passenger Station, First Street North, Second Street North, Holden Street, Lyndale Junction, Union Yard puzzles, West End Union "R" Yard, Minneapolis Junction East Wye, West Wye, Van Buren Street, and Northtown. Trains and engines will not proceed until proper signal is received from switchtenders to pass through or over switchtenders' territory.

TRAIN REGISTER AND CLEARANCE EXCEPTIONS.

8. Northtown—Lyndale Junction—Trains originating at these points will not require clearance when train order signal indicates proceed.

Minneapolis Passenger Station—All trains register and receive clearance.

C. & N. W. Ry. westward passenger trains arriving at Westminster Street Tower via East St. Paul may proceed to Third Street, St. Paul, over eastward passenger track without Great Northern clearance.

REGISTER STATIONS

St. Paul Passenger trains.
Westminster St. Tower Freight trains.
Minneapolis Jct. Freight trains.
Minneapolis Passenger Station Passenger trains.
Northtown All trains, passenger trains
may register by ticket.

MINNEAPOLIS PASSENGER STATION.

4. Minneapolis—All trackage within switchtenders' limits from west end of Mill Pond Bridge east of depot extending through to eastward main track west of depot, and between First Street North and east leg of wye, will be considered depot station tracks of the Minneapolis Passenger Station, and while within these limits it will not be necessary to observe Rule 99 and last paragraph of Rule 854 of the Consolidated Code of Operating Rules and General Instructions.

There is no superiority of trains on depot station tracks. All trains and engines, with or without cars, entering and leaving depot station tracks will move only on hand signal from switchtenders and must approach and proceed within these limits at

restricted speed expecting to find track occupied and be prepared to stop. A proceed signal from switchtender is no assurance that track ahead is clear.

Before starting westward train from Minneapolis Passenger Station, engineers will know way is clear at crossing beyond stop board before proceeding over the crossing, and the stop made by train in the west end of passenger station will be regarded as a stop for stop board at the west end of station.

5. Train, engines or cars must not be moved over Railroad Crossing of the C. & N. W. Ry. or the C. B. & Q. R. R. west of Minneapolis Passenger Station without flagman or member of crew in charge of movement first stationing themselves at crossing to prevent opposing movements. This rule not to apply to movements on freight tracks, which are covered by other rules.

MISCELLANEOUS

6. Between St. Paul and Minneapolis Passenger Station, employees will not permit any part of their person to project beyond the sides of moving engines or cars.
On trains, engines or cars having windshields, windows, doors or ventilators that open outward same should be kept closed between St. Paul and Minneapolis.
7. On passenger tracks between St. Paul and Minneapolis Passenger Station, lighted fuseses must not be used, except in cases of emergency, and then only when held in hand and must be extinguished before leaving. The use of torpedoes is prohibited.
8. On westward passenger track, engineers on moving engines will keep engine bell ringing passing Great Northern Union Yard puzzle switches, located just west of St. Anthony Elevator, to 15th Avenue Tower.
9. Passenger extra trains may run ahead of first class trains between St. Paul and Minneapolis; between Minneapolis and Lyndale Jct.; and between Minneapolis and Northtown.
10. Great Northern trains using the CB&Q interlocker at St. Paul Depot to back in, will not start their back-up movement until the rear brakeman is in the rear end of the rear car with the conductor to assist the conductor in observing the position of switches and signal indications.

MINNEAPOLIS.

11. Eastward freight trains at Lyndale Junction, and westward freight trains at First Street North, may run ahead of first class trains between those points after receiving proceed signal from switchtender.
12. Lyndale Junction—Eastward freight trains on Willmar line, having cars to set out at this point, will stop before passing eastward Home Signal to make set-out.
13. Minneapolis Junction—Trains must stop before passing over the crossing of the N. P. Ry. Industry Track 460 feet East of Junction yard office, unless proceed signal is received from switchtender.
14. The Laws of the Cities of St. Paul and Minneapolis prohibit the unnecessary use of the engine whistle within those limits.
15. Operation of Spring Switches. Spring switches of two different types are in use on this division.

Without facing point lock:

- (a) East leg of wye at Mississippi Street to track leading to 8th Street, St. Paul. Normal position is for west leg of wye.
- (b) Four spring switches located at east end Minneapolis Junction Roundhouse.
(1) leading off Roundhouse lead to westward main line towards First St. North. Normal position is for main track.

- (2) leading off Roundhouse lead to Main Line 4, opposite turn table. Normal position is for main track.
- (3) leading off Roundhouse lead to Main Line 4, opposite yard office. Normal position is for main track.
- (4) East end Roundhouse lead opposite yard office. Normal position is for east lead #2.

With facing point lock:

- (a) East end of eastward freight track near Fourth Street, St. Paul. Normal position is for westward freight track.

- 16. The normal position of a spring switch with facing point lock is identified by a color light type signal displaying a lunar white light for train or engine movements in a trailing point direction and for movements in facing point direction when conditions require.
- 17. The normal position of a spring switch without facing point lock is identified by a triangular yellow target on switch stand with letter "S" in black, and "lunar white" light in switch lamp in place of green light displayed in both directions through or over the switch.
- 18. Facing point locks on hand operated switches are indicated by a six inch yellow stripe painted on target staff. Be positive locking device is restored to normal position after using. A running switch must not be made through this type switch.
- 19. Loaded dump cars should not be handled on double track after dark, but if necessary to do so, close watch must be kept by trainmen and if a car dumps its load, train must be stopped and protection afforded on the opposite track.
- 20. Due to limited overhead clearance at tunnels and structures, employees are warned to keep off top of cars of extreme height and width when handled in trains and yards, except in emergency. In absence of previous advice on such cars, wire proper officer for instructions.
- 21. When any passenger car or cars are left on any track, the hand brakes must be adequately applied on each car. The brakes on one passenger car are not to be depended upon to hold other cars when coupled together.

YARD LIMITS**ST. PAUL-MINNEAPOLIS.**

- 22. St. Paul to yard limit board west of the west Fridley yard switch; Minneapolis Jct. to yard limit board 2640 feet west of the new spur head block about 8 miles west of Hopkins Jct., including Hopkins Branch; and 5686 feet west of Junction Switch (Osseo Line).

Automatic Interlocking

- 23. Minneapolis Mulberry Street with N. P. Ry. If a train is stopped at a home signal and no immediate conflicting train movement is evident, trainman may signal train to proceed over crossing, after making certain that conflicting home signals indicate Stop.
- 24. To insure safe movement on descending grade, trains and engines using Eastward freight track at Westminster Street Interlocking must stop at Eastward Home Signal located about 200 feet West of Tower. This signal governs movement over safety derail and will not be changed to indicate Proceed until stop is made.

Manual Interlocking

- 25. St. Anthony Park St. Paul

Manual Interlocking with Dual Control Switches

- 26. Westminster Street St. Paul
- 15th Avenue S.E. Minneapolis
- Boom Island Minneapolis

Westminster Street—Between the home signal limits of Westminster Street Interlocking, train or engine movements may be made in either direction, ON EITHER PASSENGER TRACK, by signal indication.

For movements on the Passenger or Freight Tracks, the home signal limits, Rule 605, of Westminster Street Interlocking, include all trackage between the eastward home signal located approximately 850 feet west of Mississippi Street overhead bridge and the westward home signal located approximately 900 feet west of Third Street overhead bridge.

Telephones for communication are located at the home signals, in bungalows, and in Northern Pacific switchtender's shanty near Third Street.

15th Avenue S. E. is controlled from St. Anthony Park Interlocking. Telephones for communication are located in booths near the east and west interlocking limits.

Semi-Automatic Interlockings

- 27. St. Paul Fair Grounds Spur with N. P. Ry.
- Hopkins M. & St. L. Ry. Crossing.

St. Paul, Great Northern train movements over the crossing will be governed by manually operated gates together with standard interlocking dwarf signal indications. Great Northern routes over the crossing will be set manually after obtaining release of electric lock holding gates in "Stop" position. See instructions posted in box locked with a switch lock.

Hopkins, Great Northern train and engine movements over the crossing will be governed by "Stop" signs located each side of crossing, and by manually operated crossing gates, with red lights, normally set and electrically locked across G. N. track. See instructions posted in box locked with a switch lock.

ST. PAUL UNION DEPOT & MINNESOTA TRANSFER

- 28. "The Consolidated Code of Operating Rules, Edition of 1959, in addition to the following instructions will govern employees while operating on Minnesota Transfer Railway Co. and St. Paul Union Depot Company trackage:—
 - (a) All trackage of the Minnesota Transfer Railway Company is defined as a system of tracks within yard limits over which movements must be made at restricted speed and are not authorized by timetable, or train order, but subject to prescribed signals and rules or special instructions. The limits of the Saint Paul Union Depot Company property extend from connection with the Northern Pacific Ry. and Great Northern Ry. tracks at Third Street and connection with the CMStP&P-CB&Q R.R. tracks opposite depot roundhouse, on the east, to connection with the CGW Ry. and CMStP&P R.R. tracks at Robert Street on the west.
 - (b) The timetable of the Saint Paul Union Depot Company is for information only. Employees of railroads using the tracks of this Company will be governed by current timetable of their respective Companies only as to arriving and departing time of trains.
 - (c) Where in the rules of the Consolidated Code reference is made to trains, such rules will also apply to yard movements and engines.
 - (d) Under Rule 11, the use of torpedoes is prohibited.
 - (e) Under Rule 15, burning fusees must not be used except in case of emergency and then only when held in hand and must be extinguished before leaving.

SPECIAL INSTRUCTIONS—Concluded

- (f) There is no superiority of trains within the limits of Saint Paul Union Depot Company property.
- (g) Within the limits of the Saint Paul Union Depot Company property trains and engines must move at restricted speed and must not exceed ten (10) miles per hour through crossovers, turnouts and puzzle switches. The entrance to and all movements on this property will be made only on authority of hand signals from switch tenders. No train or engine may foul any track or puzzle switch without authority of hand signals from switch tenders in control of such movements, except that short interior switching movements may be made through crossovers connecting shed tracks when authorized by train director.
- (h) Any lead or track may be used for the make-up of trains on authority of train director. The movement of trains should be given preference.
- (i) When indicated by the ringing of the bell, flashing of headlight, hand or light signal that a train or engine is ready to move, the switch tender in charge of the shed track on which the movement is standing will handle as follows: at west end of station the switch tender will control the movement by hand or light signal; at the east end of station the switch tender will inform the train director, who will route the movement by instructions over the public address system. Switch tenders will be governed by these instructions, relaying such instructions by hand or light signal to the next switch tender in the direction of the movement, each must receive an acknowledgement before signalling the movement. Signals must not be acknowledged or acted upon unless the signal corresponds with instructions from the train director and is definitely understood.
- (j) When backing, the back-up air brake valve on passenger trains must be operated by the conductor, except in the movement of empty equipment, it may be operated by a competent trainman or yardman. When practicable, conductors must see that trainmen are stationed so hand or light signals may be used, in case of any emergency. When backing a train, the engine brake valve must be in running position; an application of the brakes must be made with back-up brake valve before starting and it must be known that the brakes are in operative condition. Movement must not be started until the proper signal is given. A running test must be made with the back-up air brake valve before the train has moved 300 feet; if the running test is not made within 300 feet the engineer must stop the train and ascertain cause. The speed of train must not exceed eight (8) miles per hour and train must be under such control that it can be stopped short of train, or obstruction, and short of bumping post on stub tracks.
- (k) Headlights must be dimmed while on shed tracks.