COMPANY SUR						
*Dr. Abbott Skinner, Chief Medical *Dr. Hugo F. Schroeckenstein, Asst.	to Chief Medical Officer					
1	St. Paul. Minn					
*Dr. Robert S. Flom	St. Paul Minn					
Dr. James N. Berbos	Aberdeen, S.D.					
*Dr. Carson B. Murdy Dr. William C. Kaufman *Dr. R. P. Griffin	Appleton Minn					
*Dr. R. P. Griffin	Benson, Minn.					
Dr. Robert H. Nelson	Benson, Minn.					
*Dr. Louis T. O'Brien	Breckenridge, Minn.					
Dr. C. W. Jacobson Dr. Theodore Greenfield	Breckenridge, Minn.					
Dr. Theodore Greenfield	Cokato, Minn.					
Dr. Joseph C. Houts	Dassel, Minn.					
Dr. I. L. Oliver	Granite Falls, Minn.					
*Dr. W. H. Saxton	Huron, S. D.					
Dr. Kenneth H. Peterson						
Dr. V. S. Irvine *Dr. B. C. Ford Dr. Phillip C. Hedenstrom Dr. J. E. Eckdale	Marshall, Minn.					
Dr. Phillip C. Hedenstrom	Marshall, Minn.					
Dr. J. E. Eckdale *Dr. Ernest R. Anderson	Marshall, Minn.					
l Dr. William E. Hart	Monticelle Minn					
*Dr. R. A. Rossberg *Dr. Jack Guy	Morris, Minn.					
*Dr. Jack Guy Dr. T. J. Bloedel	New London, Minn.					
Dr. C. R. Myre	Paynesville Minn					
Dr. C. R. Myre Dr. H. W. Goehrs	St. Cloud, Minn.					
Dr. Vernon E. Neils *Dr. John F. Alden	St Paul Minn					
*Dr. Darrel E. Westover *Dr. A. L. McGilvra	St. Paul, Minn.					
*Dr. A. L. McGilvra	Sioux Center, Iowa					
*Dr. H. E. Rudersdorf *Dr. John W. Drahoe	Sloux City, lowa					
'Dr. G. Robert Bartron	Watertenn Q II					
Dr. Lloyd C. Gilman Dr. Walter E. Hinz	Willmar, Minn.					
*Dr. Waiter E. Hinz	Willmar, Minn.					
*Dr. A. M. McCarthy. *Dr. R. P. Michels	Willmar, Minn.					
Dr. Chester B. McVay	Yankton, S. D.					
*Designates also Examining Surgeo	on.					
OPHTHALMIC SU						
(Eye Doctor	•					
Dr. Malcoim A. McCannel	Minneapolis, Minn.					
Dr. Richard C. Horns Dr. Edward P. Burch Dr. Donald C. Sterner	Minneapolis, Minn.					
Dr. Donald C. Sterner	St. Paul. Minn.					
ur.w.jwenner	St Cland Minn					
Dr. James E. Reeder Dr. Sidney F. Becker	Sioux City, Iowa					
Dr. Stanley S. Chunn	Willmar, Minn					
	•					
ROENTGENOLO (X-Ray only						
Dr. David A. Burlingame						
Dr. Roll M. Iverson	Minnespolis Minn					
Dr. Malcolm B. Hanson	Minneapolis, Minn.					
P. B. RASMUSSEN, Amst	. Superintendent.					
J. G. TOOMEY, Asst. Su	perintendent.					
D. W. HARTUNG, Chief Dispatcher.						
A. T. WALKER, Master Mechanic						
T. C. WHITACRE, Trainmaster.						
M. M. DONAHUE, Trainmaster.						
F. L. HENRY, Trainmaster.						
A. D. POWERS, Trainmaster. J. H. BOYD, Trainmaster.						
R. D. NELSON, Trainmaster.						
A. Q. FORD, Traveling Engineer						
H. M. LARY, Traveling	mgmeer Engineer					
J. B. MURRAY, Traveling						
i						

GREAT NORTHERN RAILWAY COMPANY

WILLMAR DIVISION TIME TABLE

EFFECTIVE 12:01 A. M.

113

CENTRAL STANDARD TIME

Sunday, May 26, 1963

E. F. OVIATT, Superintendent

R. N. WHITMAN, General Manager.

H. J. SURLES,

General Superintendent Transportation.

Printed in U.S.A.

2	WE	STW	ARD					FIRST SUBDIVISIO	N]	EASTW	ARD
190	Cap	Car acity	SECON	D CLASS	FIRST	CLASS		Time Table				FI	## Transfer CLASS 14		SECON CLAS
Station Numbers	_	_	5	329	31	27	and thom	No. 113 Effective May 26, 1963 STATIONS		Distance from Breckenridge	SIGNS	32	14		(825) 330
tatio	Sidings	Other Tracks	TOFC Daily	Daily	· · · ·		Distance St. Paul	May 26, 1963	15	leten					
00	00	OH	Ex. Sat.	Ex. Sun.	Daily	Daily	A&	STATIONS	F	DA	<u> </u>	Daily	Daily	İ	Daily Ex. Sun
0					L 9.50թո			ST. PAUL	. ע	214.85	к	A 6.45Am	A 9.50pm		
11	 .		• • • • • • • •		10.20pm	9.05An	10.57	MINNEAPOLIS	s	204.28	к	6.20Am	9.25 ₽ п		
	T	RAINS	BETW	EEN ST.	PAUL A	ND LYN	IDALE	JCT. ARE GOVERNED I	BY 7	WIN	CITY TE	RMINAL	TIME	TABLE.	
								일본 (1.60) m							
A 24	Yard 200	58	L 9.00₽m 9.15		ւ 10.24 թ ո 10.38	4	12.17	1.60 LYNDALE JCT*.		202.68	DNJPX	II.			
A 27	200	19	9.15		10.58	9.23	23.90 27.00	주는 (WAŸZĀTA) 3.10 LONG LAKE	WA	190.95	DPJ	5.50	8.49	[ļ
A 32		15				• • • • • • • • • • • • • • • • • • • •	31.37	4.37	ON	187.85	DP		· · · · · · · · · · · · · · · · · · ·		
				•••••			31.87	6.99	MA	183.48	DP				
A 39	188	54			. 	9.39	38.36	DELANO	DA	176.49	DP				
48	· · · · · ·	26		-			47.88	WAVERLY	WY	167.02	DP				.
53	307	59	· • • • • • • • • •	•••••			52.84	HOWARD LAKE	RD	162.01	DP				
A 59	148	155	· • · · • • · · · ·		· • • • • • • • • • •	9.57	59.15	COKATO 5.79	CT	155.70	DP				
65	168	165	· · · · · · · · · · · · · · · · · · ·				64.94	DASSEL	DS	149.91	DP		• • • • • • • • • • • • • • • • • • • •		
70		66	· • • · · • • • • • •				70.04	5.10 DARWIN	DN	144.81	DP				
76	171	262				s 10.15	76.18	6.14 LITCHFIELD	FD	188.67	DNP		750	• • • • • • • • • • • •	
84		58					83.86	7.68 GROVE CITY	G	130.99	DP	•••••	s /.DU	•••••	• • • • • • • •
89	190	50					88.99	5.13 ATWATER	WR	125.86	DP		• • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • • •
L 97		88	 .		 .		96.35	KANDIYOHI	KD	118.50	DP		• • • • • • • • • •		• • • • • • • •
					A 2.0 Am	A 10.45			 			4.12			
1102	Yard	1661	A 10.45Pm		L 12.03	L 10.50	102.19		w	112.66	ORDNK PTBXWZJ				
1109	· · · · · · ·	56		 .			108.79	PENNOCK	ĸ	106.06	DP				
1116	173	47					116.23	7.44 KERKHOVEN	кн	98.62	DP				
121		32					120.71	MURDOCK	СК	94.14	DP				
125		52					125.27	4.56 DE GRAFF	DG	00.70	DD.				
133	856	412				s 11.22	132.78	7.51 BENSON★	BN	89.58 82.07	DP JYDNPK		4.75	••••••	
138	139	38					138,45	5.67 CLONTARF	ŀ	76.40	P		s 0.35	• • • • • • • • • • • •	
149		125					148.67	10.22 HANCOCK	NC	66.18	DP		• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • •	· · · · · · · ·
157	400	300			1.02	s 11.48	157.52		MR	57.83	DNYTP	2 10		•••••	• • • • • • •
								8.22	10116	07.00	DNIIF	3.10	s 0.05	•••••	
166	145	41			• • • • • • • • • •	•••••	165.74	DONNELLY	DY	49.11	DP				
.176 .181	135 143	51 30	· · · · · · · · · · · · · · · ·	• • • • • • • • • • •	• • • • • • • • • •		176.20	HERMAN	HR	38.65	DP		•••••	• • • • • • • • • • • • • • • • • • • •	
193	150		• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	12.10 _{Pm}		11.50	RC	83.76	DP		• • • • • • • • • • • •		
140		64	• • • • • • • • • • • • • • • • • • • •	T 0 455	••••••	; · · · · · · · · · · ·	192.59	TINTAH	QN	22.26	DP	·····	• • • • • • • • • • • • • • • • • • • •		
				L 8.45pm			195.39		• • • • •	19.46	PJ				A 8.35
200	264	108		s 8.55			199.81	CAMPBELL	СВ	15.04	DP	[s 8.25
207	••••••	21	. 	s 9.05	.:		206.97	7.16 DORAN	OD	7.88	DP				8.10
214	Yard	1143		A 9.20Pm	A 2.01Am	A 1.00₽m	214.85	BRECKENRIDGE. *.	BR		RDNWB PYOKXZ	L 2.04Am	ւ 5.02թտ		L 8.00
			1.45 51.44	.25 38.26	3.37 56.04	3.51 52.64		Time Over Subdivision Average Speed Per Hour				4.01 50.46	4.08 49.03		.35 38.86

Westward trains are superior to eastward trains of the same class.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 7 THROUGH 12.

W	WESTWARD SECOND SUBDIVISION EASTWARD 3																			
Derra	Ca Capa	r city	SEC	DND	CLASS	FIF	RST CLA	\ss		Т	ime I			11.8		• •	Fil	RST CL	ASS	SECOND CLASS
Num			43	7	405	7	11	3	se fron	No. 113				pb Calls	oe from	SIGNS	8	28	4	406
Station Numbers	Sidings	Other Tracks	Dai	ly	Daily	Daily	Daily	Daily	Distance from St. Paul		May 26, STATIO		-	Telegraph	Distance Willmar		Daily	Daily	Daily	Daily
0			<u> </u>			L 7.55Pm	L 4.30Pm	ւ 7.30Am			.ST. PA			A	131.23	к	A 7.30Am	A 3.30pm	A 8.30Pm	
11	1	TD	AINS	PET	rween (8.30 _{Pm} ST. PAU	4.55Pm			. ARE	INNEA	POLIS	<u>*.l</u>	8	120.66 WIN C	K	T.05 _{Åt}	3.00pn		<u> </u>
				 -		SI. PAU	LANDI	LINDAL			1.60		<u> </u>				KWINAL	S IIIWIE	I ABLE,	
	Yard		L 8.	15Pm	L 1.10Pm				12.17 13.76	M	IDALE J 1.59 . W. JC			UD 	119.06 117.47	DIJNPRX J				A 3.00Am
17	87	44	8.	25	1.20		• • • • • • • • • •		17.17	RO	3.41 BBINSD: 6.48	ALE] ;	RB	114.06	DPX				2.47
24	92	72		35	1.30		· · · · · · · · · · · · · · · · · · ·		23.65		9.01		1 1	SI	107.58	DP				2.35
33	99	19	8.	48	1.43			•••••	32.66		6.26	<u> </u>	-	RO	98.57	DP			<u> </u>	2.20
39	98	29		00	1.55				38.92	1	BERTVII 8,43		(P)	SA	92.31	DP		• • • • • • • • • •		2.07
48 62	79 80	43 13		14 35	2.08 2.30				47.35 62.15	1	NTICEI 14.80 EARWAT		1 1	MC: CW	83.88 69.08	DP DP	• • • • • • • • • • • • • • • • • • • •			1.52
02	au	10									12.67		11			BDNKOR		• • • • • • • • • • • • • • • • • • • •		1.20
	Yard		IA 10.	05 Pm	A 3.00 Р ш				74.82	1	r. cLot		/ 	DX	56.41	WXYZ	<u>,</u>		<u> </u>	L [2.45Am
G63	• • • • •	182			• • • • • • • • • • • • • • • • • • • •	L 9.32Pm A 9.40		L 8.57Am	• • • • • • • • • • • • • • • • • • • •	EAS	1.54		۱ ا	• • • •		DNPIX	A 5.48Am	1		
75	Yard	1501						L 9.08	74.82	S1	r. CLOU 0.73		ABS	DX	56.41	BDNKOF WXYZ	A 5.35	L 1.28	L 6.50 A 6.47	
	• • • • •					A 9.47Pm	A 6.12Pm	A 9.10Am	75.55	R	ICE JC.] [• • • •	55.68	IJPX	L 5.32An	L 1.22Pm	n L 6.45Pm	
I-10	57	39	ļ					<u> </u>	85.15	ļi	9.60 ROCKVI	LLE			46.08	P				
I-15	110	73							89.96	с	OLD 5P 4.49	RING		CG	41.27	DP				
I-20		42							94.45		RICHMO 6.21		. ''	RI	36.78	DP				
I-26	• • • • •	85		·····	• • • • • • • • • • • • • • • • • • • •		•••••		100.66		.ROSC(- }.	XN	30.57	DP				
I-31		51	-						106.09		12.06			SY	25.14	DIPX			<u> </u>	
I-43	50	3 8	ļ		• • • • • • • • • • • • • • • • • • • •			 	118.15	N	EW LON 4.31	IDON	- 1	ND	13.08	DPX				
I-48 A102	Yard	35 1661]	····					122.46 131.23		SPICE 8.77 WILLM			CR. W	8.77	DP BDNOK TRWXZ				
									101.50				- -							
			1. 84.	50 17	1.50 84 .17	0.15 9.08	0.12 11.35	0.13 10.48		Avers	ge Speed	bdivision Per Hou	ir,				0.16 8.51	0.14 9.73	0.13 10.48	2.15 27.84
W.	EST	W.	ARD	T	HIRD	SUBDI	VISIOI		TWA	RD	WE	STWA	ARI)	FOU.	RTH S	UBDIV	ISION	EAST	WARD
	٦		rom	_	Time	Table I	No. 113	=			ST.				1	ime Ta	able No	. 113		1.4
a 5	1 -	<u>, </u>	•			Effective			1	GNS		.	from		_		fective		S I	:
Station Numbers	Capacity	Ta OK	Distance Morris			May 26, 19		Telegran			Z		noe f				26, 1963		q	SIGNS
- ×	1 0	-	H4			STATION			<u>' </u>		Station Num	Capacity Tracks	Distance Waysata		-	ST	ATIONS		Telegraph	
A157	ı			• • • • •		. MORRIS. 8.22 . ALBERTA	••••••	★. M	R RI	BNK PYJ D		~		1						
D 6		.	8.22	••••		. ALBERTA 6.05 . CHOKIO.		A	j		A24		•••••	<u>.</u> .	•••••	w	AYZATA 6.60 Ing Park	• • • • • • • • • • •	WA	DPRJ
D12			14.27 20.17			.JOHNSON		K	- 1	D D	B 6 B 8	97 31	6.60 8.50	- 1		SPRI	ING PARK 1.90 IOUND		··· PK	D
	_					7.04			_		B13	35	13.07	- 1			4.57 ONIFACIU:	s.,,,,,,,,,	MU	D D
D25	1		27.21 . 33.09 .	• • • • •	G	RACEVILL 5.88 BARRY	·E	G	1	יים ס	ļ ———			- -			7.81			
D89	1		40.44			7,35 B eards le	Y	В:	1	D	B21 B28	17 49	20.88		· · · · · · · · ·	LESTE	NAYER 7.48 ER PRAIRI		KY	D D
D45	j	- 1	47.37	· · · · · ·	BRC	OWNS VAL		В	1	DΤ	B44	88	44.42	- 1	•••••	HU1	16.06 CHINSON		но	DY
	Westward trains are superior to eastward trains of the same class on the Second, Third, and Fourth Subdivisions except as follows:																			
ľ	Nos. 4, 8 and 28 are superior to Nos. 3, 7 and 11 between Rice Junction and St. Cloud Passenger Station.																			
<u> </u>	SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 7 THROUGH 12.																			

4	WE	STW	ARD	ARD FIFTH SUBDIVISION EASTWARD										
Sers	Caps			SECON	D CLASS			Time Table No. 113			SECOND CLASS			
Station Numbers						419	ce from	Effective May 26, 1963	aph Calls	SIGNS	420			
Station	Sidings	Other	1 e .			Daily	Distance Willmar	STATIONS	Telegraph		Daily			
A-102		,				L 9.30Am		willmar	w	BDNKOR JWXZP	A 8.35Pm			
I- 70	50	32				10.00	11.99	11.99 RAYMOND	RA	DP ·	8.05	 		
I- 77	116	52		 	 	10.10	19.55	CLARA CITY	CA	DPI	7.53			
I- 83	61	88				10.20	25.48	MAYNARD	MY	DP	7.43			
I- 92	97	130				10.36	34.59	GRANITE FALLS	GX	DPI	7.27			
I-102	56	35				10.56	44.22	9.63 HANLEY FALLS	HY	DPI	7.10			
I-109	50	37				11.05	50.39		С	DP	7.01			
I-116		35			,	11.17	57.70		GV	DP	6.50			
I-121	148	144				11.25	63.07	MARSHALL	MD	DNXPU	6.40			
I-134	50	38				11.50	76.01	12.94 RUSSELL	RS	DP	6.19	,		
I-142		38			 <i>-</i>	12.02 Pm	83.88	7.87FLORENCE	F	DP	6.08			
I-147	100	56				12.10	88.89	5.01 RUTHTON	RV	DP	6.00			
I-155		37				12.21	96,73	7.84 HOLLÄND	HD	DP	5.45			
I-164	30	69				12.35	105.53	8.80 PIPESTONE	NE	DPU	5.30			••••••
I-170	120			l	 	12.45	112.27	6.74 		P	5.15			
I-175	53	108		 		12.52	116.88	4.61 JASPER	JA	DP	5.05			
I-183	50	35				1.03	124.58	7.70 SHERMAN		P	4.52			
I-186	145	220				1.10	127.90	3.32 GARRETSON	JC.	P DNKPRXY	4.45			,
IA-17	100	37				1.40	145.23	17.33 HILLS	нѕ	DPI	4.43			
IA-23	100	42	,		[1.50	151.65	6.42 LESTER	[[PI	4.02			
IA-30	101	34]		2.00	158.55	6.90 ALVORD	AD	DP	3.52			
IA-36	50	31				2,09	164.24	5.69 DOON	DO	DP	3.42			
IA-50	100	72				2.34	180.78	16.54 SIOUX CENTER	UX	DNP	3.42 3.17			· · · · · · · · · · · ·
IA-66	41	29			l	2.54 2.54	193.96	13.18 STRUBLE		P	2.54			••••••
IA-78	43	51				3.11	206.50	12.54 MERRILL		î P	2.30			
		,					211.96	5.46 TOWER	GS	DNIP	2.23			
IA-85	51	30				3.21	213.32	1.36 HINTON	ні	ĎD.	2.00			
IA-85	Yard	ou .	* * * * * * * * * *			3.40Pm	213.32	9.45 sioux city*	SX	DP BDNKOW RXZ	2.20 L 2.00 _{Pm}			••••••
						<u> </u>								
						6.10 36.12		Time Over Subdivision Average Speed Per Hour			6.35 33.84			

Westward trains are superior to eastward trains of the same class.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 7 THROUGH 12.

WE	STW	ARD			S	IXTH SUBDIVISION				EAS	rwa ri	D 5
E		SE	COND C	LASS		Time Table No. 113			SECOND CLASS			
Numh	ty of			579	se from	Effective May 26, 1963	ph Call	SIGNS	580			
Station	Capacity Tracks			Daily Ex. Sun.	Distance Garretsor	STATIONS	Telegra		Daily Ex. Sun.			
I-186 I-205	220 527			L 12.01Am	18.40		an 1c	DNKPRXY UJBD KPRXY	A 4.40Pm L 4.00Pm			
				.49 22.53		Time Over Subdivision Average Speed Per Hour			.40 27.60			

WESTWARD SEVENTH SUBDIVISION EASTWARD

Station Numbers	of	SECOND	Distance from Geneseo Jet.	Time Table No. 113 Effective	Calle		SECOND
ion A	Capseity Tracks	325	ance	May 26, 1963	Telegraph	SIGNS	326
Sta	Cap	Daily Ex. Sun.	Gen	STATIONS	Tele		Daily Ex. Sun.
		L 8.35Am		ABERDEEN LINE JCT		JP	A 8,45Pm
E45	36	A 8.40Am		G. N. JCT		J	L 8.42Pm
				G. N. JCT. AND GEN Y Soo Line R. R. Til			ARE
		L 10.15Am		GENESEO JCT		J	A 6.55Pm
E80	28	s 10.35	0.66	GENESEO	GO	D	s 6.50
E86	34	s 10.49	5.81	CAŸÜGA	CŪ	D BDJY	s 6.35
E92	85	s 11.15	11.94	RUTLAND, N. D	RJ	KRX	s 6.20
F 9	36	s 11.40	21.30	9.36 HAVANA 6.58	wB	D	s 5.35
F16	35	s 11.55	27.88	KIDDER	KS	D	s 5.20
			31.40	MILW. R. R. CROSSING		U	
F30	35	s 12.25Pm	42.13	AMHERST	MN	D	s 4.50
F36	34	s 12.40	48.50	CLAREMONT	QC	D	s 4.35
F47	24	s 1.05	59.33	PUTNEY			s 4.08
F64	175	A 1.45Pm	76.28	ABERDEEN	FN	BDIKRY	L 3.30 _{Рт}
		3.30 21.79		Time Over Subdivision Average Speed Per Hour			3.25 22.32

WESTWARD EIGHTH SUBDIVISION EASTWARD

Numbers		SECOND CLASS	from	Time Table No. 113	Catte	l	SECOND CLASS
	city of	337	ance fra	Effective May 26, 1963	Telegraph Calls	SIGNS	338
Station	Capacity Tracks	Mon., Wed. and Fri.	Distance Rutland	STATIONS	Tele		Mon., Wed. and Fri.
E 92	35	L 11.40Am		RUTLAND, N. D	RJ	BDJY KRX	A 5.25Pm
	!		29.77	C. & N. W. RY. CROSSING		U	
E126	34	s 1.10Pm	35.01	5.24 GUELPH	Gυ	D	s 3.55
E141	55	s 1.50	49.65	14.64 ELLENDALE 13.38	N	DU	s 3.15
E155	44	A 2.25Pm	63.03	FORBES	FO	DRY	L 2.40pm
		2.45 22.92		Time Over Subdivision Average Speed Per Hour	==		2.45 22.92

Westward trains are superior to eastward trains of the same class on the Sixth, Seventh and Eighth Subdivisions except No. 580 is superior to No. 579.

No. 337 and No. 338 will stop at Straubville and will stop on flag at Silver Leaf for revenue passengers.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 7 THROUGH 12.

6	W	ÆS	TWARI	и с	INTH SUBDIVISIO	NC	EAST	WARD	WES	STW	ARD	TENTH SUBDIVISION E	AS'	rward
Station Numbers		Other Tracks	SECOND CLASS 529 Daily Ex. Sun.	Distance from Benson	Time Table No. 113 Effective May 26, 1963 STATIONS	Telegraph Calls	SIGNS	SECOND CLASS 530 Daily Ex. Sun.	Station Numbers	Capacity of Tracks	Distance from Watertown	Time Table No. 113 Effective May 26, 1963 STATIONS	Telegraph Calls	SIGNS
A 133 C 9 C 16 C 22 C 30 C 37 C 46 C 52 C 58 C 66 C 73 C 92 C 102	43	36 15 31 324 34	s 8.40 s 9.30 s 9.55	7.88 15.83 21.96 30.65 37.14 46.34 51.82 57.98 65.57 72.82 91.99	BENSON ★ 7.88 DANVERS. 7.96 HOLLOWAY 6.13 APPLETON 8.69 LOUISBURG 6.49 BELLINGHAM 9.20 NASSAU 5.48 ALBEE 6.16 LA BOLT 7.59 STOCKHOLM 7.25 SOUTH SHORE 19.17 WATERTOWN 9.90 GROVER 6.36	BN DR OW AU BG BA NA NA VR	DNPKR JY D DNXI D D D D BDNK UOXJ	A 4.30pm f 4.10 f 3.52 s 3.40 f 2.55 f 2.35 f 2.23 f 2.10 f 1.55 f 1.40 s 1.00	C-92 WS-18 WS-23 WS-30 WS-39 WS-49 WS-55 WS-61 WS-67 WS-75	324 32 27 29 34 26 48 28 26 42 45	18.09 23.41 30.03 39.40 49.23 55.25 61.01 67.28 74.90 82.51 100.55	### WATERTOWN ### 18.09 ### 18.09 ### 18.09 ### 18.09 ### 18.09 ### 18.09 ### 18.00 ### 18.00 ### 18.00 ### 18.00 ### 18.00 ### 18.00 ### 18.00 ### 18.00 ### 18.00 ### 18.00 ### 18.00 ### 18.00 #### 18.00 #### 18.00 #### 18.00 #### 18.00 #### 18.00 #### 18.00 #### 18.00 ##### 18.00 ###################################	WN H NR B AR SN NU WH CH CO	BDNK UORXJ D D D D D D D D D D D D D
C109 C116 C124		37 41 35	10.15 10.35 11.25	108.24 115.17 124.05	HAZEL 6.93 VIENNA 8.88 WILLOW LAKE	Z VA WK	D UD D	s 2.0 Pm s 1.45 s 11.25	G	RAINS OVER	S BET	WEEN WEST JCT. AND EAST BY C. M. St. P. & P. R. R. TIM	JCT. E T/	ARE
C136 C141 C149 C162	•••••	35 36	s 11.55 s 12.10 _{Pm} s 12.30 A 1.00 _{Pm}	136.19 140.64 148.36 161.83	12.14 BANCROFT 4.45 . OSCEOLA 7.72 YALE 13.47 HURON	BF SC YA HU	D D D IDRY	s 10.55 s 10.45 s 10.30 L 10.00Am	I-205 I-222 I-231	527 50 36	102.32 103.66 104.39 121.27 129.88	1.77 EAST JCT. (C. M. St. P. & P.)	su ox	BDK UPRXYJ X D
			8.45 18.49		Time Over Subdivision Average Speed Per Hour			6.30 24.89	I-238 I-245 I-260 I-267	35 34 18 172	137.28 144.66 159.68 166.52	7.40 VIBORG. 7.38 IRENE. 15.02 MISSION HILL. 6.84 YANKTON.	VB RN YK	D D DRM

Westward trains are superior to eastward trains of the same class on the Ninth and Tenth Subdivisions except No. 530 is Superior to No. 529.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 7 THROUGH 12.

ALL SUBDIVISIONS

1. SPEED RESTRICTIONS GENERAL.

The following speed limits apply to trains and engines operating under the conditions outlined, unless rules or conditions require a further reduction.

- 50 MPH-Diesel engines light or with caboose only.
- 35 MPH—Trains or engines on main routes, actuating the points of spring switches; trains or engines thru No. 20 turnouts at following locations: End of double track at Wayzata. Wayzata, east and west switches. End of two main tracks at MP 98 and MP 105. Crossover just west of stockyards at Willmar and east crossover switch at Benson. Delano, east and west switches. Howard Lake, east and west switches. Cokato, east and west switches. Dassel, east and west switches of control siding. Litchfield, east switch of control siding. Atwater, east and west switches. Kerkhoven, east and west switches. Benson, east switch of control siding. Morris, east and west switches. Donnelly, east and west switches. Herman, east and west switches. Norcross, east and west switches. Campbell, west switch. M.P. 212, east switch of control siding. Robbinsdale, east and west switches. Sioux City, east switch 26th street yard.
- 30 MPH—On Main lines, when handling following equipment in trains, not in actual service but on own wheels, derricks, cranes, pile drivers, Jordan spreaders, shovels, wedge plows, scale test car, also ore cars series 80000 thru 94250 and air dump cars X-2000 thru X-2096, X-7000 thru X-7049 when such cars are loaded with ore or gravel.
- 25 MPH—Trains handling logs; trains or engines moving in facing point direction at spring switches without facing point lock; trains or engines thru No. 15 turnouts at following locations:
 Clontarf, west switch of control siding.
- 20 MPH—Trains handling the following equipment on Branch Lines or on 6 degree or sharper curves of Main Lines, scale test car, ore cars series 80000 thru 94250, air dump cars X-2000 thru X-2096, X-7000 thru X-7049 when such cars are loaded with ore or gravel.
- 15 MPH—Trains handling the following equipment on Branch Lines or on 6 degree or shaper curves of Main Lines, derricks, cranes, pile drivers, Jordan spreaders, shovels and wedge plows.

 Trains or engines moving thru interlockings against the current of traffic on double track; trains or engines thru all other turnouts, except equilateral

turnouts, and those shown previously in this item.

- 1(a). Rule 240 W of the Consolidated Code of Operating Rules is modified to permit handling Great Northern cars 60276 through 60279, 61000 through 61009 and 61500 through 61524 in passenger trains at passenger train speeds.
- 2. MOVEMENT OF ENGINES DEAD IN TRAINS. Engine 2350 must be handled on rear of freight and mixed trains. Diesel engines 1 thru 196 or any road switcher unit not equipped with alignment control couplers must be towed as single units. On engines 550 thru 599, coupler alignment control lock blocks must be "DOWN" when coupled in multiple unit operation.

Following road switchers are equipped with alignment control couplers:

200	through	218	
220	"	230	
550	22	599	(lock blocks)
600	"	699	
700	27	734	
900	**	915	
9000	**	9095	

Single unit diesel engines, or multiple unit groups (when such groups consist of road freight, road passenger, or engines with alignment control couplers), when towed dead in freight trains, are to be handled not less than five (5) cars nor more than fifteen (15) cars behind the road engine. There should not be more than five (5) units in a group. Additional such units or groups of units must be separated by not less than five (5) cars. When towing diesel engines dead in trains the following speeds must not be exceeded:

MA	XIMUM SPEED	ENGINE NUMBER
50	MPH	1 thru 10, 14 thru 16, 24 thru 28,
		75 thru 162, 165 thru 170.
79	MPH	350 thru 875, 500 thru 512, 679,
		680, 2350.
65	MPH	All other diesel engine units.

- 3. Except at points where it is necessary to classify trains, open cars loaded with poles, piling, lumber, timber, pipe, or other lading which might shift, should be placed as close as possible to the head end of trains, but not next to engine, caboose, occupied outfit car, passenger car or another unprotected car containing commodities which might be subject to damage. Loaded trailer-on-flat cars and multi-level automobile cars are not included in this category. In double track territory, trains handling such cars must use extreme care to avoid slack running in or out when passing or being passed by other trains. In single track territory, trains handling such cars must be at stop when on siding or other track to meet or be passed by other trains, except when they have more cars than siding will hold, it is permissible for such trains to pull by each other at restricted speed. Loaded dump cars should not be handled on double track after dark, but if necessary to do so, close watch must be maintained by members of the crew, and if a car dumps its load, train must be stopped at once and protection provided as prescribed by the rules.
- Brakemen with less than one year of experience should not be used as flagman except in emergency, and then Superintendent will be notified by wire.
- 5. Due to limited overhead clearance at tunnels and structures, employees are warned to keep off top of cars of extreme height and width when handled in trains and yards, except in emergency. In absence of previous advice on such cars, wire proper officer for instructions.
- Placarded loaded tank cars handled in through freight or mixed trains shall not be nearer than 6th car from engine, occupied caboose or passenger car.

Cars placarded "Explosives", "Flammable", "Corrosive Liquids", or "Poison Gas" handled in through freight trains, local and mixed trains, shall not be nearer than 16th car from engine, occupied caboose or passenger car.

When length of train will not permit handling of cars as prescribed above—ANY PLACARDED CAR, loaded with above commodities—shall be placed near middle of train, but not nearer than 2nd car from engine, occupied caboose or passenger car.

When switching such cars in terminal yards they must be separated from engine by at least one non-placarded car.

When placarded cars described above are handled in freight trains made up in "blocks" or classifications, placarded car or cars shall be placed near middle of the "block" or classification, but not nearer than 6th car from engine, occupied caboose or

passenger car.

When such placarded cars are placed in trains they must not be placed next to each other, next to refrigerators equipped with gas-burning heaters, stoves or lanterns, or next to loaded flat cars, or gondola cars containing lading higher than ends of car that is liable to shift.

Carload express shipments of explosives, sealed and placarded, may be handled on passenger trains; LCL shipments may be made in so-called peddler car with messenger in charge when such car is assigned to the handling of express and baggage exclusively.

Terminal or pick-up points enroute must furnish conductor and engineer Form 250 showing consecutively location in train of all cars placarded "Explosives". At points other than terminals where crews change, notice will be transferred from crew to crew.

Employes will be guided by further instructions governing handling of loaded tank cars, Explosives, Flammables, Corrosive Liquids, and Poison Gas found in I.C.C. Regulations and Consolidated Code Rules 727 and 811.

7. Trains, departing from stations, either from siding or main track in trailing point movement actuating points of spring switches, a member of crew must observe indication of governing signal in opposite direction after rear end of train has passed through switch to ascertain if switch points return to normal position. If this signal indicates Stop and no immediate train movement or other cause is evident report the fact to Superintendent from first available point of communication.

During and immediately following snow storms or violent wind storms, spring switches must be operated by hand and relined to normal position before heading out through switch in trailing point movement, actuating switch points, to insure switch is in proper operating condition.

- 8. Facing point locks on hand operated switches are indicated by a six inch yellow stripe painted on target staff. Be positive locking device is restored to normal position after using. A running switch must not be made through this type switch.
- Rule 2 of the Consolidated Code of Operating Rules is modified for Great Northern Railway Company employes to the extent that a watch certificate form is no longer required. Watches of employes will be inspected by Division Officers, Rules Examiners and other designated officers.
 - Rule 3 (C) of the Consolidated Code of Operating Rules is amended as follows: Empoyes governed by time service rules must not wear wrist watches while on duty unless such watches are of an approved type. Approved type wrist watches are: Elgin, B. W. Raymond model, 13/0 size, 23 jewels. Ball Official Standard, 1604 B, stainless steel, 13/0 ligne, 21 jewels. Bulova Accutron Railroad Approved Model.
- 10. Regarding Consolidated Code Rule 103.

 In addition to complying with the provisions of this rule, members of a crew will be governed by the following: When an engine, with or without cars, is about to move over a public crossing not protected by a watchman, by gates or by crossing signals in operation, a member of the crew must be on the ground at the crossing to provide protection. Exception—In the movement of a through yard transfer or of a light engine being handled only by hostlers, it is not necessary for a member of the crew to be on the ground at the crossing.
- 11. St. Paul Union Depot and Minneapolis, in order to facilitate the handling of patients arriving on cots in baggage cars and who require use of wheel chair or stretcher, conductors will wire Union Depot Company, St. Paul, or Stationmaster, Minneapolis, describing the class of service required.
- 12. "The Consolidated Code of Operating Rules, Edition of 1959, in addition to the following instructions will govern Great Northern employees while operating on Minnesota Transfer Railway Co. and St. Paul Union Depot Company trackage:

(a) All trackage of the Minnesota Transfer Railway Company is defined as a system of tracks within yard limits over which movements must be made at restricted speed and are not authorized by timetable, or train order, but subject to prescribed signals and rules or special instructions.

The limits of The St. Paul Union Depot Company property extend from connection with the Northern Pacific Ry. and Great Northern Ry. tracks at Third Street and connection with CMStP&P-CB&Q R. R. tracks opposite depot roundhouse, on the east, to connection with the CGW Ry. and the CMStP&P R. R. tracks at Robert Street on the west.

- (b) The timetable of the St. Paul Union Depot Company is for information only. Employes of railroads using the tracks of this Company will be governed by current timetable of their respective Companies only as to arriving and departing time of trains.
- (c) Where in the rules of the Consolidated Code reference is made to trains, such rules will also apply to yard movements and engines.
- (d) Under Rule 15, the use of torpedoes is prohibited.
- (e) Under Rule 11, burning fusees must not be used except in case of emergency and then only when held in hand and must be extinguished before leaving.

THE FOLLOWING RULES APPLY ONLY ON THE ST. PAUL UNION DEPOT COMPANY PROPERTY:

- (f) There is no superiority of trains within the limits of St. Paul Union Depot Company property.
- (g) Within the limits of the St. Paul Union Depot Company property trains and engines must move at restricted speed and must not exceed ten (10) miles per hour through crossovers, turnouts and puzzle switches. The entrance to and all movements on this property will be made only on authority of hand signals from switchtenders. No train or engine may foul any track or puzzle switch without authority of hand signals from switchtenders in control of such movements, except that short interior switching movements may be made through crossovers connecting shed tracks when authorized by train director. Any lead or track may be used for the make-up of trains on authority of train director. The movement of trains should be given preference.
- (h) When indicated by the ringing of the bell, flashing of headlight, hand or light signal that a train or engine is ready to move, the switchtender in charge of the shed track on which the movement is standing will handle as follows: at west end of station the switchtender will control the movement by hand or light signal; at the east end of station the switchtender will inform the train director, who will route the movement by instructions over the public address system. Switchtenders will be governed by these instructions, relaying such instructions by hand or light signal to the next switchtender in the direction of the movement, each must receive an acknowledgment before signaling the movement. Signals must not be acknowledged or acted upon unless the signal corresponds with instructions from the train director and is definitely understood.
- (i) When backing, the back-up air brake valve on passenger trains must be operated by the conductor, except in the movement of empty equipment, it may be operated by a competent trainman or yardman. When practicable, conductor must see that trainmen are stationed so hand or light signals may be used, in case of any emergency. When backing a train, the engine brake valve must be in running position; an application of the brakes must be made with back-up air brake valve before starting and it must be known that brakes are in operative condition. Movement must not be started until the proper signal is given. A running test must be made with the back-up air brake valve before the train has moved 300 feet; if the running test is not made within 300 feet the engineer must stop the train and ascertain cause. The speed of train must not exceed eight (8) miles per hour and train must be under such control that it can be stopped short of train, or obstruction, and short of bumping post on stub tracks.
- (j) Headlights must be dimmed while on shed tracks.

FIRST SUBDIVISION

(Main Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

2. TRAIN REGISTER EXCEPTIONS.
Willmar, register is for freight trains only.

8. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

All trains must obtain Clearance Form A at Willmar.

At Lyndale Jct., trains for which this point is initial station may proceed on authority of clearance under which such trains arrive, when train order signal indicates proceed.

Westward Seventh Subdivision trains will require Soo Line R.R. clearance at Campbell.

4. CONDITIONAL STOPS.

No. 27 stops at Wayzata to discharge passengers from Chicago and east and to pick up passengers destined Fargo and west where No. 27 is scheduled to stop.

No. 14 stops at Wayzata to discharge passengers from Fargo and west and to pick up passengers destined Chicago and east.

- Lyndale Jct., eastward freight trains on Willmar Line having cars to set out at this point will stop before passing eastward Home Signal to make setout.
- 6. All movements on house track over State Aid road No. 11 just west of depot Campbell, all movements on industry track over 4th Street Crossing Donnelly and 4th Street Crossing Waverly must be protected by flagman.

At Wayzata, when switching over Barry Avenue Crossing, or when standing on either main track, and a train is approaching on adjacent track, a member of the crew standing at the station will protect the crossing on the ground.

7. SPEED TEST BOARDS.

Engineers shall test speed of their trains passing following points as compared with Speed Table:

Westward trains, between MP 18.75 and MP 19.75 five miles east of Wayzata.

Eastward trains, between MP 87 and MP 86 two miles west of Grove City.

Westward trains between MP 110 and MP 111 one mile west of Pennock.

Eastward trains between MP 205 and MP 204 two miles east of Doran.

8. CROSSOVERS ON DOUBLE TRACK AND TWO MAIN TRACKS.

Facing Point

Willmar, double crossover just west of stockyard.

9. Consolidated Code Rules 251, 251 (A), 253 and 254 are in effect on the double track between Lyndale Jct. and beginning of CTC at end of double track Wayzata. The use of these rules does not modify Rule 99.

10. INSTRUCTIONS GOVERNING OPERATION OF TRAIN AND ENGINES WITHIN CENTRALIZED TRAFFIC CONTROL SYSTEM

Two main tracks known as—NORTH MAIN and SOUTH MAIN—extends between the following points:

MP 98 and MP 105.

Willmar is the control station for CTC under the supervision of train dispatcher.

THE FOLLOWING SIGNALS ARE LOCATED TO THE LEFT OF THE TRACK WHICH THEY GOVERN:

Eastward on North Main Track:

Signal 99.4.

Westward on South Main Track:

Signal 99.5.

Benson:

Double crossover at MP 132 for westward movements from Main Track to controlled siding—and for eastward movements from controlled siding to Main Track.

Morrie

Eastward governing home signal on siding at east end of siding.

11. MANUAL INTERLOCKINGS.

12. AUTOMATIC INTERLOCKINGS.

Soo Line R.R. crossing2.17 miles west of Tintah

13. Diesel radiator and boiler water stations.

Willmar.

Morris.

SECOND SUBDIVISION

(Osseo Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Freight
Lyndale Junction and St. Cloud	50 MPH
St. Cloud and Willmar	40 MPH
;	

2. SPEED RESTRICTIONS.

Between Home Signals of Interlockings at: 20 MPH Rice Jct.

Paynesville.

3. TRAIN REGISTER EXCEPTIONS.

Lyndale Jct., all trains register by ticket.

St. Cloud, First Class Trains will register by ticket.

4. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

At Lyndale Jct., trains for which this point is initial station may proceed on authority of clearance under which such trains arrive when train order signal indicates proceed.

All trains must obtain Clearance Form A at St. Cloud.

Trains originating at East St. Cloud may proceed without a clearance.

Trains originating at Rice Jct. may proceed without a clearance. At M. W. Jct., eastward M. W. trains will not require a clearance.

5. All movements on industry track over Noble Avenue Crossing, 1000 feet east of depot Robbinsdale, must be protected by flagman.

All movements on the North Maiers Transfer & Storage track St. Cloud must be protected by flagman when crossing 25th Avenue.

Track north of main track extending approximately 2 miles eastward from depot, St. Cloud, is known as LONG LEAD and must be kept clear for meeting and passing of trains.

7. SPRING SWITCHES WITH FACING POINT LOCK.

Robbinsdale, east and west siding switch.

Osseo, east and west siding switch.

Rogers, east and west siding switch.

Albertville, east and west siding switch.

Monticello, east and west siding switch.

Clearwater, east and west siding switch.

Normal position is for main track.

8. AUTOMATIC INTERLOCKINGS.

M.W. Ry. crossing	0.76 miles west of Lyndale Jct.
Soo Line RR. crossing	1.34 miles west of Robbinsdale
Soo Line RR. crossing	0.76 miles west of Paynesville

9. MANUAL INTERLOCKING WITH DUAL CONTROL SWITCHES.

Rice Jct.

This switch is electrically controlled by operator at St. Cloud.

10. Diesel radiator and boiler water stations.

Monticello.

St. Cloud.

THIRD, FOURTH, FIFTH AND SIXTH **SUBDIVISIONS**

(Browns Valley, Hutchinson, Sioux City and Sioux Falls Lines)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Freight
Morris and Browns Valley	35 MPH
Wayzata and Hutchinson	
Willmar and Sioux City	49 MPH
Garretson and Sioux Falls	

2. SPEED RESTRICTIONS.

Between Home Signals of Interlockings at: 20 MPH Clara City.

Hanley Falls.

C.&N.W. Ry. Crossing 6.68 miles east of Hills.

Hills.

Wren Tower.

CMStP&P. RR. crossing 1.13 miles west of Sioux City. Sioux Falls.

Garretson, within city limits..... I. C. RR. Crossing, 2.89 miles east of Sioux City........ 10 MPH

Between Morris and Browns Valley.....GP-9 heaviest permitted Between Wayzata and HutchinsonGP-9 heaviest permitted

4. TRAIN REGISTER EXCEPTIONS.

Garretson, Register only for trains originating and terminating.

- 5. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B). All trains must obtain Clearance Form A at Garretson.
- 6. Pipestone, trains and engines using CRI&P main track between G.N. interchange track switch and east end of CRI&P siding, must move at restricted speed, and must be governed by current operating rules and time table of CRI&P Ry.

7. AUTOMATIC INTERLOCKINGS.

CMStP&P. RR. crossing1.44 miles east of Granite Falls C&NW. Ry. crossing0.32 miles east of Hanley Falls C&NW. Ry. crossing ______6.68 miles east of Hills CRI&P. Ry. crossing0.22 miles west of Lester CMStP&P. RR. crossing1.13 miles west of Sioux City C&NW. Ry. crossing ______3.96 miles east of Sioux Falls

Granite Falls, push button controls are located on east end of depot, at crossover switches, at east siding switch, and on eastward home signal. Trains and engines occupying main track at depot or lining east siding switch or crossover switches, for movements out of siding automatically set up route for eastward movement through interlocking at CMStP&P crossing, provided no conflicting movement on CMStP&P track, and will hold this set up for a period of approximately four minutes, after which, set up for a period of approximately four minutes, after which, if route is not used, automatic interlocking control can be taken away by CMStP&P trains or engines approaching crossing. If an eastward train occupies main track at depot for meeting trains or station work for a period in excess of four minutes, trainman must operate push button at depot or at crossover switches to obtain interlocking route. If an eastward train occupies main track between controls of operated approach and home circular for a residual. track between eastward approach and home signals for a period in excess of four minutes, trainman must operate push button at east siding switch or on home signal to obtain interlocking route. Push button boxes must be kept closed and locked except when

CMStP&P. RR. crossing 1.13 miles west of Sioux City is under supervisory control of CMStP&P Operator West Yard.

8. MANUAL INTERLOCKING.

I.C. RR. crossingWren Towe

9. SEMI-AUTOMATIC INTERLOCKINGS.

M.W. Ry. crossing0.46 miles east of Clara City

If a train is stopped by a Stop-indication and no immediate conflicting train movement is evident, and both smash boards are in reverse position, trainman may signal train to proceed over the crossing after making certain that gates are set against conflicting route. If smash boards are not in reverse position, trainman shall operate them by hand with crank attached to mechanism.

10. RAILROAD CROSSINGS PROTECTED BY GATES.

I.C. RR. crossing2.89 miles east of Sioux City
Normal position is clear for Great Northern.

11. SPEED TEST BOARDS.

Engineers shall test speed of their trains passing following points as compared with Speed Table:

Westward trains, between MP 7 and MP 8 between Priam and Raymond.

Eastward trains, between MP 121 and MP 122 between Jasper and Sherman.

Westward trains, between MP 134 and MP 135 between Garretson and C.&N.W. Ry. crossing.

Eastward trains, between MP 208 and MP 209 between Merrill and Wren Tower.

12. Diesel radiator and boiler water stations.

Garretson.

Marshall.

13. Unless otherwise instructed, protection against following trains, as required by Consolidated Code Rule 99, is not necessary between stations on the Third and Fourth Subdivisions and Form Z train order is not required between the above stations. If it becomes necessary to operate a following train when there is still a train between the above stations, the train ahead must be notified to protect against the following train. If this is not practical, the following train must be notified to protect against the train ahead.

SEVENTH, EIGHTH, NINTH AND TENTH SUBDIVISIONS

(Aberdeen, Forbes, Huron and Watertown-Yankton Lines)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Freight
Geneseo Jct. and Aberdeen	45 MPH
Rutland and Forbes	25 MPH
Benson and Huron	35 MPH
Watertown and Yankton	25 MPH

2. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

At Aberdeen Line Jct., trains for which this point is initial station may proceed on authority of clearance under which such trains arrive.

3. SPEED RESTRICTIONS.

Between Home Signals of Interlockings at:20 MPH
Aberdeen.
Appleton.
Huron.
Arlington.

Lennox.

Davis.

Watertown, within city limits	6 MPH
Arlington, within city limits	10 MPH
Yankton, CMStP&P. RR. crossing	10 MPH

4. ENGINE RESTRICTIONS.

Between Geneseo Jct. and AberdeenGP-9 heaviest permitted Between Rutland and ForbesGP-9 heaviest permitted Between Watertown and HuronGP-9 heaviest permitted Between Watertown and YanktonGP-9 heaviest permitted

5. AUTOMATIC INTERLOCKINGS.

C&NW. Ry. crossing	0.62 miles east of Aberdeen
CMStP&P. RR. crossing	0.64 miles east of Aberdeen
CMStP&P. RR. crossing	0.77 miles west of Appleton
C&NW. Ry. crossing	0.64 miles east of Huron
C&NW. Ry. crossing	0.97 miles west of Arlington
CMStP&P. RR. crossing	0.21 miles west of Lennox
C&NW. Ry. crossing	3.54 miles west of Davis

6. RAILROAD CROSSINGS PROTECTED BY GATES.

CMStP&P. RR. crossing1.41 miles east of Yankton Normal position is stop for Great Northern.

- 7. Westward Seventh Subdivision trains will require Soo Line RR. clearance at Campbell.
- 8. Eastward Seventh Subdivision trains will require Soo Line RR. clearance at Aberdeen.
- 9. Unless otherwise instructed, protection against following trains, as required by Consolidated Code Rule 99, is not necessary between Geneseo Jct. and Aberdeen on the Seventh Subdivision; between stations on the Eighth and Ninth Subdivisions; between Watertown and West Jct. and between Sioux Falls and Yankton on the Tenth Subdivision and Form Z train order is not required between the above stations. If it becomes necessary to operate a following train when there is still a train between the above stations, the train ahead must be notified to protect against the following train. If this is not practical, the following train must be notified to protect against the train ahead.

SPEED	TA	DI	E
355.51	8 24		

		il		
Time Per M		Time P		Miles
Min. Se	ec. Per Hour	Min.	Sec.	Per Hour
1	6 78.3	1	18	46.2
4		1 1	20	45.0
4		i	20 22	43.9
. 4	0 10.0	1 1	24	42.9
. 5		1 1	26	41.9
: 5	1 70.6	1 1	28	40.9
5	2 69.2	i	30	40.0
5	3 67.9	1	33	38.7
5		1	36	37.5
5		1	89	36.4
5		1	42	35.8
5		1 1	45	34.8
5		1 1	50	32.7
		1 1	5 5	31.3
5		1 .	99	30.0
	0 60.0 1 59.0		10	27.7
1			20	25.7
1	2 58.1 8 57.1 4 56.8 5 55.4 6 54.5 7 53.7 8 52.9	1 2 2 2 2 2 2 2 3 8		24.0
÷	4 56.8	6	80 40	
÷	5 55.4		40	22.5 20.0
+	0 00.4	1 :		
÷	6 54.5	11 7	80	17.1
1	7 53.7		_	15.0
1	8 52.9	1 9	_	12.0
1	9 52.2	11 5		10.0
1 1	0 51.4	1 7		8.6
	2 50.0	5 6 7 8 9	_	7.5
1 1	4 48.6			6.7
1 1	6 47.4	10	_	6.0
		<u>и</u>		

BUSINESS TRACKS

NAME	LOCATION	Capac- ity Cars	Switch Opens
First Subdivision			4
Montrose	6.70 miles west of Delano	28	E & W
Charlesville	6.47 miles west of Norcross	24	E & W
Second Subdivision			
Tileston Mill Spur	3.50 miles east of St. Cloud	288	East
Oscar Roberts Co. Inc	1.56 miles west of Robbinsdale 1.57 miles east of Osseo	8	West West
North Star Concrete Co. Spur	0.50 miles west of Osseo	19	West West
St. Cloud Rendering			11 000
Co. Spur		6	East
Empire Quarry Spur	2.47 miles west of Rice Jct	141	East
North Star Granite Corp. Spur	4.23 miles west of Rice Jct	41	West
Cold Spring Granite Spur	5.01 miles west of Rice Jct	7	East
Hawick	5.45 miles west of Paynesville	40	$\mathbf{E} & \mathbf{W}$
Gravgaard Spur	7.29 miles west of Paynesville	7	E & W
New London Materials and	8.46 miles west of Paynesville	ا به	T-7 6. TX7
New London Gravel Pit	1.73 miles east of New London	34	E & W
New London Gravel Pit	1.75 miles east of New London	250 6	E & W East
Steel lanks, Inc	1.20 mmes east of 1444 hondon	۱۳	Last
Fourth Subdivision	l l	I	
Cox Bros. Spur	0.53 miles west of Spring Park	2	West
Manle	4.18 miles west of St. Bonifacius	13	West
New Germany	3.80 miles west of Mayer	26	E & W
Silver Lake	7.83 miles west of Lester		
	Prairie	23	West
		1	
Fifth Subdivision	F 07 7		TIT and
Priam	5.97 miles west of Willmar	18	West
Asbury	3.73 miles west of Maynard 0.58 mile west of Marshall	85	E&W
Readi-Mix and On Spur	6.69 miles west of Marshall	6 17	East West
Lynd Parking	8.96 miles west of Marshall	19	E & W
Maurice		2	E of W
maurico	O'A HITTON MANE OF DIGHT COTTON	- 1	Man
Sixth Subdivision			
Corson	8.26 miles west of Garretson	87	E & W
Pathfinder Spur	112.38 miles west of Garretson I	27	West
Lawrence Spur	13.76 miles west of Garretson	45	E & W
Crampton Spur	15.24 miles west of Garretson	22	West
Seventh Subdivision			
Tidearmond	5.70 miles east of Geneseo Jct.	88	E&W
Hankinson	17.90 miles east of Geneseo Jct.	55	R & W
Huffton	5.86 miles west of Claremont	21	E & W
Eighth Subdivision			
Straubville	18.64 miles west of Forbes	٠.	
	Line Jct.	84	E & W
Silver Leaf	7.09 miles west of Guelph	7	West
W-1 G-1 2-1-1-			
Ninth Subdivision	12 26 miles west of South Shore	84	E & W
Rauville	. 18.26 miles west of South Shore	04	2 0 11
Tenth Subdivision			
Foley	4.24 miles west of Watertown	9	E & W
Lyons	5.82 miles west of Colton	15	E & W
Crooks	. 11.41 miles west of Colton	14	E & W
Tea	. 10.92 miles west of Sioux Falls	28	E & W
Naomi Spur	2.50 miles west of Lennox	7	East
	9.18 miles west of Irene	22	E&W
Volin	0110 111101 11001 01 110101111111111		