COMPANY SURC	EONS
*Dr. Abbott Skinner, Chief Medical *Dr. Hugo F. Schroeckenstein, Asst.	
-	St. Paul. Minn
*Dr. Robert S. Flom	St. Paul. Minn.
Dr. James N. Berbos	Aberdeen, S.D.
*Dr. Carson B. Murdy Dr. William C. Kaufman	Appleton Min
*Dr. R. P. Griffin	Rencon Minn
Dr Robert H Neison	Rengon Minn
*Dr. Louis T. O'Brien	Breckenridge, Minn.
*Dr. Louis T. O'Brien Dr. C. W. Jacobson Dr. Theodore Greenfield	Breckenridge, Minn.
Dr. Joseph C. Houts	Dassel, Minn
Dr. I. L. Oliver	Graceville Minn
Dr. Carl L. Landell	Granita Falls Minn
Dr. W. H. Saxton Dr. Kenneth H. Peterson	Huron, S. D.
Dr. V. S. Irvine	Idgerwood N D
Dr. V. S. Irvine *Dr. B. C. Ford	Marshall, Minn.
Dr. Phillip C. Hedenstrom	Marshall Minn
Dr. J. E. Eckdale *Dr. Ernest R. Anderson	Marshall, Minn.
Dr. William E. Hart	Monticello Minn
*Dr. R. A. Rossberg *Dr. Jack Guy	Morris, Minn,
*Dr. Jack Guy	New London, Minn.
Dr. I. J. Bioedel	Osseo, Minn
Dr. C. R. Myre *Dr. Everett J. Schmitz	St. Cloud Minn
# 11r (2 H (2006rd	Of Classification
*Dr. Vernon E. Neils *Dr. John F. Alden *Dr. Darrel E. Westover *Dr. A. L. McGilvra	St. Cloud, Minn.
*Dr. John F. Alden	St. Paul, Minn.
*Dr. A. L. McGilvra	Sioux Center Iowa
Dr. H. E. Rudersdorf	Signx City, lows
*Dr. G. Robert Bartron *Dr. Lloyd C. Gilman *Dr. Walter E. Hinz	Watertown, S. D.
*Dr. Walter E. Hinz	Willmar, Minn
TIJE, A. M. MICLINEEDV	W 111771 OF RESTRICT
*Dr. R. P. Michels Dr. Chester B. McVay	Willmar, Minn.
*Designates also Examining Surgeon	Yankton, S. D.
Designates also Examining Durgeor	L.
OPHTHALMIC SUR	
(Eye Doctors	•
Dr. Malcolm A. McCannel Dr. Richard C. Horns	Minneapolis, Minn.
Dr. Donald C. Sterner	St. Pani Minn
Dr. Donald C. Sterner Dr. W. T. Wenner	St. Cloud, Minn.
Dr. James E. Reeder	Sioux City, Iows
Dr. James E. Reeder Dr. Sidney F. Becker Dr. Stanley S. Chunn	Sioux Falls, S. D.
Di Stantoj D. Catalii	
ROENTGENOLOG (X-Ray only)	
Dr. David A. Burlingame	St. Paul. Minn.
Dr. Rolf M. Iverson Dr. Malcolm B. Hanson	Minneapolis, Minn.
Dr. Malcolm B. Hanson	Minneapolis, Minn.
P. B. RASMUSSEN, Asst.	
J. G. TOOMEY, Asst. Supe	rintendent.
D. W. HARTUNG, Chief D	
K. W. BATCHELLER, Mas	
G. T. RASMUSON, Trainm	aster.
M. M. DONAHUE, Trainma	
F. L. HENRY, Trainmaster	
A. D. POWERS, Trainmast	er.
J. H. BOYD, Trainmaster.	_
R. D. NELSON, Trainmaste A. Q. FORD, Traveling En	

H. M. LARY, Traveling Engineer J. B. MURRAY, Traveling Engineer

GREAT NORTHERN RAILWAY COMPANY

WILLMAR DIVISION

EFFECTIVE 12:01 A. M.

CENTRAL STANDARD TIME

Tuesday, September 8, 1964

W. L. SMITH, Superintendent

R. N. WHITMAN, General Manager.

H. J. SURLES,

General Superintendent Transportation.

Printed in U.S.A.

	WI	ESTW			1		1	FIRST SUBDIVISION	OI.	1					EASTV	
Numbers	Са	Car pacity	SECON	D CLASS	FIRS	CLASS		Time Table	Ì	Calls	8_		F	RST CI	.ASS	SECO
on Nun	8.8		5 TOFC	329	31	27	tance from Paul	No. 118 Effective September 8, 1964		raph Cr	Distance from Breekenridge	SIGNS	32	14		33°
Station	Sidings	Other Tracks	Daily	Daily		 	99. 194.	STATIONS	-	Telegraph)istar Ireek		 			Dail
	<u> </u>		Ex. Sat.	Ex. Sun.	Daily	Daily	<u> </u>	1				<u> </u>	Daily	Daily	-	Ez. S
0 11					L 9.50p		1	ST. PAUL		U	214.85	K	A 6.45A	``I	i	
	1	1			<u> </u>	<u> </u>	<u> </u>		*	s	204.28	K	6.20A	7	7	· · · · · · ·
-	ĭ	RAINS	BETW	EEN ST.	PAUL.	AND LY	NDALE	JCT. ARE GOVERNED	1 3	YT	WIN	CITY TE	RMINAL	S TIME	TABLE.	·
	Yard		i. 10,00pn		L 10.24p	. 0.00	1,,,,	LYNDALE JCT	zo .							1
A 24	200	58	10.15	1	10.246	n L 9.09år 9.23	12.17 23.90	EN LYNDALE JCT	⋖	i	202,68 190.95	DNJPX	A 6.05An	1 .	m'	· ·····
A 27		19					27.00	LONG LAKE		i	187.85	DPJ P	5.50	8.49		
A 32		15			.		31.37	4.37 MAPLE PLAIN			183.48	DP				
A 89	188	54					88.36	6.99 DELANO*		DA	178 40	DP			1	
A 48		26					47.83	9.47 WAVERLY	- [1	176.49 167.02	DP	j			· [· · · · ·
A 53	307	59					52.84	HOWARD LAKE	- 1	- 1	162.01	DP				1
A 59	148	155				ļ	59.15	cokato	- 1		155.70	DP		[]	
65	168	165		<u> </u>			64.94	5.79 DASSEL		DS	149.91	DP				.
A 70		66	,				70.04	5.10 DARWIN	Γ,	DN	144.81	DP				
A 78	171	262		[s 10.15	76.18	LITCHFIELD	- 1	- 1	138.67	DNP	 	s 7.50		
A 84		53			<i></i>]	83.86	GROVE CITY	1	I	130.99	DP				
£ 89	190	50			· • • • • • • • • • • • • • • • • • • •		88.99	5.13 ATWATER	Ţ	VR	125.86	DP				ļ
A 97		33		·····			96.35	KANDIYOHI	ł	KD .	118.50	DP	· • • • • • • • • • • • • • • • • • • •			
1102	Yard	1861	12.10Am		A 12.01Am L 12.05	A 10.45	102.0	5.84 WILLWAR				ORDNK	L 4.20	L 7.17		
1102	*****	56	ı I∠-IUAm		12.03	10.50	102.19 108.79	6.60 PENNOCK		- 1	112.66 106.06	PTBWZJ	A 4.15	A 7.09		ļ
1116	178	47			,		116.23	7.44 KERKHOVEN	- 1	KH	98.62	DP DP				
121		32					120.71	4.48MURDOCK	-	CK	94.14	DP				
125		52					125.27	4.56 DE GRAFF	-	-		n.~				·····
183	356	412				s 11.22	132.78	7.51 BENSON	- 1	DG BN	89.58 82.07	DP JYDNPK		s 6.35	ļ	·····
188	139	38					138.45	CLONTARF	1		76.40	P		s 0.30		ļ
149 .		125					148.67	HANCOCK	- 1	- 1	66.18	DP				
157	400	300				s 11.50	157.52		M	1R	57.33	DNYTP		s 6.05		
.166	145	41	<i>.</i>			• • • • • • • • • •	165.74	DONNELLY	П	OY	49.11	DP				
176	135	51					176.20	10.46 HERMAN		- 1	38.65	DP				
181	143	30					181.09	Norcross	1	- 1	33.76	DP		• • • • • • • • • • • • • • • • • • •		
198	150	64					192.59	11.50 TINTAH 2.80	Q	N	22.26	DP				
		· · · · · · · · · · · · · · · · · · ·		L 8.45pm.		· • • · · · · · · · ·	195.39	2.80 ABERDEEN LIME JCT	<u> </u>	• • •	19.46	PJ	·			а 8.3
200	264	108		в 8.55 .			199.81	CAMPBELL	C	в	15.04	DP				s 8.2
207 .		21		s 9.05 .			206.97	7.16 DORAN	0	D						s 8.10
214	Yard	1143		а 9.20 _{Ра А}	1.01Am	A. 1.00pm	214.85	7.88 BRECKENRIDGE *	В	R		DP RDNWB PYOKZ	L 2.04Am	i. 5.02pm		L 8.00
-									-	 -						
		1	2.10	.85 88 88	3.37 56.04	3.51 52.64		Time Over Subdivision	-	-	1		4.01	4.08		6.0
			41.54	** *6	56 04	52.64		Average Speed Per Hour	+		 -		00.40	**************************************		88.80

Westward trains are superior to eastward trains of the same class.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 7 THROUGH 12.

V	VES	TW	ARD				SEC	CONI	D SU	BDIV	ISIO	N					EAS	TWAR	D 3
ers	Caps	ar acity	SECOND	CLASS	FI	RST CL/	\SS		7	Cime 7			Uls			FI	RST CL	ASS	SECOND CLASS
Station Numbers	82	. 23	437	405	7	green green	3	nce from sul	Sen	No. : Effecti tember	ve		raph Calls	Distance from Willmar	SIGNS	8	28	4	406
Static	Sidings	Other Tracks	Daily	Daily	Daily	Daily	Daily	Distance St. Paul	<u>-</u>	STATI			Telegraph	Dista Will r		Daily	Daily	Daily	Daily
0 11		 .			ւ 8.55թո 9.30թո	ւ 5.30թտ 5.55թտ				ST. PA 10.57 MINNEAR	7	*		31.23 20.66	K K	A 7.35Am 7.05Am	A 3.20Pm 2.50Pm	1	
		TR	ins be	rween :	ST. PAUI	L AND			. ARE	GOVE	RNED	BY	TWI	N C	ITY TE	RMINAL:	S TIME	TABLE.	
	Yard		L 8.15 _{Pm}	L 1,10pm				12.17	LY	1.60 NDALE J	ET. 🖈 .) [2]	JD 1	19.06	DIJNPRX			<u> </u>	A 3.00Am
<i>,</i>		.						13.76	1	1.59 I. W. JC		∫ò	1	17.47	J				
17	87	44	8.25	1.20				17.17	RO	BBINSD.	ALE	.) 1	RB 1	14.06	DPX				2,47
24	92	72	8.35	1.30	,			23.65		, OSSEO , 9.01	<i>.</i>	. :	SI 10	07.58	DP				2.35
33	99	19	8.48	1.43				32.66		ROGERS	S		30	98.57	DP				2.20
39	93	29	9.00	1.55				38.92		6.26 BERTVII		w s	SA !	92.31	DΡ				2.07
48	79	43	9.14	2.08				47.35	M	NTICEL	LLO	മ്പ	- 1	83.88	DР				1.52
62	80	13	9.35	2.30				62.15	CL	14,80 EARWAT	ΓER	. c	w o	69.08	DP				1.20
75	Yard	1501	A 10.05Pm	A 3.00Pm				74.82	s	12.67 T. CLOU	יי. יפו] ,	x x	56.41	BDNKOR WXYZ				L 12.45Am
G63	LALU	182	A 10.05mil	A 3.00(m)	ւ 10.32թո	ь 7.00 _{Рт}	L 8.57Am	i	i	ST ST. (00.41	DNPIX	A 5.48 _{A0}	A 1.26Pn	n A 6.48pm	D TZ.47AB
""	,	10				A 7.08	A 9.05			1.54		ั้า			BDNKOR		L 1.18	L 6.40	
75	Yard	1501					L 9.08	74.82	s	T. CLOU 0.73	ານ★.	. [8] I	OX 5	56.41	WXYZ	A 5.35	A 1.15	A 6.36	
	· · · · ·		• • - • • • •		A 10.47Pm	A 7.12Pm	а 9.10 _{Ап}	75.55	F	RICE JC	T] .		55.68	IJPX	L 5.32Am	L 1.12pn	ո∟ 6.34Թո	
I-10	57	39						85.15		ROCKVI	LLE			46.08	P				
I-15	110	73						89.96	с	OLD SP	RING] (G .	41.27	DP				
I-20		42						94.45	ļ	RICHMO	סאס		RI :	36.78	DР			ļ	
I-26		35						100.66		ROSC 0	DE	2	ΩN :	30.57	DP			 	
I-31		51						106.09	P	AYNESV	ILLE	8	SY :	25.14	DIPX				
I-43	50	38		·				118.15	N	12.06 EW LON	iDON		ND :	13.08	DPX				
I-48		35						122.46		4.31 SPICE		- 1	CR	8,77	DP				
A102	Yard	'						131.23		8.77 WILLW	AR	*	w		BDNOK TRWXZ				
										· ^ G	1. 11. 1.1.	-	-	-					
			1.50 34.17	1.50 34.17	0.15 9.08	0.12 11.35	0.13 10.48		Aver	e Over Su age Speed	Per Hou	ir				0.16 8.51	0.14 9.73	9.73	2.15 27.84
W	EST	`WA	RD T	HIRD	SUBDI	VISIO	V EAS	TWA	RD	WES	STW	ARD	F	OUI	RTH S	UBDIV	ISION	EAST	WARD
			a	Time	Table N	VO 112	i e							Т	ime Ta	ble No.	118		
g	f. 40		Distance fro	*11116	Effective				GN5	11 0		g		_				Sella	
tion	Capacity	CKB	rris	Sept	ember 8,		Telegraph	· -	. w. 10 W	ž	ty of	of fr				fective ber 8, 19	64	4	SIGNS
Station Numbers	ឹ	Ä.	##		STATION	S	[편			Station Numb	Capacity Tracks	Distance from Waysata				• • •		Telegraph Call	,
A157		ij			. MORRIS.		ж. М	R R	DBNK		QE	ų v	<u> </u>		STA	ATIONS		12	
D 6	- 1	.	8.22		ALBERTA		A1	B	D D	A24			.[YZATA		WA	DPRJ
D12	1		4.27		. CHOKIO .		ко		D	В 6	97	6.60	·		SPRI	6.60 NG PARK		РК	D
D18	2	1 2	0.17		10 <u>2</u> 0890		s		D	B 8	31	8.50			M	1.90 เ ดินพืช		ми	D
D25	- 50		7.21		7.04 RACEVILL	E	GI	3 ,	DU	B13	35	13.07	<u> </u>		ST, B	4.57 ONIFACIUS	5	NI	D
D25	1		3.09		5.88 BARRY		Вз	1	D	B21	17	20,88				7,81 AYER		ку	D
D39	1	ł	0.44	, E	7.35 EARDSLE	Y	Вт	- 1	D .	B28	49	28.36	1		LESTE	7.48 R PRAIRII	E	PR	D
D45	1		7.37	BRC	6.93 DWNS VAL	LEY		ſ	DT	B44	88	44.42	1		HUT	16.06 CHINSON.		но	DY
							<u> </u>			L	<u> </u>								••

Westward trains are superior to eastward trains of the same class on the Second, Third, and Fourth Subdivisions except as follows:

Nos. 4, 8 and 28 are superior to Nos. 3, 7 and 11 between Rice Junction and St. Cloud Passenger Station.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 7 THROUGH 12.

4	WE	ESTW	ARD		FIFTH SUBDIVISION									EASTWARD			
Sers	Caj	Car pacity		SECON	D CLAS	s		Time Table No. 118	भ्			SECON	D CLASS	 S			
Station Numbers		"				419	Distance from Willmar	Effective September 8, 1964	aph Calls	SIGNS	420						
Station	Sidings	Other Treeks				Daily	Distar Willin	STATIONS	Telegraph		Daily						
A-102	J					. L 9.30Am	ļ	₩ILLMAR	. w	BDNKOR JWXZP	A 8.35Pn	1]			
I- 70	50	32			.	. 10.00	11.99	RAYMOND	. RA	DP	8.05						
I- 77	160	52			.	. 10.10	19.55	7.56 CLARA CITY 5.93	. CA	DPI	7.53			. 			
I- 83	61	38				. 10.20	25.48	MAYNARD	. MY	DP	7.43	ļ					
I- 92	97	130				10.36	34.59	GRANITE FALLS	. GX	DPI	7.27						
I-102	56	35				10.56	44.22	9.63 HANLEY FALLS	. НҮ	DPI	7.10		ļ.,.,.,.,.	·			
I-109	50	37		.		11.05	50.39	COTTONWOOD	. С	DP	7.01] 			
I-116	ļ	35		.		11.17	57.70		.]	P	6.50		 				
I-121	148	156				11.25	63.07	MARSHALL	MD	DNXPU	6.40		 				
I-134	50	38				11.50	76.01	12.94 RUSSELL	RS	DP	6.19						
I-142	.	38		.		12.02Pm	83.88	7.87 FLORENCE	F	DP	6.08	l					
I-147	100	58				12.10	88.89	RUTHTON	RV	DP	6.00			l			
I-155		37				12.21	98.73	7.84 HOLLAND	HD	DP	5.45						
I-164	30	69	<i></i>		 	12.35	105.53	PIPESTONE	NE	DPU	5.30						
I-170	120					12.45	112.27	6.74 HILEN	ļ	P	5.15						
I-175	53	108				12.52	116.88	4.61 JASPER	JA	DP	5.05						
I-183		55				1.03	124.58	7.70 SHERMAN		P	4.52						
I-186	145	220			 	1.10	127.90	GARRETSON	JC	DNKPRXY	4.45						
IA-17	100	37	<i></i>			1.40	145.23	17.33 HILLS	HS.	DPI	4.12						
IA-23	100	42	<i>,</i>	ļ		1.50	151.65	6.42 LESTER	 	ΡΙ	4.02						
IA-30	101	34				2.00	158.55		AD	DP	3,52			 			
IA-36	50	31				2.09	164.24	5.69 DOON	DO	DP	3.42						
IA-52	100	72		ļ		2.34	180.78	SIGUX CENTER	υx	DNP	3.17						
IA-66	41	29				2,54 2,54	193.96	STRUBLE		P	2.54]					
IA-78	110	51		[3.11	206.50	12,54 MERRILL 5.46	. <i>.</i>	P	2.30						
							211.96	WREN TOWER	GS	DNIP			<i></i>				
IA-85	51	30				3.21	213.32	I.36 HINTON	ні	DP BDNKOW	2.20						
IA-97	Yard					а 3.40 _{Рт}	222.77	sioux city	sx	BDNKOW RXZ	ւ 2,00թա						
			•			6.10 36.12		Time Over Subdivision Average Speed Per Hour			6.35 33.84	-					

Westward trains are superior to eastward trains of the same class. SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 7 THROUGH 12.

WE	STW	ARD				S	IXTH SUBDIVISION			EASTWARD 5				
8t18			SECONI	CLASS			Time Table No. 118	g.			SECOND CLASS			
Nump	ty of				579	ee from son	Effective September 8, 1964		SIGNS	580				
Station	Capacity Tracks		Daily Ex. Sun. QC September 8, 1964	Telegr		Daily Ex. Sun.								
I-186 I-205	220 527			1	L 12.01Am A 12.50Am	18.40	GARRETSON. ★.	JC JC	DNKPRXY UJBD KPRXY	A 4.40pm L 4.00pm				
					.49 22.53		Time Over Subdivision Average Speed Per Hour			,40 27.60				

ł								
Station Numbers	Capacity of Tracks	SECOND CLASS 325 Daily Ex. Sun.	Distance from Geneseo Jet.	Time Table No. 118 Effective September 8, 1964 STATIONS	Telegraph Calls	SIGNS	(C)	COND LASS 326 Daily z. Sun.
E45	36	L 8.35Am A 8.40Am		. ABERDEEN LINE JCT 0.68 G. N. JCT		JP	A L	8.45pm 8.42pm
				G. N. JCT. AND GEN SOO LINE R. R. TI			AR	RE
		L 10.15Am		GENESEO JCT		J	A	6.55pm
E80	28	s 10.35	0.66	0.66 GENESEO	GO	D	s	6.50
E86	34	s 10.49	5.81	CAYUGA	CU	BDJY	s	6.35
E92	85	s 11.15	11.94	RUTLAND, N. D	RJ	KRX	s	6.20
F 9	36	s 1.40	21.30	9.36 HAVANA	wB	D	s	5.35
F16	35	s 11.55	27,88	KIDDER	KS	Œ	s	5.20
			31.40	MILW. R. R. CROSSING 10.73		ש		
F30	35	s 12.25թա	42.13	AMHERST	MN	D	s	4.50
F36	34	s 12.40	48.50	CLAREMONT	QC	D	5	4.35
F47	24	s 1.05	59.83	10.83 PUTNEY, 16.95	 .		ŝ	4.08
P64	175	A 1.45Pm	76.28	ABÉRDEEN	FN	BDIKRY	L	3.30pm
		3.80 21.79		Time Over Subdivision Average Speed Per Hour			-	3.25 22.32

WESTWARD SEVENTH SUBDIVISION EASTWARD WESTWARD EIGHTH SUBDIVISION EASTWARD

Station Numbers	Capacity of Tracks	SECOMD CLASS 337 Mon., Wed. and Fri.	Distance from Rutland	Time Table No. 118 Effective September 8, 1964 STATIONS	Telegraph Calls	SIGNS	SECOND CLASS 338 Mon., Wed. and Fri.
E 92		L [[.40Am s [.10Pm	29.77 35.01	RUTLAND, N. D 29.77 C. & N. W. RY. CROSSING 5.24 GUELPH		BDJY KRX U	A 5.25Pm s 3.55
E141 E155	55 44	s 1.50 A 2.25pm	49.65 63.03	14.64 ELLENDALE 13.38 FORBES	N FO	DU DRY	s 3.15 L 2.40pm
		2.45 22.92		Time Over Subdivision Average Speed Per Hour			2,45 22.92

Westward trains are superior to eastward trains of the same class on the Sixth, Seventh and Eighth Subdivisions except No. 580 is superior to No. 579.

No. 337 and No. 338 will stop at Straubville and will stop on flag at Silver Leaf for revenue passengers.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 7 THROUGH 12.

	6 WESTWARD NINTH SUBDIVISION EASTWA								WES	STW.	ARD	TENTH SUBDIVISION I	CAS	TWARD
Station Numbers	Sidings	Other Tracks	SECOND CLASS 529 Daily Ex. Sun.	Distance from Benson	Time Table No. 118 Effective September 8, 1964 STATIONS	Telegraph Calls	SIGNS	SECOND CLASS 530 Daily Ex. Sun.	Station Numbers	Capacity of Tracks	Distance from Watertown	Time Table No. 118 Effective September 8, 1964 STATIONS	Telegraph Calls	SIGNS
C102 C109 C116 C124 C136 C141 C149	45 45 45 45 47 47	34 37 41 35 35 35 36	L 4.15Am s 4.40 s 5.00 s 6.10 s 6.35 s 6.55 s 7.25 s 7.40 s 8.00 s 8.20 s 8.40 s 9.30 s 9.55 s 10.15 s 10.35 s 11.25 s 11.25 s 12.10Pm s 12.30 A 1.00Pm	7.88 15.83 21.96 30.65 37.14 46.34 51.82 57.98 65.57 72.82 91.99 101.89 101.89 115.17 124.05 136.19 140.64 148.36 161.83	BENSON. ★. 7.88 . DANVERS. 7.95 . HOLLOWAY. 6.13 . APPLETON. . S.69 . LOUISBURG. 6.49 . BELLINGHAM. 9.20 . NASSAU. 5.48 . ALBEE. 6.16 . LA BOLT. . T.59 . STOCKHOLM. 7.25 . SOUTH SHORE. 19.17 . WATERTOWN. . GROVER. 6.35 . HAZEL 6.33 . VIENNA 8.88 . WILLOW LAKE. . BANCROFT. 4.45 . OSCEOLA 7.72 . 7.72 . 13.47 . HURON.	BN DR OW AU BG BA NA	D UD D	A 4.30Pm f 4.10 f 3.52 s 3.40 f 2.55 f 2.35 f 2.23 f 2.10 f 1.55 f 1.40 s 1.00 s 12.16 s 12.01Pm s 11.45 s 11.	C-92 WS-18 WS-23 WS-30 WS-39 WS-49 WS-55 WS-61 WS-67 WS-75 WS-82	324 32 27 29 34 26 48 28 26 42 45 RAINS 6 VEF 527	18.09 23.41 30.03 39.40 49.23 55.25 61.01 67.28 74.90 82.51 100.55 BET 102.32 103.66 104.39 121.27 129.88	WATERTOWN 18.09 MAYTI 18.09 MAYTI LAKE NORDEN 6.02 BADGER ARLINGTON 9.37 SINAI 6.02 NUNDA 5.76 RUTLAND, S. D. WENTWORTH 7.62 CHESTER 7.61 COLTON WEST JCT. (C. M. St. P. & P.) SIOUX FALLS 16.88 LENNOX 8.61 DAVIS 7.40	WN H NR B AR SN NU CH CO SU OX	D BDK UPRXYJ
			18,49	1	Average Speed Per Hour			6.30 24.89	I-238 I-245 I-260 I-267	35 34 18 172	137.28 144.66 159.68 1166.52		VB RN 	D D DRM

Westward trains are superior to eastward trains of the same class on the Ninth and Tenth Subdivisions except No. 530 is Superior to No. 529.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 7 THROUGH 12.

ALL SUBDIVISIONS

1. SPEED RESTRICTIONS GENERAL

The following speed limits apply to trains and engines operating under the conditions outlined, unless rules or conditions require a further reduction.

- 50 MPH-Diesel engines light or with caboose only.
- 35 MPH—Trains or engines on main routes, actuating the points of spring switches; trains or engines thru No. 20 turnouts at following locations: End of double track at Wayzata. Wayzata, east and west switches. End of two main tracks at MP 98 and MP 105. Crossover just west of stockyards at Willmar and east crossover switch at Benson. Delano, east and west switches. Howard Lake, east and west switches. Cokato, east and west switches. Dassel, east and west switches of control siding. Litchfield, east switch of control siding. Atwater, east and west switches. Kerkhoven, east and west switches Benson, east switch of control siding. Morris, east and west switches. Donnelly, east and west switches. Herman, east and west switches. Norcross, east and west switches. Campbell, west switch. M.P. 212, east switch of control siding. Robbinsdale, east and west switches. Sioux City, east switch 26th street yard.
- 30 MPH—On Main lines, when handling following equipment in trains, not in actual service but on own wheels, derricks, cranes, pile drivers, Jordan spreaders, shovels, wedge plows, scale test car, also ore cars series 80000 thru 94250 and air dump cars X-2000 thru X-2096, X-7000 thru X-7049 when such cars are loaded with ore or gravel.
- 25 MPH—Trains handling logs; trains or engines moving in facing point direction at spring switches without facing point lock; trains or engines thru No. 15 turnouts at following locations:
 Clontarf, west switch of control siding.
- 20 MPH—Trains handling the following equipment on Branch Lines or on 6 degree or sharper curves of Main Lines, scale test car, ore cars series 80000 thru 94250, air dump cars X-2000 thru X-2096, X-7000 thru X-7049 when such cars are loaded with ore or gravel.
- 15 MPH—Trains handling the following equipment on Branch
 Lines or on 6 degree or shaper curves of Main Lines,
 derricks, cranes, pile drivers, Jordan spreaders,
 shovels and wedge plows.

 Trains or engines moving thru interlockings against
 the current of traffic on double track; trains or
 engines thru all other turnouts, except equilateral
 turnouts, and those shown previously in this item.
- 1(a). Rule 240 W of the Consolidated Code of Operating Rules is modified to permit handling Great Northern cars 60276 through 60279, 61000 through 61009 and 61500 through 61524 in passenger trains at passenger train speeds.
- 2. MOVEMENT OF ENGINES DEAD IN TRAINS. Engine 2350 must be handled on rear of freight and mixed trains. Diesel engines 1 thru 196 or any road switcher unit not equipped with alignment control couplers must be towed as single units. On engines 550 thru 599, coupler alignment control lock blocks must be "DOWN" when coupled in multiple unit operation.

Following road switchers are equipped with alignment control couplers:

200 through 218 220 " 280 550 " 599 (lock blocks) 600 " 699 700 " 734 900 " 915 2000 " 2035

Single unit diesel engines, or multiple unit groups (when such groups consist of road freight, road passenger, or engines with alignment control couplers), when towed dead in freight trains, are to be handled not less than five (5) cars nor more than fifteen (15) cars behind the road engine. There should not be more than five (5) units in a group. Additional such units or groups of units must be separated by not less than five (5) cars. When towing diesel engines dead in trains the following speeds must not be exceeded:

MAXI	MUM SPEED	ENGINE NUMBER							
50 M	PH1 tl	nru 10, 14 tb	ru 16, 24 thru 28,						
	7 5	thru 162, 165	thru 170.						
79 M	PH350	thru 375, 5	500 thru 512, 679,						
		, 2350.							
SS MI	PET All	other diesel	engine units.						

3. Except at points where it is necessary to classify trains, open cars loaded with poles, piling, lumber, timber, pipe, or other lading which might shift, should be placed as close as possible to the head end of trains, but not next to engine, caboose, occupied outfit car, passenger car or another unprotected car containing commodities which might be subject to damage. Loaded trailer-on-flat cars and multi-level automobile cars are not included in this category. In double track territory, trains handling such cars must use extreme care to avoid slack running in or out when passing or being passed by other trains. In single track territory, trains handling such cars must be at stop when on siding or other track to meet or be passed by other trains, except when they have more cars than siding will hold, it is permissible for such trains to pull by each other at restricted speed. Loaded dump cars should not be handled on double track after dark, but if necessary to do so, close watch must be maintained by members of the crew, and if a car dumps its load, train must be stopped at once and protection provided as prescribed by the rules.

Great Northern tie flats in series X-4800 to X-4975 and X-4410, whether loaded or empty, must be handled on rear of train.

- Brakemen with less than one year of experience should not be used as flagman except in emergency, and then Superintendent will be notified by wire.
- 5. Due to limited overhead clearance at tunnels and structures, employees are warned to keep off top of cars of extreme height and width when handled in trains and yards, except in emergency. In absence of previous advice on such cars, wire proper officer for instructions.
- 6. Trains, departing from stations, either from siding or main track in trailing point movement actuating points of spring switches, a member of crew must observe indication of governing signal in opposite direction after rear end of train has passed through switch to ascertain if switch points return to normal position. If this signal indicates Stop and no immediate train movement or other cause is evident report the fact to Superintendent from first available point of communication.

During and immediately following snow storms or violent wind storms, spring switches must be operated by hand and relined to normal position before heading out through switch in trailing point movement, actuating switch points, to insure switch is in proper operating condition.

7. Facing point locks on hand operated switches are indicated by a six inch yellow stripe painted on target staff. Be positive locking device is restored to normal position after using. A running switch must not be made through this type switch.

- Rule 2 of the Consolidated Code of Operating Rules is modified for Great Northern Railway Company employes to the extent that a watch certificate form is no longer required. Watches of employes will be inspected by Division Officers, Rules Examiners and other designated officers.
 - Rule 3 (C) of the Consolidated Code of Operating Rules is amended as follows: Employes governed by time service rules must not wear wrist watches while on duty unless such watches are of an approved type. Approved type wrist watches are: Elgin, B. W. Raymond model, 13/0 size, 23 jewels. Ball Official Standard, 1604 B, stainless steel, 13/0 ligne, 21 jewels, Bulova Accutron Railroad Approved Model and Hamilton 505 R. R. Electric Special. Electric Special.
- Regarding Consolidated Code Rule 103. In addition to complying with the provisions of this rule, members of a crew will be governed by the following: When an engine, with or without cars, is about to move over a public crossing not protected by a watchman, by gates or by crossing signals in operation, a member of the crew must be on the ground at the crossing to provide protection. Exception—In the provider of a through ward transfer or of a light engine being movement of a through yard transfer or of a light engine being handled only by hostlers, it is not necessary for a member of the crew to be on the ground at the crossing.
- Employes are prohibited from riding or walking on the roof of any moving car, except when absolutely necessary in the passing of signals, and then only when they place themselves near the middle of the car.
- Supplementing Rule 7(A) and 12 of The Consolidated Code of Operating Rules. When movement being made is controlled by hand, flag or lantern signals, the employees involved will give or relay such signals directly to the engineer.
 - The last paragraph of Rule 7(A) of The Consolidated Code of Operating Rules is revised as follows: When backing or pushing a train, engine or cars in response to hand or light signals from a trainman, the disappearance from view of the trainman giving such signals or of his light by which such signals are given, must be recorded as a ston signal excent when movement is under be regarded as a stop signal, except when movement is under control of a trainman on the leading car that is equipped with back-up air brake or hose or pipe.
- St. Paul Union Depot and Minneapolis, in order to facilitate the handling of patients arriving on cots in baggage cars and who require use of wheel chair or stretcher, conductors will wire Union Depot Company, St. Paul, or Stationmaster, Minneapolis, describing the class of service required.
- "The Consolidated Code of Operating Rules, Edition of 1959, in addition to the following instructions will govern Great Northern employees while operating on Minnesota Transfer Railway Co. and St. Paul Union Depot Company trackage:

 (a) All trackage of the Minnesota Transfer Railway Company is defined as a system of tracks within yard limits over which movements must be made at restricted speed and are not authorized by timetable, or train order, but subject to prescribed signals and rules or special instructions.

 The limits of The St. Paul Union Depot Company preparts are
 - The limits of The St. Paul Union Depot Company property extend from connection with the Northern Pacific Ry. and Great Northern Ry. tracks at Third Street and connection with CMStP&P-CB&Q R. R. tracks opposite depot roundhouse, on the east, to connection with the CGW Ry. and the CMStP&P R. R. tracks at Robert Street on the west.
 - (b) The timetable of the St. Paul Union Depot Company is for information only. Employes of railroads using the tracks of this Company will be governed by current timetable of their respective Companies only as to arriving and departing time of trains.
 - (e) Where in the rules of the Consolidated Code reference is made to trains, such rules will also apply to yard movements
 - (d) Under Rule 15, the use of torpedoes is prohibited.
 - (e) Under Rule 11, burning fusees must not be used except in case of emergency and then only when held in hand and must be extinguished before leaving.

THE FOLLOWING RULES APPLY ONLY ON THE ST. PAUL UNION DEPOT COMPANY PROPERTY:

- (f) There is no superiority of trains within the limits of St. Paul Union Depot Company property.
- (g) Within the limits of the St. Paul Union Depot Company (g) Within the limits of the St. Paul Union Depot Company property trains and engines must move at restricted speed and must not exceed ten (10) miles per hour through crossovers, turnouts and puzzle switches. The entrance to and all movements on this property will be made only on authority of hand signals from switchtenders. No train or engine may foul any track or puzzle switch without authority of hand signals from switchtenders in central of such mayments, except that short switchtenders in control of such movements, except that short interior switching movements may be made through crossovers connecting shed tracks when authorized by train director. Any lead or track may be used for the make-up of trains on authority of train director. The movement of trains should be given preference.
- (h) When indicated by the ringing of the bell, flashing of head-light, hand or light signal that a train or engine is ready to move, the switchtender in charge of the shed track on which the move-ment is standing will handle as follows: at west end of station the switchtender will control the movement by hand or light signal; at the east end of station the switchtender will inform the train director, who will route the movement by instructors the train director, who will route the movement by instructions over the public address system. Switchtenders will be governed by these instructions, relaying such instructions by hand or light signal to the next switchtender in the direction of the movement, each must receive an acknowledgment before signaling the movement. Signals must not be acknowledged or acted upon unless the signal corresponds with instructions from the train director and is definitely understood.
- (i) When backing, the back-up air brake valve on passenger trains must be operated by the conductor, except in the movement of empty equipment, it may be operated by a competent trainman or yardman. When practicable, conductor must see that trainmen are stationed so hand or light signals may be used, in case of any emergency. When backing a train, the engine brake valve must be in running position; an application of the brakes must be made with back-up air brake valve before starting and it must be known that brakes are in operative condition. Movement must not be started until the proper signal is given. A running test must be made with the back-up air brake valve before the train has moved 300 feet; if the running test is not made within 300 feet the engineer must stop the train and asmade within 300 feet the engineer must stop the train and ascertain cause. The speed of train must not exceed eight (8) miles per hour and train must be under such control that it can be stopped short of train, or obstruction, and short of bumping post on stub tracks.
- (j) Headlights must be dimmed while on shed tracks.

FIRST SUBDIVISION

(Main Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

2. TRAIN REGISTER EXCEPTIONS.
Willmar, register is for freight trains only.

CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).
 All trains must obtain Clearance Form A at Willmar.

At Lyndale Jct., trains for which this point is initial station may proceed on authority of clearance under which such trains arrive, when train order signal indicates proceed.

Westward Seventh Subdivision trains will require Soo Line R.R. clearance at Campbell.

4. CONDITIONAL STOPS.

No. 27 stops at Wayzata to discharge passengers from Chicago and east and to pick up passengers destined Fargo and west where No. 27 is scheduled to stop.

No. 14 stops at Wayzata to discharge passengers from Fargo and west and to pick up passengers destined Chicago and east.

- Lyndale Jct., eastward freight trains on Willmar Line having cars to set out at this point will stop before passing eastward Home Signal to make setout.
- 6. All movements on house track over State Aid road No. 11 just west of depot Campbell, all movements on industry track over 4th Street Crossing Donnelly and 4th Street Crossing Waverly must be protected by flagman.

At Wayzata, when switching over Barry Avenue Crossing, or when standing on either main track, and a train is approaching on adjacent track, a member of the crew standing at the station will protect the crossing on the ground.

7. SPEED TEST BOARDS.

Engineers shall test speed of their trains passing following points as compared with Speed Table:

Westward trains, between MP 18.75 and MP 19.75 five miles east of Wayzata.

Eastward trains, between MP 87 and MP 86 two miles west of Grove City.

Westward trains between MP 110 and MP 111 one mile west of Pennock.

Eastward trains between MP 205 and MP 204 two miles east of Doran.

8. CROSSOVERS ON DOUBLE TRACK AND TWO MAIN TRACKS.

Facing Point

Trailing Point

Mile Post 15 400 feet west of.
Mile Post 19 700 feet west of.

Willmar, double crossover just west of stockyard.

- Consolidated Code Rules 251, 251 (A), 253 and 254 are in effect on the double track between Lyndale Jct, and beginning of CTC at end of double track Wayzata. The use of these rules does not modify Rule 99.
- INSTRUCTIONS GOVERNING OPERATION OF TRAIN AND ENGINES WITHIN CENTRALIZED TRAFFIC CONTROL SYSTEM.

Two main tracks known as—NORTH MAIN and SOUTH MAIN—extends between the following points:

MP 98 and MP 105.

Willmar is the control station for CTC under the supervision of train dispatcher.

THE FOLLOWING SIGNALS ARE LOCATED TO THE LEFT OF THE TRACK WHICH THEY GOVERN: Eastward on North Main Track:

Signal 99.4.

Westward on South Main Track: Signal 99.5.

Benson:

Double crossover at MP 132 for westward movements from Main Track to controlled siding—and for eastward movements from controlled siding to Main Track.

Morris

Eastward governing home signal on siding at east end of siding.

11. MANUAL INTERLOCKINGS.

12. AUTOMATIC INTERLOCKINGS.

Soo Line R.R. crossing ______2.17 miles west of Tintah

Diesel radiator and boiler water stations.
 Willmar.

Morris.

14. At Wayzata, when the route is properly lined for a westward train to proceed from the westward main track to single main track, the signal aspect displayed on the westward approach signal will be yellow over green. (See C. M. St. P. & P. Rule 240-E, Figure 1, page 104 in the Consolidated Code of Operating Rules). The indication of this signal means "Approach next signal prepared to proceed on diverging route".

At Wayzata, when a green under red aspect is displayed on the dwarf signal for a movement from siding to eastward main track, Rule 240K Figure 1 will apply.

- 15. At Litchfield, when a green under red aspect is displayed on the dwarf signal for a movement from siding to main track, Rule 240K Figure 1 will apply.
- 16. At Mile Post 98 east of Willmar, when the route is properly lined for a westward train to proceed from single track to South Main track, the signal aspect displayed on the westward approach signal will be yellow over green.

At stockyards crossover east of Willmar, when the route is properly lined for a westward train to proceed from North Main track to South Main track, the signal aspect displayed on the westward approach signal will be yellow over green.

At Mile Post 105 west of Willmar, when the route is properly lined for an eastward train to proceed from single track to the South Main track, the signal aspect displayed on the eastward approach signal will be yellow over green.

(See C. M. St. P. & P. Rule 240-E, Figure 1, page 104 in the Consolidated Code of Operating Rules). The indication of this signal means "Approach next signal prepared to proceed on diverging route".

17. At Sioux City Line Jct. just west of Willmar, when a green under red aspect is displayed on the dwarf signal for a movement from South Main Track to North Main Track, Rule 240K Figure 1 will apply.

SECOND SUBDIVISION

(Osseo Line)

1.	MAXIMUM	PERMISSIBLE	SPEED	FOR	TRAINS.
----	---------	-------------	-------	-----	---------

Between	Freight
Lyndale Junction and St. Cloud	50 MPH
St. Cloud and Willmar	40 MPH

2. SPEED RESTRICTIONS.

Between Home Signals of Interlockings at: 20 MPH

Paynesville.

3. TRAIN REGISTER EXCEPTIONS.

Lyndale Jct., all trains register by ticket.

St. Cloud, First Class Trains will register by ticket.

4. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

At Lyndale Jct., trains for which this point is initial station may proceed on authority of clearance under which such trains arrive when train order signal indicates proceed.

All trains must obtain Clearance Form A at St. Cloud.

Trains originating at East St. Cloud may proceed without a clearance.

Trains originating at Rice Jct. may proceed without a clearance. At M. W. Jct., eastward M. W. trains will not require a clearance.

5. All movements on industry track over Noble Avenue Crossing, 1000 feet east of depot Robbinsdale, must be protected by

All movements on the North Maiers Transfer & Storage track St. Cloud must be protected by flagman when crossing 25th Avenue.

Track north of main track extending approximately 2 miles eastward from depot, St. Cloud, is known as LONG LEAD and must be kept clear for meeting and passing of trains.

7. SPRING SWITCHES WITH FACING POINT LOCK.

Robbinsdale, east and west siding switch.

Osseo, east and west siding switch.

Rogers, east and west siding switch.

Albertville, east and west siding switch.

Monticello, east and west siding switch. Clearwater, east and west siding switch.

Normal position is for main track.

8. AUTOMATIC INTERLOCKINGS.

Soo Line RR. crossing1.34 miles west of Robbinsdale Soo Line RR. crossing0.76 miles west of Paynesville

MANUAL INTERLOCKING WITH DUAL CONTROL SWITCHES.

Rice Jct.

This gritch is electrically controlled by operator at St.

10. Diesel radiator and boiler water stations.

Monticello.

St. Cloud.

THIRD, FOURTH, FIFTH AND SIXTH SUBDIVISIONS

(Browns Valley, Hutchinson, Sioux City and Sioux Falls Lines)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Freight
Morris and Browns Valley	35 MPH
Wayzata and Hutchinson	25 MPH
Willmar and Sioux City	49 MPH
Garretson and Sioux Falls	

2. SPEED RESTRICTIONS.

Between Home Signals of Interlockings at: 20 MPH Clara City.

Hanley Falls.

C.&N.W. Ry. Crossing 6.68 miles east of Hills. Hills.

Wren Tower.

CMStP&P. RR. crossing 1.13 miles west of Sioux City. Sioux Falls

Garretson, within city limits..... I. C. RR. Crossing, 2.89 miles east of Sioux City.......... 10 MPH

3. TRAIN REGISTER EXCEPTIONS.

Garretson, Register only for trains originating and terminating.

- 4. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B). All trains must obtain Clearance Form A at Garretson.
- 5. Pipestone, trains and engines using CRI&P main track between G.N. interchange track switch and east end of CRI&P siding, must move at restricted speed, and must be governed by current operating rules and time table of CRI&P Ry.

6. AUTOMATIC INTERLOCKINGS.

CMStP&P. RR. crossing ______1.44 miles east of Granite Falls C&NW. Ry. crossing0.32 miles east of Hanley Falls C&NW. Ry. crossing ______6.68 miles east of Hills I.C. RR. crossing0.38 miles west of Hills CRI&P. Ry. crossing _______0.22 miles west of Lester CMStP&P. RR, crossing ______1.13 miles west of Sioux City C&NW. Ry. crossing ______3.96 miles east of Sioux Falls

Granite Falls, push button controls are located on east end of Grante Fails, push button controls are located on east end of depot, at crossover switches, at east siding switch, and on east-ward home signal. Trains and engines occupying main track at depot or lining east siding switch or crossover switches, for movements out of siding automatically set up route for eastward movement through interlocking at CMStP&P crossing, provided no conflicting movement on CMStP&P track, and will hold this set up for a period of approximately four minutes, after which is not ward substantial substantial controls and the provided to the confliction of t if route is not used, automatic interlocking control can be taken away by CMStP&P trains or engines approaching crossing. If an eastward train occupies main track at depot for meeting trains or station work for a period in excess of four minutes, trainman must operate push button at depot or at crossover switches to obtain interlocking route. If an eastward train occupies main track between eastward approach and home signals for a period in excess of four minutes, trainman must operate push button at east siding switch or on home signal to obtain interlocking route. Push button boxes must be kept closed and locked except when

CMStD&P DR. crossing west of Sioux City is under supervisory control of CMStP&P Operator West Yard.

7. MANUAL INTERLOCKING.

I.C. RR. crossingWren Tower

8. SEMI-AUTOMATIC INTERLOCKINGS.

M.W. Ry. crossing 0.46 miles east of Clara City

If a train is stopped by a Stop-indication and no immediate conflicting train movement is evident, and both smash boards are in reverse position, trainman may signal train to proceed over the crossing after making certain that gates are set against conflicting route. If smash boards are not in reverse position, trainman shall operate them by hand with crank attached to mechanism.

9. RAILROAD CROSSINGS PROTECTED BY GATES.

10. SPEED TEST BOARDS.

Engineers shall test speed of their trains passing following points as compared with Speed Table:

Westward trains, between MP 7 and MP 8 between Priam and Raymond.

Eastward trains, between MP 121 and MP 122 between Jasper and Sherman.

Westward trains, between MP 134 and MP 135 between Garretson and C.&N.W. Ry. crossing.

Eastward trains, between MP 208 and MP 209 between Merrill and Wren Tower.

11. Diesel radiator and boiler water stations.

Garretson.

Marshall.

12. Unless otherwise instructed, protection against following trains, as required by Consolidated Code Rule 99, is not necessary between stations on the Third and Fourth Subdivisions and Form Z train order is not required between the above stations. If it becomes necessary to operate a following train when there is still a train between the above stations, the train ahead must be notified to protect against the following train. If this is not practical, the following train must be notified to protect against the train ahead.

SEVENTH, EIGHTH, NINTH AND TENTH SUBDIVISIONS

(Aberdeen, Forbes, Huron and Watertown-Yankton Lines)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Freight
Genesec Jct. and Aberdeen	
Rutland and Forbes	25 MPH
Benson and Huron	35 MPH
Watertown and Yankton	25 MPH

2. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

At Aberdeen Line Jct., trains for which this point is initial station may proceed on authority of clearance under which such trains arrive.

All trains must obtain Clearance Form A at Sioux Falis.
Westward Seventh Subdivision trains will require Soc Line RR.
clearance at Cambbell.

Eastward Seventh Subdivision trains will require Soo Line RR. clearance at Aberdeen.

3. SPEED RESTRICTIONS.

Davis.

Between Home S	ignals of	Interlockings	at:	Z0 MPH
Aberdeen.				
Appleton.				
Huron.				
Arlington.				
Lennox.				

Watertown, within city limits		
Arlington, within city limits		
Sioux Falls, within city limits		
approaching 6th & 8th street crossings	6 MPH	
Yankton CMStP&P, RR crossing	10 MPH	

4. AUTOMATIC INTERLOCKINGS.

C&NW. Ry. crossing	0.62 miles east of Aberdeen
	0.64 miles east of Aberdeen
CMStP&P. RR. crossing	0.77 miles west of Appleton
C&NW. Ry. crossing	0.64 miles east of Huron
C&NW. Ry. crossing	0.97 miles west of Arlington
CMStP&P, RR, crossing	0.21 miles west of Lennox
C&NW, Ry, crossing	3.54 miles west of Davis

5. RAILROAD CROSSINGS PROTECTED BY GATES.

CMStP&P. RR. crossing _______0.88 miles east of Yankton Normal position is clear for Great Northern.

6. Unless otherwise instructed, protection against following trains, as required by Consolidated Code Rule 99, is not necessary between Geneseo Jct. and Aberdeen on the Seventh Subdivision; between stations on the Eighth and Ninth Subdivisions; between Watertown and West Jct. and between Sioux Falls and Yankton on the Tenth Subdivision and Form Z train order is not required between the above stations. If it becomes necessary to operate a following train when there is still a train between the above stations, the train ahead must be notified to protect against the following train. If this is not practical, the following train must be notified to protect against the train ahead.

SDEED	TABLE		BUSINESS TRACKS			
Time Per Mile Miles Min. Sec. Per Hour	Time Per Mile	Miles Per Hour	Name	LOCATION	Capac- ity Cars	Switch Opens
46 78.3 47 76.6 48 75.0 49 73.5	1 18 1 20 1 22 1 24	46.2 45.0 43.9 42.9	First Subdivision Montrose Charlesville	6.70 miles west of Delano 6.47 miles west of Norcross	23 24	E&W E&W
50 72.0 51 70.6 52 69.2 58 67.9	1 24 1 26 1 28 1 30 1 83	41.9 40.9 40.0 38.7	Crystal Lumber Co. Spur	3.50 miles east of St. Cloud 1.56 miles west of Robbinsdale 2.00 miles east of Osseo	288 3 11	East West East
54 66.7 55 65.5 56 64.3 57 68.2	1 36 1 39 1 42 1 45	37.5 36.4 35.8 34.8	Oscar Roberts Co. Inc. North Star Concrete Co. Spur St. Cloud Rendering Co. Spur	1.57 miles east of Osseo	8 19 6	West West East
58 62.1 59 61.0 1 0 60.0 1 1 59.0	1 50 1 55 2 — 2 10	32.7 31.3 30.0 27.7	Empire Quarry Spur North Star Granite Corp. Spur Cold Spring Granite Spur Hawick	2.47 miles west of Rice Jct	141 41 7 40	East West East E & W
1 0 50.0 1 1 59.0 1 2 58.1 1 3 57.1 1 4 56.3 1 5 55.4 1 7 58.7 1 8 52.9 1 9 52.2 1 10 51.4 1 12 50.0 1 14 48.6	2 20 2 80 2 40 8 —	25.7 24.0 22.5 20.0	Gravgaard Spur New London Materials and Construction Co. New London Gravel Pit	7.29 miles west of Paynesville 8.46 miles west of Paynesville 1.73 miles east of New London	7 34 250	E & W E & W E & W
1 6 54.5 1 7 53.7 1 8 52.9 1 9 52.2 1 10 51.4	8 80 5 <u>—</u> 6 —	17.1 15.0 12.0 10.0 8.6	Fourth Subdivision Cox Bres. Spur	1.25 miles east of New London 0.53 miles west of Spring Park 4.18 miles west of St. Bonifacius	6 2 13	East West West
1 12 50.0 1 14 48.6 1 16 47.4	8 — 9 —	7.5 6.7 6.0	New Germany Silver Lake	3.80 miles west of Mayer	26 23	E & W West
			Asbury	5.97 miles west of Willmar 3.73 miles west of Maynard 0.58 mile west of Marshall	18 35 6	West E & W East
			Appleton Silo Company Spur.	1.00 mile west of Marshall 6.69 miles west of Marshall 8.96 miles west of Doon 8.04 miles west of Sioux Center	6 17 19 2	East West E & W East
			Pathfinder Spur	8.26 miles west of Garretson 12.38 miles west of Garretson	37 27	E & W West
			Crampton Spur Seventh Subdivision	13.76 miles west of Garretson 15.24 miles west of Garretson 5.70 miles east of Geneseo Jct	45 22 88	E & W West
			Hankinson Huffton Eighth Subdivision	17.90 miles east of Geneseo Jct. 5.36 miles west of Claremont	85 21	E & W E & W
			Straubville Silver Leaf	18.64 miles west of Forbes Line Jct. 7.09 miles west of Guelph	84 7	E & W West
		2	Nizth Subdivision Rauville Tenth Subdivision	13.26 miles west of South Shore		E & W
	÷		Foley	4.24 miles west of Watertown 5.82 miles west of Colton 11.41 miles west of Colton 10.92 miles west of Sioux Falls	9 15 14 23	E&W E&W E&W E&W
en er i i som en			Naomi Spur Volin	2.50 miles west of Lennox 9.18 miles west of Irene	22	East E & W