L PAUL, MIR MPTROLLER"

VICE PRESIDE GREAT NORTHERN RAILWAY COMPANY

KALISPELL DIVISION

TIME TABLE 110

EFFECTIVE 12:01 A. M. MOUNTAIN STANDARD TIME AND

PACIFIC STANDARD TIME

Sunday, November 27, 1966

MOUNTAIN STANDARD TIME GOVERNS FIRST, AND THIRD SUBDIVISIONS.

PACIFIC STANDARD TIME GOVERNS SECOND, FOURTH, FIFTH, SIXTH, SEVENTH, EIGHTH AND NINTH SUBDIVISIONS.

P. F. CRUIKSHANK, Superintendent.

C. M. RASMUSSEN, General Manager.

H. J. SURLES General Superintendent Transportation. Printed in U.S.A.

COMPANY SURGEONS

*Dr. Abbott Skinner, Chief Medica	l OfficerSt. Paul
*Dr. Hugo F. Schroeckenstein, Assi Chief Medical Officer	t. to St. Paul
Dr. David A. Burlingame, Roentgenologist	St. Paul
*Dr. R. K. West	
Dr. James R. Markette	Cut Bank, Montana
Dr. T. B. Moore	Kalispell, Montana
Dr. W. F. Bennett	
*Dr. J. W. Whalen	Whitefish, Montana
*Dr. Bruce C. McIntyre	Whitefish, Montana
*Dr. Jerrold E. Johnson	Whitefish, Montana
Dr. Robert D. MacKenzie	Libby, Montana
Dr. William T. Matthews	Libby, Montana
*Dr. Clifford J. Edwards	
Dr. Franz H. Siemsen	
Dr. R. B. Morrow	
*Dr. E. B. Coulter	Spokane, Wash.
Dr. Robert J. Albi	Hillyard, Wash.
Dr. Roy S. Lowell	
*Dr. John C. Carpenter	

OPHTHALMOLOGIST

Dr. H.	D.	Hu	gins	Kalispell, M	ontana
Dr. Ph	ilin	R.	Greene	Spokane.	Wash.

- D. E. PARKS, Asst. Superintendent.
- D. H. CARPENTER, Chief Dispatcher.
- R. J. SEELEY, Master Mechanic.
- D. S. NELSON, Trainmaster.
- A. R. McKEEN, Trainmaster.
- P. A. FREUEN, Trainmaster.
- J. M. ANDERSON, Trainmaster.
- P. A. JEROME, Traveling Engineer.
- J. L. GARRITY, Traveling Engineer.
- G. T. LITTON, Traveling Engineer.

*Designates also Examining Surgeon.

(Eye Doctors)

2	WE	STW	ARD		•		FIRST SUBDI	/ISI	ON				F	CASTW	ARD
Ę		ar acity	FII	RST CL	ASS		MOUNTAIN STANDARD TIME				FIRST	CLASS	SEC	OND CL	ASS
Station Numbers			2	31	27	Distance from Cut Bank	Time Table No. 110	raph Calls	Distance from Troy	SIGNS	32	28	494	490	492
Statio	Siding	Other Tracks	11 es 70	Daily	Daily	Dista Cut I	November 27, 1966 STATIONS	Telegraph	Dista		Daily	Daily	Daily	Daily	Daily
01475	130	340		L 315 _{Pm}	L 5.45Am	0.00	# (cut BANK★.)	CI	260.34	BDNIK PRXW	A 9.15Am	A 5.30Pm	A 2.35Pm	A 1.30Am	а 7.45 _{/un}
01484	100	30		3.25	5.55	9.60	SUNDANCE		. 250.74	P	9.02	5.20	2,20	1.17	7.30
01501	112	272		3.42	6.12	26.24	6 (BLACKFOOT)	4	CONTRACT CONTRACT	DPY	8.42	5.02	1.55	12.47	7.05
01508	114	183		3.53 4.06	s 6.27	33.53	BROWNING★.)	BG	0.0000000000000000000000000000000000000	DNP	8.34 8.24	s 4.52 4.36	1.40 1.25	12.32	6.55 6. 39
01517	180	32		4.06	6.39	41.82	5.05		. 218.52	P	8.24	4.30	1.25	12.15	6.39
01522	93	62		4.14	£ 6.48	46.87	GLACIER PARK	МП	213.47	DNPYW	8.18	f 4.29	1.15	12.01Am	6.12
01527	186 E144			4.22	6.56	51.94	BISON		. 208.40	P	8.09	4.22	12.58	11.48	6.01
01534	W123	81		4.33	7.06	58.44	SUMMIT★ .	8M		DNPIYXW	7.59	4.04	12.45	11 33	5.45
01540	E 58	9		4.46	7.18	65.48	BLACKTAIL	••••	. 194.86	P	7.41	3.47	12.25Pm	11.18	5.20
01548	E 128	36		5.04	7.34	72.75	NIMROD		. 187.59	IP KDNP	7.23	3.30	11.55	10.48	4.55
01552		93		5.11	t 7.44	76.65	ESSEX★.	sx	183.69	ÖYXW	7.17	r 3.23	11.45	10.35	4.45
01558				5.20	7.51	82,30	PINNACLE		. 178.04	IP	7.07	3.13	11.30	10.05	4:3
01568	W 95	14		5.36	8.07	92.50	10.62		. 167.84	IYP	6.50	2.56	11.10	9.25	4.
01578	151	91		5.52	r 8.25	103.12	BELTON ★.	BE	157.22	DNPW	6.34	1 2.40	10.50	9.05	3.50
01586	62	63		6.01	r 8.36	110.99	7.87 coram 4.38	СМ	149.35	DP	6.23	1 2.27	10.30	8.45	3.35
01590		122		6.08	8.43	115.37	Z.85		. 144.97	PI	6.16	2.18	10.20	8.37	3.25
01593	79	240		6.11	s 8.52	118.22	COLUMBIA FALLS.	CF	142.12	DNJYXPW	6.13	s 2.15	10.15	8.30	3.18
01601	Yard	1733		A 6.20 L 6.25	A 9.00 L 9.10	125.85	ă (₩HITEFISH★.	WF	134.49	KRDNWP BOXZI	L 6.05 A 6.00	L 2.00 A 1.45			L 3.01 A 1.40
01607	147			6.32	9.16	131.24	5.39 VISTA		. 129.10	P	5.47	1.39	8.40	5.55	1.25
01613	188	14		6.40	9.23	137.66	LUPFER		. 122.68	P	5.39	1.32	8.30	5.45	1.15
01618	72	26		6.47	1 9.32	143.12	OLNEY		. 117.22	P	5.31	1 1.25	8.20	5.35	1.05
01624	138 W104	17		6.54	9.39	148.69	RADNOR		. 111.45	P	5.23	1.15	8.10	5.20	12.55
01631	E 112	17	•••••	7.03	1 9.48	155.96	STRYKER★.	SY	104.38	DNPYW	5.14	f 1.07	7.55	5.08	12.40
01687	135	14		7.10	e 9.55	161.96	TŘĚGO	1	. 98.38	P	5.07	1 12.58	7.45	4.54	12.25
01642	130	39		7.16	£ 10.05	166.55	FORTINE	FR	93.79	DPW		1 12.51	7.32	4.45	12.10Am
01648	127	76		7.22	10.11	172.47	TOBACCO			PI	4.54	12.41	7.20	4.37	11.50
01654	149 W130	68		7.29 7.39	10.23	178.23	EUREKA	KA		DNPW	4.47 4.38	s 12.34	7.05	4.30	IL
01662	E 168	167		1.39	t 10.35	187.11	REXFORD★.	RE	73.23	DPYW	4.38	1 12.19	6.45	4.15	11.20
01673	126	23		7.51	10.47	197.99	STONEHILL		. 62.35	P	4.26	12.07pm		3.57	11.05
01684	136	4		8.04	10.59	209.06	URAL		. 51.28	P	4.13	11.54	6.05	3.20	10.50
01689	126	4		8.09	11.04	214.01	VOLCOUR★.	VR		DNPW	4.07	11.48	5.55	3.00	10.42
01697	137	•••••		8.18	11.12	221.82	13.10 RIPLEY		38.52	P	3.59	11.40	5.40	2.50	10.30
01710	150	3		8.33	11.26	234.92	7.24		. 25.42	P	3.45	11,26	5.20	2.35	10.12
01718	254	248		8.42	s 11.40	242.16		CK	18.18	DNPZW	3.37	11.12	5.05	2.10	10.00
01729	166			8.54	11.52	253.18	KOOTENAI FALLS			P KRDNP	3.24	10.50	4.45	1.45	9.45
01786	279	451		▲ 9.05 _{Pm}	A 12.01Pm	260.34	★.)	UX	0.00	BXIYW	L 3.15Am	L 10.43Am	L 4.30 _{Am}	L 1.30 _{Pm}	ւ 9.30թո
		65.0 200 87.1		5.50 44.62	6.16 41.54	. ⁵	Time Over Subdivision Average Speed Per Hour			,s=	6.00 4 3.38	6.47 38.37	10,05 25.81	12.05 21.55	10.15 25.39
			ليستنا		Wash		rains are superior to eastwi	<u> </u>	raine of	the same	<u>-</u>				

Westward trains are superior to eastward trains of the same class.
SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 6 THROUGH 12.
See page 9 for CONDITIONAL STOPS

W	ÆS	TW	ARD					S	ECOND SU	BDIV	/ISI	ON				F	CASTV	WARD	3
au o		ar		FIR	ST CL	ASS			Time Ta No. 11		la la				FIRST	CLASS		SECOND	CLASS
Station Number	Sidings	Other	1 S. P. & S. No. 1 Daily	31	45 S. P. & S. No. 3	5 TOFC	27	Distance from Troy	Effective November 27, PACIFIC STAN TIME	1966 DARD	Telegraph Calls	Distance from Fort Wright	SIGNS	46 S. P. & S. No. 4	28	2 S. P. & S. No. 2 Daily	32	490	492
						Ex. Sat.			STATIO	,			RDNPBK						
01736	279	451		L 8.05Pm			LII.08Am	0.00	TROY	★.	UX	142.08	XIYW		A 9.37Am		A 2.15Am	A10.00Am	A 8.00Pm
01742	140	20		8.15 8.26			11.16	18,49	6.80 LEONIA			135.39	P		9.27		2.02 1.52	9.40 9.25	7.50 7.38
01768	130	11		8.46			11.46	27.00	13.51 CROSSPORT			115.08	P		8.58		1.32	9.02	7.13
01767	116	177		8.56			s11.56	81.81	BONNERS FERR		BY	110.77	DNPVY		s 8.47		1.26	8.47	7.01
									11.37				pw						
01778	116	38		9.10			fl 2.08pm	43.68	7.39	·-#-		99.40	PW		£ 8.36 8.28		1.13	8.28 8.15	6.38
01793	122	11		9.19			12.23	56.88	6.81 COLBURN			85.20	P		8.21		12.57	8.05	6.15
61903	105	891		9.35			sl 2.34	65.23	SANDPOINT	*	8	76.85	DNPVY		s 8.12		12.48	7.52	6.02
									13.35										
61917	124	16		9.50			12.48	78.58	LACLEDE.			63.50	P		7.54		12.33	7.32	5.40
61921	68	105		9.55 9.59			12.53 s12.59	83.29 86.88	THAMA 3.54 PRIEST RIVE	, m	NC	55.25	DP		7.49 * 7.45		12.27	7.25	5.32 5.25
	120	242		10.08			5 .	98.40	6.57 NEWPORT		NR	48.68	DNPVW		s 7.35		12.15	7.08	5.10
61939	126	4		10.08			1.19	101.19	7.79 SCOTIA			40.89	P		7.22		12.06Am	6.55	4.55
									6,59										
61946	117	25		10.25			1.26	107.78	CAMDEN.			34.80	P		7.15		11.58	6.45	4.45
61953	121	31		10.34			1.35	115.07	10.38		8F	27.01 16.63	DNPXJI		7.07		11.50	6.35	4.35
61963		171		10.47			1.53	120.68	M 4.28			13.40	р		6.50	••••••	11.37	6.20	4.20
61972		3519		11.01			1 2.00	184.57	HILLYARD		HU	7.81	BRKDNP		1 6.45		11.25	L 6.00Am	L 4.00pm
01872		-							3.59		-				6.35	1000000	11.15	II O.OOA	D 4.COPIN
				11.08 All.15			2.08	188.16	U. P. R. R. C.	ress'g		3.93	PIMVX						
61977		621	L11.40Pm		L 9.40Pm	L 9.15Pm	A 2.15 L 3.00	139.84	SPOKANE.	★.	Q	2.74	RKDNPO BXVZW IDNP	A 5.40An	L 6.30 A 6.00	A1 0.00pm	L11.10 A10.40		
61980	68	87	A11.45Pm	A11.50Pm	A 9.50Pm	A 9.20Pm	A 3.05Pm	142.06	FORT WRIG	нт*	FW	0.00	YXVR	L 5.30An	The Manager of	the first or a second state of the last	L10.35Pm		
			.05 32.88	3.45 38.15	.10 16.44	.05 32.88	3.57 35.96		Time Over Subo Average Speed P		-			.10 16.44	3.44 38.05	16.44	3.40 38.75	4.00 33.64	4.00 33.64
77/7	PCA	ATT	DD	тттр	D SI	אוותם	ICION	T	ASTWARD	1									
W	ו פינ	AW.	'KD	THIK	ש פט	אזעם.	ISION	E.	HOI WAKD	WES	STW	ARD	FOU	RTH	SUBD	IVISI	ON F	EASTV	VARD
G.					INTAIN				4	-		1							
dal		Jo	Fall	Tir	ne Ta		. 110		Calle	1			Time '			10	ah	4	
N			poe f		Eff. Novemb	ective er 27, 1	966		d SIGNS	1	8		Nove	mber 2	7, 1966		Ferr	Coll	SIGNS
Station Numb		Capacity	Distance from Columbia Falls			TION			Telegraph	M as M	1 1 1				ARD TIM		8.0	dara	- Valvis
- i		OH	40						H	The state of	Capacity		ST	ATI	ONS		Distance from Bonner's Ferry	Pales	
0159	03	240	0.00			BIA FAL	LS	·.*.	CF JDNPYX		1 01						HH		
6160	05	44	5.46		LA	SALLE.			P	61826	15			PORT H	LL		25.95		

Westward trains are superior to eastward trains of the same class on Second, Third and Fourth Subdivisions.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 6 THROUGH 12.

BY DMNPYJY

DNP

PX

61617

61625

427

Yard

14.40

10.45 SOMERS.

WESTWARD FIFTH SUBDIVISION EASTWARD Time Table ECOND SECOND Car Capacity CLASS CLASS No. 110 Effective 704 703 November 27, 1966 SIGNS Distance PACIFIC STANDARD TIME ST. Tue., Fri. Mon., Thur. STATIONS 6.00ANELSON.... BC 185.79 DNWP A 3.20Pm BETWEEN TROUP JCT. AND NELSON BE GOVERNED BY C. P. RY. TIME TABLE AND RULES TROUP JUNCTION 6.30A 2.45P 62180 180.81 YPV SOUTH NELSON 6.55 24 2.10 62176 175.48 9.00 12.30 62151 72 51 150.60 D 5.59 9.25 20 11.55 62145 145.01 FRUITVALE. 10.45 11.10 35 62135 135.88 WANETA, B. C.. 2.11 BOUNDARY, U. S. 11.40 126.18 P 10.20 62128 27 11.50 10.05 62124 40 124.07 NORTHPORT. 12.40P 9.30 NP 60 46 115.26 PDYW 1.10 62107 87 MARBLE. 106.99 8.25 DOLOMITE. 1.20 8.20 62105 105.76 14.10 EVANS 2.10 104 7.35 62092 91.66 RKDNW 2.50P 318 KETTLE FALLS MF 81.74 BYXOJPZ 7.00 An 62081 COLVILLE 107 VD 62073 73.26 PD ARDEN. 62067 7.19 17 62059 59.38 9.07 79 107 CH 50.81 PDZ 62050 81 23 VY 42.60 PD 62043 9.63 27 INGDALE 82.97 62032 P 24.55 62025 24 CLAYTON .. 17.76 P 62018 DE 12.48 PDX 62012 62 SF 0.00 JDNX 61963 Pime Over Subdivision Average Speed Per Hr. 8.50 11.78 8.20 12.49 Westward trains are superior to eastward trains of the same class.

WESTWARD SIXTH SUBDIVISION EASTWARD

-					A STATE OF THE PARTY OF		
Station Numbers	Capacity of Tracks	SECOND CLASS 393 Wed. and Sat.	Distance from Kettle Falls	Time Table No. 110 Effective November 27, 1966 PACIFIC STANDARD TIME STATIONS	Telegraph Calls	SIGNS	SECOND CLASS 394 Wed. and Sat.
						ORKDNB	
62081	318	L 5.00Am	0.00	KETTLE FALLS		JYXPZW	A 4.10Pm
62204	167	5.20	4.70	WEST KETTLE FALLS		P	3.45
62212	24	5.45	12.09	BOYDS		P	3.15
62217	35	6.05	17.48	BARSTOW			2.55
62222	35	6.30	22.71	DULWICH			2,40
62228	12	7.00	28.59	GOLDSTAKE			2.10
62234	18	7.30	34.67	LAURIER, WASH		P	1.50
62246	4	8.15	46.01	GRAND FORKS, B. C.		JYV	1.10
62249	18	8.30	49.12	DANVILLE, WASH		P	12.55
62259	62 88	9.05 9.20	59.52 64.82	10.40 CURLEW		P	12.15Pm
62276	84	9.50	75.81	10.99 TORBOY			
62280	78	A 10.10Am	80.72	4.91 REPUBLIC	z	DYW	L II.UUAm
		5.10 15.62		Time Over Subdivision Average Speed Per Hour			5.10 15.02

Westward trains are superior to eastward trains of the same class.

WESTWARD SEVENTH SUBDIVISION EASTWARD

Station Numbers	Capacity of Tracks	SECOND CLASS 95 Daily Ex. 8un.	Distance from Spokane	Time Table No. 110 Effective November 27, 1966 PACIFIC STANDARD TIME STATIONS	Telegraph Calls	SIGNS	SECOND CLASS 96
61976 62606 62607 62618	00 9 18	L 8.00Am 8.20 8.25 A 9.30Am	0.00 6.07 6.98 18.29	SPOKANE		DMJNKOR YXZVBW X V	A 5.20Pm 4.55 4.50 L 4.10Pm

BETWEEN SPOKANE BRIDGE AND GIBBS C. M. ST. P. & P. RY. TIME TABLE AND SPECIAL INSTRUCTIONS WILL GOVERN.

62630 62632	The second secon	GIBBS	The second second	TO TO WE THE	A 3.00pm L 2.50pm
	2.50 11.16	Time Over Subdivision Average Speed Per Hour			2,30 12,66

Westward trains are superior to eastward trains of the same class.

WESTWARD EIGHTH SUBDIVISION EASTWARD

Station Numbers	Capacity of Tracks	Time Table No. 110 Effective November 27, 1966 PACIFIC STANDARD TIME STATIONS	Distance from Spokane	Telegraph Calls	SIGNS
63694	42	Moscow	96.04	мо	KDYXVW
63686	27	7.87 VIOLA	88.17		
68680	100	PALOUSE	81.56	PA	DAA
63669	43	10.92 GARFIELD	70.64	Q.F	DWM
63657	72	OAKESDALE	58.83	KA	DAM
68644	59	SPRING VALLEY	45.70		A1
63688	31	WAVERLY	39.72		
63635	0	WEST FAIRFIELD	36.79		
63633			34.19		▼

BETWEEN U. P. R. R. JCT. AND N. P. CROSSING U. P. R. R. TIME TABLE AND SPECIAL INSTRUCTIONS WILL GOVERN.

61974	117	 1.95	 VM

OPERATION BETWEEN N. P. CROSSING AND SPOKANE IS OVER SEVENTH SUBDIVISION.

OCCUPATION NAMED IN	CHARLES AND ADDRESS OF THE PARTY OF THE PART	STREET, SQUARE, SQUARE,	-	The second second
61976		 0.00	D8	DNKORYX

Westward trains are superior to eastward trains of the same class.

WESTWARD NINTH SUBDIVISION EASTWARD

Station Num.	Capacity of Tracks	Time Table No. 110 Effective November 27, 1966 PACIFIC STANDARD TIME STATIONS	Distance from Spring Valley	Telegraph Calls	SIQNS
63837	43		36.75	CO	YDW
63825	68	STEPTOE	24.58		
63820	28	5.01 CASHUP	19.57		
63815	28	THORNTON.	15.37		
63806	39	ROSALIA	5.77	EO	DW
63644	59	SPRING VALLEY	0.00		JY

Westward trains are superior to eastward trains of the same class.
SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 6 THROUGH 12.

SPEED TABLE

Time P.	er Mile Sec.	Miles Per Hour	Time Po	er Mile Sec.	Miles Per Hour
Melso	46	78.3	1	18	46.2
	47	76.6	1	20	45.0
	48	75.0	ī	22	48.9
	49	73.5	ī	24	42.9
	50	72.0	1	26	41.9
	51	70.6	1	28	40.9
	52	69.2	ī	30	40.0
	58	67.9	1	88	38.7
	54	66.7	1	86	87.5
	55	65.5	1	39	36.4 35.3
	56	64.8	1	42	35.3
	57	63.2	1	45	34.3
	58	62.1	1	50	32.7
	59	61.0	1 1 2 2 2 2 2 2 2 3	55	81.8
1	0	60.0	2		30.0 27.7
i		59.0	2	10	27.7
1 1 1	2	58.1	2	20	25.7
î	3	57.1	2	30	24.0
1	4	56.8	2	40	22.5
1 1 1	5	55.4	8		20.0
i	6	54.5	8	80	17.1
1	7	58.7	8 4		15.0
1	1 2 3 4 5 6 7 8	53.7 52.9	5		12.0
î	9	52.2	6		10.0
	10	51.4	7		8.6
1	12	50.0	8		7.5
i	14	48.6	9		6.7
1	16	47.4	10		6.0

SPECIAL INSTRUCTIONS

ALL SUBDIVISIONS

1. SPEED RESTRICTIONS GENERAL

The following speed limits apply to trains and engines operating under the conditions outlined, unless rules or conditions require a further reduction.

- 50 MPH-Diesel engines light or with caboose only.
- 40 MPH—Ore cars, Series 80,000 through 95,039, when loaded with zinc concentrates. Helper engines must be cut in ahead of this series of cars in train.
- 35 MPH—Trains or engines on main routes, actuating the points of spring switches: Trains or engines thru No. 20 turnouts at following locations:

Ends of double track.

East and west siding switches at:

Browning Volcour Naples Spotted Robe Ripley Colburn Belton Kootenai Falls Sandpoint Lupier Troy Laclede Stonehill Yakt Scotia Ural Leonia

East switch eastward siding Essex.

East siding switch Vista, Fortine, Crossport.

West siding switch Bison, Libby, Newport, Bonners Ferry.

West yard lead switch Whitefish. SP&S Junction switch Fort Wright.

- 80 MPH—On main lines, when handling following equipment in trains, not in actual service but on own wheels: derricks, cranes, pile drivers, Jordan spreaders, shovels, wedge plows, scale test car, also ore cars series 80000 thru 95039 and air dump cars X-2000 thru X-2096, X-7000 thru X-7049 when such cars are loaded with ore or gravel.
- 25 MPH—Trains handling logs, rotarys; Trains or engines moving in facing point direction at spring switches without facing point lock; Trains or engines thru No. 15 turnouts at following locations:

East and west siding switches at Stryker, Elmira. West siding switch Tobacco.

- 20 MPH—Train handling the following equipment on Branch Lines or on 6 degree or sharper curves of Main Lines: scale test car, ore cars series 80000 thru 95039, air dump cars X-2000 thru X-2096, X-7000 thru X-7049 when such cars are loaded with ore or gravel.
- 15 MPH—Trains handling the following equipment on Branch Lines or on 6 degree or sharper curves of Main Lines: derricks, cranes, pile drivers, Jordan spreaders, shovels and wedge plows.
- 15 MPH—Trains or engines moving thru interlockings against the current of traffic on double track; Trains or engines thru all other turnouts, except equilateral turnouts, and those shown previously in this item.
- 1(a). Rule 240 W of the Consolidated Code of Operating Rules is modified to permit handling Great Northern cars 60276 through 60279, 61500 through 61524 and 61000 through 61009 in passenger trains at passenger train speeds.

2. MOVEMENT OF DIESEL UNITS DEAD IN TRAINS.

Engine 2350 must be handled on rear of Freight or mixed trains.

Diesel engines 1 through 195 are not equipped with alignment control couplers and when in tow in freight or mixed trains must be handled singly, not in groups, and not less than 5 cars or more than 15 cars from the road engine. Other diesel units when in tow dead in trains should not be in groups of more than 5 units, such units may be handled next to road engine.

Engines 550 through 599 must have coupler alignment control blocks in "Down" position when such units are used in multiple operation.

When towing diesel engines dead in trains the following speeds must not be exceeded.

3. Except at points where it is necessary to classify trains, open cars loaded with poles, piling, lumber, timber, pipe, or other lading which might shift, should be placed as close as possible to the head end of train, but not next to engine, caboose, occupied outfit car or passenger car or another unprotected car containing commodities which might be subject to damage. Loaded trailer-on-flat cars are not included in this category. In double track territory, trains handling such cars must use extreme care to avoid slack running in or out when passing or being passed by other trains. In single track territory, trains handling such cars must be at stop when on siding or other track to meet or be passed by other trains, except when have more cars than siding will hold, it is permissible for such trains to pull by each other at restricted speed.

Loaded dump cars should not be handled on double track after dark, but if necessary to do so, close watch must be maintained by members of the crew, and if a car dumps its load, train must be stopped at once and protection provided as prescribed by the rules.

Great Northern flat cars series X-4800 to X-4975 and X-4410, whether loaded or empty, must be handled on rear of train only.

8(a). Trains handling flat or skeleton cars loaded with logs will not exceed 10 MPH passing over thru-truss bridges, or through tunnels. Thorough inspection of all cars of logs in train must be made at appropriate locations when train is stopped for meeting trains and other purposes, making certain train and lading are in safe condition before proceeding. Extra stops enroute will be made for this purpose when in the judgment of the Conductor it is necessary. Members of the crew must maintain a watch for logs that may have rolled off cars and if a track is fouled, take prompt action to protect trains.

On double track, Conductors must notify train dispatcher when logs are to be handled and the log train must be at stop when being passed by other trains, except when both trains are handling logs, either one should be at stop until the other train pulls by, whether on siding or double track.

On single track, trains handling logs must be at stop when meding or being passed by other trains, except when there are more cars than siding will hold, it is permissible for log train to pull by other train at restricted speed.

In double track territory, logs must be secured to cars by chains or cables.

- Brakemen with less than one year of experience should not be used as flagmen except in emergency, and then Superintendent will be notified by wire.
- 5. Due to limited overhead clearance at tunnels and structures, employes are warned to keep off top of cars of extreme height and width when handled in trains and yards, except in emergency. In absence of previous advice on such cars, wire proper officer for instructions.
- 6. Trains departing from stations, either from siding or main track, in trailing point movement actuating points of spring switches, a member of crew must observe indication of governing signal in opposite direction after rear end of train has passed through switch to ascertain if switch points return to normal position. If this signal indicates Stop and no immediate train movement or other cause is evident, report the fact to Superintendent from first available point of communication.

During and immediately following snowstorms or violent wind storms, spring switches must be operated by hand and relined to normal position before heading out through switch in trailing point movement, actuating switch points, to insure switch is in proper operating condition.

- 7. Facing point locks on hand operated switches are indicated by a six-inch yellow stripe painted on target staff. Be positive locking device is restored to normal position after using. A running switch must not be made through this type switch.
- 8. Rule 2 of the Consolidated Code of Operating Rules is modified for Great Northern Railway Company employes to the extent that a watch certificate form is no longer required. Watches of employes will be inspected by Division Officers, Rules Examiners and other designated officers.

Rule 3(C) of the Consolidated Code of Operating Rules is amended as follows: Employees governed by time service rules must not wear wrist watches while on duty unless such watches are of an approved type. Approved type wrist watches are: Elgin, B. W. Raymond model 13/0 size, 23 jewels.
Ball Official Standard 1604B, 13/0 Ligne, 21 jewels. Bulova Accutron Railroad approved model. Hamilton 505 RR Electric Special. Bulova model 23J.

- Regarding Consolidated Code Rule 108. In addition to complying with the provisions of this rule, members of a crew will be governed by the following: When an engine, with or without cars, is about to move over a public crossing not protected by a watchman, by gates or by crossing signals in operation, a mem-ber of the crew must be on the ground at the crossing to provide protection. It is not necessary for a member of the crew to be on the ground at the crossing for a through yard transfer movement, or for a light engine movement being handled only by hostlers.
- 10. Employees are prohibited from riding or walking on the roof of any moving car, except when absolutely necessary in the passing of signals, and then only when they place themselves near the middle of the car.
- 11. The last paragraph of Rule 7(A) of the Consolidated Code of Operating Rules is revised as follows: When backing or pushing a train, engine or cars in response to hand or light signals from a trainman, the disappearance from view of the trainman giving such signals or of his light by which such signals are given must be regarded as a stop signal, except when movement is under control of a trainman on the leading car that is equipped with backup air brake hose or pipe.

Supplementing Rules 7(A) and 12 of the Consolidated Code of Operating Rules: When movement being made is controlled by hand, flag or lantern signals, the employees involved will give or relay such signals directly to the engineer.

The following Uniform Code of Operating Rules are in effect in Canada.

Rule 14. (k-a) 00-

Answer to 14k

Rule 98. Unless protected by block or interlocking signals, trains and engines must approach the end of two or more tracks, junctions, railway crossings at grade or drawbridges, at restricted speed. Unless otherwise specified in special instructions, the speed of any train or engine must not exceed thirty-five miles per hour at interlocked railway crossings at grade until the entire movement has passed the crossing.

Unless otherwise specified in special instructions the speed of any train or engine must not exceed twenty-five miles per hour at interlocked drawbridges until the entire movement has passed the drawbridge.

Trains or engines must stop at the stop signs at non-interlocked railway crossings at grade and at non-interlocked drawbridges and not proceed until the proper signal has been given for that purpose.

Rule 99. When a train is moving under circumstances in which it may be overtaken by another train, lighted fusees must be dropped off at proper intervals and such other action taken as may be necessary to ensure full protection.

When a train stops under circumstances in which it may be overtaken by another train, a flagman must immediately go back a sufficient distance to ensure full protection.

In day time, if there is no down grade toward train within one mile of its rear and there is a clear view of its rear of 2000 yards from an approaching train....at least 1000 yards;

At other times and places, if there is no down grade toward train within one mileat least 1500 yards: of its rear ..

If there is a down grade toward train within one mile of its rear _____at least 2000 yards;

The flagman must, after going back a sufficient distance from train to ensure full protection, take up a position where there will be an unobstructed view of him from an approaching train of, if possible, 500 yards, first placing torpedoes not more than 100 nor less than 50 yards apart to cause two explosions at least 200 yards beyond such position.

If necessary to go beyond the required distance, he will leave the torpedoes at the required distance as an indication of the location of his train, but must, under such conditions, also place torpedoes at the point at which an approaching train is flagged. Torpedoes so placed must not be removed.

The front of a train must be protected in the same manner when necessary.

When a train stops under circumstances in which it may be overtaken by another train, the enginemen will immediately signal the flagman to protect the rear. When ready to proceed he will recall the flagman.

After taking up position at the distance required, flagman must remain at that point until recalled or relieved and safety of the train will permit. Flagman must always on the approach of a train display stop signals.

If recalled before another train arrives, he must leave a fusee burning red at the point from which he returns, and while returning to his train, a fusee burning red must be placed at such points or times as may be necessary to ensure full protection. A fusee burning red must be left at the point from which the train moves.

When curvature, weather or other conditions require, or when snow plows or flangers may be running, extra precaution must be taken.

Flagmen must each be equipped for day time with:

A red flag on a staff, At least eight torpedoes and Seven red fusees.

For night time and when weather or other conditions obscure day signals,

A white light, A supply of matches, At least eight torpedoes and Seven red fusees.

A train should not stop between stations at a place where the view from following trains is obstructed if it can be avoided.

Conductors and enginemen are responsible for the protection of their trains.

PROTECTION OF IMPASSABLE OR SLOW TRACK

- 40. (a) Before undertaking any work which may render the main track unsafe for movements at normal speed, or if rendered unsafe from any cause, trackmen, bridgemen, or other employees must provide protection by sending out a flagman with flagman's signals in each direction at least 2000 yards from the defective or working point.
- (b) After going out the required distance, flagman must take up a position where there will be a clear view of him from an approaching train of, if possible, 500 yards, first placing torpedoes not more than 100 nor less than 50 yards apart to cause two explosions at least 200 yards beyond such position.
- (c) Flagman must not return until recalled or relieved.
- (d) If necessary to go beyond the required distance, flagman will leave the torpedoes at the required distance, but under such conditions must also place torpedoes at the point at which an approaching train is flagged.
- (e) On the approach of a train flagman must display stop signals, using lighted fusees at night or in obscure weather.
- (f) Trains stopped by a flagman will be governed by his instructions, and on reaching the defective or working point will there be governed by instructions of the foreman in charge.
- (g) Flagmen must each be equipped for day time with:

A red flag on a staff.

At least eight torpedoes and

Seven red fusees.

For night time and when weather or other conditions obscure day signals,

A red light,
A white light,
A supply of matches,
At least eight torpedoes and
Seven red fusees.

- 41. On subdivisions or portions thereof specified in the time table or special instructions, Rule 40 may be modified as follows:
- (a) By day place a red flag and, in addition, by night a red light between the rails 200 yards in each direction from the defective or working point, and place torpedoes on each rail to cause one explosion 200 yards beyond the red signals, also:
- (b) By day place a yellow over red flag and in addition, by night, a yellow light and a red light at least 2000 yards in each direction from the defective or working point to the right of the track as seen from an approaching train, and place torpedoes not more than 100 nor less than 50 yards apart to cause two explosions 200 yards beyond these signals.
- (c) Trains approaching the signals prescribed by clause (b) must stop, replace the torpedoes and proceed to the red signal prescribed by clause (a) prepared to stop and there be governed by instructions or signal of the flagman, but must not proceed until the red signal has been removed in the clear view of the engineman.

NOTE: The red signal must be not removed except as authorized by the foreman in charge,

- (d) When weather or other conditions obscure day signals, night signals must be used in addition.
- 43. When the nature of the defect does not require stop to be made, and after speed restriction has been placed by train order and the foreman so advised, Rules 40 and 41 may be modified as follows:
- (a) By day place a yellow flag and, in addition, by night a yellow light at least 2000 yards in each direction from the defective point to the right of the track as seen from an approaching train, also:
- (b) By day place a green flag and, in addition, by night a green light in each direction immediately beyond the defective point.

- (c) Trains must reduce speed to comply with requirements of the train order, and must not increase speed until the entire train has passed the green signal.
- (d) When weather or other conditions obscure day signals, night signals must be used in addition.
- 44. On subdivisions or portions thereof specified in the time table or special instructions, when the main track is found to be unsafe for movements at normal speed but safe for speed of ten miles per hour or more. Rule 41 may be modified as follows:
- (a) By day place a yellow flag and, in addition, by night a yellow light 200 yards in each direction from the defective point to the right of the track as seen from an approaching train, also:
- (b) By day place a yellow over red flag and, in addition, by night a yellow light and a red light at least 2000 yards in each direction from the defective point to the right of the track as seen from an approaching train, and place torpedoes not more than 100 nor less than 50 yards apart to cause two explosions 200 yards beyond these signals, also:
- (c) By day place a green flag and, in addition, by night a green light in each direction immediately beyond the defective point.
- (d) Trains must stop and replace torpedoes on each side of the defective point, and must reduce speed to ten miles per hour before passing the yellow signal and must not increase speed until the entire train has passed the green signal.
- (e) When weather or other conditions obscure day signal night signals must be used in addition.
- (f) The foreman must report the condition to the train dispatcher as soon as practicable, and when advised that speed restriction has been placed by train order must mark the defective point as prescribed by Rule 48.
- 45. In providing protection each main track must be regarded as a track upon which trains may run in either direction. Where two main tracks are on the same roadbed, flags and lights required to be placed to the right of the track as seen from an approaching train under Rules 41-44 inclusive must be placed to the outside of the track affected and not between the two main tracks.
- 46. When flags or lights are placed as set forth in Rules 41-45 inclusive they will be mounted on staffs and elevated so there will be an unobstructed view of them from an approaching train.
- 47. Where the use of torpedoes is required, duplicates should be placed on the opposite rail to explode simultaneously.
- 48. Torpedoes must not be placed near stations nor on public crossings at grade.
- 49. A sign bearing figures indicating permissible speeds, or the word SLOW, placed at the side of the track will indicate a permanent slow order; its location and speeds permitted will be specified in the time table or special instructions.

FIRST SUBDIVISION

(Main Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

2. SPEED RESTRICTIONS.

3. TRAIN REGISTER EXCEPTIONS.

Cut Bank, first class trains and passenger extras register by ticket.

Register of regular trains at Cut Bank will cover their arrival at Blackfoot.

Register of regular trains at Whitefish will cover their arrival at Conkelley.

Troy, First class trains and passenger extras register by ticket.

- CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B). All trains require clearance Form A at Whitefish. Such clearance will confer the same authority as though received at initial station.
- 5. On arrival at Essex, eastward freight trains requiring helper engine assistance will come to a stop and make full application of air brakes and leave applied until proceed signal received from helper engine. Helper engine will be coupled against rear of caboose and immediately make back up movement to ascertain positive coupling.
- Summit is a regular inspection point where stop shall be made for the inspection of freight and mixed trains. Westward freight trains will pull rear end of train clear of end of double track to avoid delay to eastward trains.

On arrival at Summit, eastward freight trains with helper engine assistance behind caboose must come to a stop clear of the end of double track. Under no circumstances whatsoever will anyone be allowed to ride in the caboose within the limits of helper territory while helper engine is shoving against the rear of train. Train crew must ride in rear cab of helper engine, using rear headlight for center of track inspection when necessary.

When outfit cars or passenger equipment handled on rear of freight trains or when stockmen, messengers, etc., are carried in the caboose, helper engines must be cut into train.

8. CROSSOVERS ON DOUBLE TRACK.

FACING POINT

TRAILING POINT

Cut Bank

Sundance MP 1110

Summit Blacktail

Essex, east crossover

Essex, west crossover

Columbia Falls, west crossover

Columbia Falls, east crossover Half Moon

9. MANUAL INTERLOCKINGS WITH DUAL CONTROL SWITCHES.

Cut Bank-end of double track east and west end Bridge 1090.8. .End of Double track. East switch westward siding.

Switch at end of double track and westward siding above points controlled by operator at depot.

Controlled by operator at Eureka.

......West siding switch.

10. AUTOMATIC INTERLOCKINGS.

Nimrod	Single Tra	ıck	Bridge	1165.3
Pinnacle	Single Track MP	11	78.2 to	1177.6
Red Eagle	End	of	double	track.
Conkelley.	End	of	double	track.
Whitefish	End	of	double	track.

Nimrod and Pinnacle:

7

-

Trains or engines stopped by a stop indication at entrance to Pinnacle interlocking will be governed by Rule 509.

Trains and engines approaching interlocking holding instructions requiring them to wait to permit other trains or engines to move through interlocking will stop before passing "Approach Control Nimrod" and "Approach Control Pinnacle" sign for track they occupy and wait until their train rights permit them to proceed.

At eastward and westward home signals a switch key controller fastened to the side of the instrument house near the home signals and a third switch key controller placed in the depot at inspection point for westward trains just east of interlocking, to assist in moving trains when home signal displays Stop-indication account plugs in slide fence pulled out. When trains

or engines receive a Stop-indication at home signal and no conflicting train movement is evident, trainmen should operate key controller by inserting switch key in controller and turning clockwise toward R, holding in that position for a few seconds. If home signal clears after operating key controller, train may proceed through interlocking at restricted speed, looking out for rocks or other obstructions fouling track. If home signal does not clear by operation of key controller, train must be governed by train rights, Interlocking Rules and Special Instructions stated above.

A work train key controller, so marked, is located on side of instrument house at west end of interlocking. Work train occupying eastward track must release interlocking for other train movements by inserting switch key in controller and turning clockwise toward "R", holding key in that position for a few seconds. To clear home signal again for work train movement to single track, key controller must be operated counterclockwise toward "N".

Indicator consisting of red banner on white background in a cast iron case marked "Trainmen's Indicator", and fastened to the west cantilever mast at Nimrod Interlocker.

The red banner, normally vertical, will change to horizontal position to indicate approach of eastward train on eastward track when train is 8000 feet west of cantilever mast,

Pinnacle, signals located to left of track to govern movements against current of traffic to single track at each end of inter-

Hand throw switch equipped with electric lock located at the west end of the eastward siding at Blackfoot, Montana is to be operated as follows:

Eastward trains or engine occupying the main track desiring to use the eastward siding must have train or engine moving from one to three miles per hour over a designated point marked by orange posts placed on both sides the main track located 80 feet in advance of the switch points.

Westward trains or engine occupying the main track desiring to use the eastward siding must move over designated point marked by orange posts placed on both sides the main track located 80 feet in advance of the switch points before making the reverse movement at one to three miles per hour.

11. Double track extends between Summit and Red Eagle except Nimrod and Pinnacle single track interlockings.

12. CONDITIONAL PASSENGER STOPS.

No's. 31 and 32 will stop at Cutbank to receive or discharge revenue passengers from or to points Williston and east or Spokane and west where scheduled to stop, and will stop at Libby to receive or discharge revenue passengers from or to points Minot and east or from or to points Spokane and west where scheduled to stop.

- 13. Westward Approach Signal to end of double track Red Eagle, Montana has been changed to double aspect signal indicating yellow over green when route is properly lined for a westward train to proceed from westward main track to single track. This aspect is named "approach diverging route" and indication is "approach next signal prepared to proceed on diverging route." This signal aspect is covered in CMStP&P R.R. Block and Interlocking Rule 240-E Figure 7, and this rule will apply to and govern Great Northern train and engine movements at this location.
- Consolidated Code of Operating Rules No. 251, 251(A), 258 and 254 apply on Eastward and Westward tracks between Cut Bank and Blackfoot for train movements with the current of traffic. The use of these rules does not modify Rule 99.
- 15. Plum Creek Plywood Mill, Columbia Falls. Spur must not be used for switching. When switching required, cars must be pulled from this track, switch lined back for the wye and switching will be done at south wye switch. When placing cars on this track, air must be cut into cars and air brakes operating.
- 16. Summit has balloon track instead of wye track.

SECOND SUBDIVISION

(Main Line)						
1.	Retween	Passenger Freight 79 MPH 60 MPH				
2.	Between Albeni Falls Spur and Mead, over switches and frogs Plant	5 МРН				
	Spokane, all trains approach crossover east of bridge 270, and crossover west of Howard Street at restricted speed. Spokane, public crossing Howard Street					
8.	TRAIN REGISTER EXCEPTIONS. Ft. Wright second subdivision trains will register by ticket. Spokane, first class trains and trains originating or terminating at passenger station will register and receive clearance. Troy and Hillyard, First class trains and passenger extras regis-					
	ter by ticket.	llyard will cover their arrival at				
4.	ward tracks between Fort Wright with the current of traffic.	4 apply on Eastward and West- at and Dean for train movements				
	not enter main track between ceed signal at an interlocking from operator or train dispatch to no Eastward home signal a	ins (Except First Class trains and Passenger Extras) must enter main track between these points unless given a production of a signal at an interlocking or until permission is received no operator or train dispatcher. At Dean, a proceed indicator on Eastward home signal at end of double track will confer nority to Eastward inferior trains to run ahead of Eastward erior trains to station Dean.				
Б.	CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B). Spokane, clearance issued and signed by the Superintendent will confer the same authority to a first class train as though received at its initial station.					
6.	CROSSOVERS ON DOUBLE Facing point. MP 1477.22 east of Br. 270, Spokane. MP 1477.61 (Scissors) on Br.	TRACK. Trailing point. MP 1476 east of UP. RR. crossing, Spokane. MP 1476.69 on Br. 269, Spo-				
	278 west of Spokane passenger depot.	kane. MP 1477.12 east of Br. 270, Spokane. MP 1477.61 (Scissors) on Br. 278 west of Spokane passen-				
		ger depot. MP 1478.41 west of Br. 278, Spokane. MP 1467.2 east of East Switch Mead				
7.	Whistle signals for routes:	double track and SP&S Ry Jct.				
je is Žini	Main Track GN Ry	1 long, 1 short. 2 long, 1 short.				
8.	SWITCHES.	west siding switch				
	controlled by operator at depot HILLYARDEnd of doub east and west of yard controlled	le track and yard lead switches				

The "home signal limits" (Rule 605) on main track extend from the westward home signals at east end of yard to eastward home signals at west end of yard. After receiving proper signal indication and entering home signal limits at east and west end Hillyard yard, switching movements may be made between these home signals and Rule 670 will not apply. Whistle signals for routes west end of yard: Eastward trains, To yard long, 1 short.

9. AUTOMATIC INTERLOCKINGS.

U.P.R.R. crossing 1.19 miles east of Spokane.

To westward main track 1 long.

To eastward main track ______2 long, 1 short.

After signal has cleared for either a GN or UP route the entry of a train or engine of the other railroad into their approach control will automatically start a predetermined time cycle of 2 to 4 minutes which at expiration will cause signal to go to stop position and after another time cycle of 2 minutes will clear signal for route on other railroad.

Push buttons located on home signals of all main track roumay be operated to obtain signal indication for a reverse mo ment. Push button emergency release is located near crossing and instructions are posted in box. Switch to the S.I. interchange just west of the crossing is electrically locked.

- 10. Double track extends between Dean and Fort Wright, except at Hillyard and over bridge 274 and SP&S Jct. which is governed by interlocking signals.
- 11. Spokane, City Ordinance prohibits sounding engine whistle within city limits, except to prevent accident not otherwise avoidable or to signal an interlocking, or to communicate with a flagman.
- Crews will stop all cars, locomotives or other equipment before entering the Post Office Terminal Building at Spokane, Wash-

THIRD, FOURTH, FIFTH, SIXTH, SEVENTH, EIGHTH AND NINTH SUBDIVISIONS.

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS. Between Bonners Ferry and Port Hill...... 10 MPH Spokane and Coeur d'Alene...... 25 MPH Spring Valley and Colfax 25 MPH 2. SPEED RESTRICTIONS. Kalispell, over main street crossing 5 MPH

Transport, o tor mour am con or opportunitions.	0 242 11
Northport, wye track	8 MPH
Dolomite, spur tracks	10 MPH
Northport to Troup Jet., handling logs	15 MPH
Kettle Falls to Dean, handling ore	80 MPH
Spokane, Crestline St., UP and Milw. crossings	15 MPH
Millwood, public crossing	4 MPH
Moscow, through city limits	10 MPH

3. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

Great Northern Clearance Form A received at Nelson will clear train at Troup Jct. Kettle Falls, all trains must obtain Clearance Form A.

Seventh subdivisions trains destined Coeur d'Alene must obtain Milwaukee clearance at Spokane, returning obtain Milwaukee clearance at Coeur d'Alene.

Eighth subdivision trains destined Moscow will obtain their U. P. clearance at Dishman, on return trip obtain U. P. clearance at Fairfield.

4. ENGINE RESTRICTIONS.

Between Bonners Ferry and Port Hill GP-7 and GP-9 class heaviest permitted, additional units must be separated by not less than 5 cars. Also empty buffer car to be used behind these engines when operated on K. V. line.

5. RESTRICTED CLEARANCES.

Bridges C 7.7, 7.8 and 7.9 3200 feet west of Millwood, restricted side clearance.

Spokane, bridges 1.3 and 1.6 will not clear man on top or side of engine or car, employes must stay off side or top of cars or engines when on bridges, except in an emergency and then must exercise extreme caution.

Post Falls, Idaho, restricted side and overhead clearance at the chip loader, Post Falls Lumber Co. Spur. The lateral restricted clearance extends for 250 feet parallel to the track on this spur, employes must be extremely careful in this area.

Colfax tunnel and bridges 71.6, 72.3 and 72.4 will not clear man on side or top of engine or car.

- 6. Train movements between N.P. Crossing and Dishman will be governed by remote controlled signals at N.P. Crossing, at east and west ends of new yard, and east end of siding at Dishman. Indications of these signals supersede the superiority of trains between these points. When a Stop-indication is displayed on one of the signals a member of the crew must communicate with the operator and be governed by his instructions in accordance with Rule 509.
- Northport-Waneta, Laurier-Danville, trains must not pass International Border without permission of Customs and Immigration Inspectors.

- 8. Canadian Maintenance of Way Flagging Rules 41 and 44 apply between Troup Junction and Boundary, U.S. and between Laurier, Wash, and Danville, Wash.
- 9. Coeur d'Alene, 11th Street and Mullan Ave., 15th Street and Mullan Ave. Crossings, train and engine movements over these crossings must stop before moving over and movement must be protected by a man on ground at crossing.
 Coeur d'Alene, train and engines must stop and sound two blasts of engine whistle before proceeding over Diamond Drill crossing. Spokane, Trent Avenue crossing protected by watchman 7:00 AM to 11:00 PM daily, outside these hours a member of the crew must be on the ground at crossing to protect the movement. Colfax, use care when moving over North and Last Street crossings account restricted view.

10. MANUAL INTERLOCKINGS.

NP Crossing, 1.86 miles west of Spokane. Whistle signal for G.N. to U.P. main track, two long 1 short. Trains from Seventh subdivision to U.P. tracks will be governed by dwarf signal at base of westward two-arm interlocking signal.

11. GATE PROTECTED RAILROAD CROSSINGS.

U.P.R.R. Crossing 0.57 miles west of Thornton, normal position of gate is stop for Great Northern.
U.P.R.R. Crossing 0.29 miles west of Colfax, normal position of gate is stop for Great Northern.

12. Unless otherwise instructed, protection against following trains, as required by Consolidated Code Rule 99, is not necessary between points shown below. If it becomes necessary to operate a following train when there is still a train between these points, the train ahead must be notified to protect against the following train. If this is not practical the following train must be notified to protect against the train ahead.

These instructions apply between the following points and train order Form Z is not required.

Between Columbia Falls and Somers.

Bonners Ferry and Port Hill Spokane and Spokane Bridge U.P. Junction at Fairfield and Moscow Spring Valley and Colfax

BUSINESS TRACKS NOT SHOWN AS STATIONS ON TIME TABLE

-		<u> </u>	T		1				
	Name	Location	Capaci- ty Cars	Switch Opens		Name	Location	Capaci- ty Cars	Switch Opens
						ubdivision No. 5—Cont.	2000 C	500	
01401	Subdivision No. 1	205 7			62148		2.73 miles west Salmo	11	Both
01481 01486	Gunsight—storage track	3.25 miles east Sundance 1.88 miles west Sundance		West East	62143 62140		1.98 miles west Meadows	6	West
01400	rarque—Sammona Spur	1.55 miles west bungance	1 ** {	e w trk	02140	ParksRoss	4.93 miles west Meadows 3.24 miles west Meadows	8	Both Both
01495	Meriwether-storage track	5.97 miles east Blackfoot	8	East	62141	Hearn Bros. Spur.	4.67 miles west Meadows	3	East
			1	e w trk	62136	ATCO Spur	0.40 mile east Fruitvale.	3	East
01555	Essex Pit	2.97 miles west Essex	50 }	East	62132	Equipment Spur	3.15 miles west Fruitvale	š	West
01505	Lawrence to Albert Tenance	- %	1 1	ww trk	62130	Columbia Gardens.	3.84 miles east Waneta, B.C.	11	Both
01591		0.50 7 / 6 11 11	Ι,		62129		0.67 mile east Int. Bdy. at Waneta	32	East
	Storage Track	0.73 mile west of end double track Conkelley	114	Beth ww trk	62127		0.40		n
01596	Half Moon	4.70 miles east Whitefish	46	West	62112	Light Co. Ldg Janni Spur	0.48 mile west Waneta	5 11	Both West
			1 ~ {	e w trk	62110	Cameron Spur.	4.40 miles west Northport.	17	East
01696	Warland Pit (Three Tracks)	1.06 miles east Yarnell	92 `	Both	62105		1.23 miles west Marble, including	**	Day
	W. R. Grace Co. Siding	4.82 miles east Libby (MP 1331).	49	Both	170 Paul Control	Secure de la company de la com	trackage Spokane-Portland		
	ANGER STATE OF THE	7					Cement Co., Private Yd	251	West
015	Subdivision No. 2				62077		5.31 miles west Kettle Falls	12	Both
01756	Katka Spur	6.46 miles east Crossport	18	East	62056 62041	Blue Creek	2.98 miles west Addy	18	Both
01761 01765	Crossport Spur	1.81 miles east Crossport 0.71 mile east Bonners Ferry	15	East	62041	Kulzer's Spur North American Non Metallics	1.70 miles west Valley	6	East
01703	Idaho-Boyd Conlee Spur Moravia	4.95 miles west Bonners Ferry	35 21	West East	02010	Spur	2.02 miles west Valley	4	Fact
01791	Emerson Spur	0.68 mile east Colburn	58	West	62034	Cline	0.96 miles east Springdale	18	de
01792	Pack River Lumber Co	0.68 mile east Colburn	15	West	62033	Silica Sand Co. Spur	0.64 mile east Springdale	8	1.30
61906	Dover connection to S. I. Ry	2.46 miles west Sandpoint	19	East	62026	Loon Lake Gravel Spur	1.60 miles east Loon Lake	40	East
61924	Hedlund Lumber Co. Spur	0.77 miles east Priest River	16	West		Carbaliation No. 0			
61928	Albeni Falls Spur	2.66 miles east Newport	21	East		Subdivision No. 6 Boise Cascade Spur	0.50 mile west West Kettle Falls	00	
61935 61949	Penrith Spur Elk—storage tracks	3.50 miles west Newport 2.99 miles west Camden	19 21	East	62205	Harter Lumber Co	1.02 miles west West Kettle Falls.	36 10	East Both
61966	Davies Spur	1.51 miles east Mead	34	East East	62207	Matneys Spur	2.72 miles west West Kettle Falls.	4	East
01000	Duvide Dpm	1.01 miles east mead	07	15030	62211	Spokane-Portland Cement Co. Spur	1.34 miles east Boyds	ĝ	East
	Subdivision No. 3	5			62245	Consolidated Mining and	•		
	LP Gas Service Co. Spur.	0.99 miles west Columbia Falls	4	East		Smelting Co. Spur	1.11 miles east Grand Forks	12	West
61602	Rocky Mtn. Lbr. Co. Spur.	1.23 miles west Columbia Falls	9	East	62272	Pollard	7.31 miles west Malo	18	Both
61610	Associated Seed Growers	3.56 miles east Kalispell	6	East	62277	San Poil Spur	0.96 mile west Torboy	21	East
61611	Montana Saw Service Co. Spur	3.34 miles east Kalispell	5	East	1	Subdivision No. 7		1	
61612	C&C Plywood Corp.	2.57 miles east Kalispell	27	Both	62631	Northwest Tbr. Co.	0.89 miles east Coeur d'Alene	16	East
61613 61614	Northwestern Lbr. Co. Spur Carter Oil Co. Spur	1.38 miles east Kalispell	47 9	East East	62629	Atlas	2.53 miles east Coeur d'Alene	37	Both
01014	Interchange Track	0.16 miles west west wye switch,	9	Dast	62626	Huetter—connection to N.P.			
		Kalispell	27	Both		Railway	2.82 miles east Coeur d'Alene	15	Both
	Forest Products Co. Spur	On interchange track	6	West	62623	Post Falls	8.15 miles east Coeur d'Alene	6	Both
61619	Monarch Lbr. Co	5.17 miles west Kalispell	8	East	62623 62624	Post Falls Lumber Co	7.63 miles east Coeur d'Alene	14	West
61621	Erickson Bros. Spur	5.57 miles west Kalispell	4	East	62615	Liberty Lake	7.63 miles east Coeur d'Alene 3.12 miles east Spokane Bridge	6 8	East East
61622	Balla Crossing	5.75 miles west Kalispell	11	East	62613	Greenacres.	5.25 miles east Spokane Bridge	15	Both
	Subdivision No. 4	200 E		ģ	62611	Carders	4.18 miles west Millwood	5	E
61802	Quarry Spur	1 37 miles and Ronners Form	4	West	62604	Parkwater	4.40 miles west Spokane	4	
61804	Allen's Spur	4.72 miles east Bonners Ferry	6	East		Cubdivision No. 0	anno	l	
61807	Ritz	7.56 miles east Bonners Ferry	15	Both	63691	Subdivision No. 8 Estes	3.22 miles west Moscow	,,	D-II
61811	Watson's Spur	11.48 miles east Bonners Ferry	2	West	63675	Grinnell.	4.91 miles west Palouse	15 11	Both Both
61813	DeVoignes Spur	13.16 miles east Bonners Ferry	4	East	63665	Crabtree	4.06 miles west Garfield	9	Both
61814	Camp 5 Spur	14.14 miles east Bonners Ferry	11	Both	63661	Sokulk	4.26 miles east Oakesdale	18	Both
61815 61816	Seelover's Spur	15.41 miles east Bonners Ferry 16.88 miles east Bonners Ferry	2 25	East	63660	Longwill	2.88 miles east Oakesdale	5	East
61817	Dehlbom Spur	17.50 miles east Bonners Ferry	25 4	Both West	63651	Seabury	5.60 miles west Oakesdale	12	Both
61818	Edward's Spur.	18.44 miles east Bonners Ferry	9	West	63649	Fairbanks	5.26 miles east Spring Valley	20	Both
61819	Camp 8	19.74 miles east Bonners Ferry	18	Both	63640 63635	Jefferson	3.48 miles west Spring Valley 2.93 miles west Waverly	6	Both
61821	Harper's Spur	21.82 miles east Bonners Ferry	4	West	63635	Old West Fairfield	2.50 miles west waverly	17	East Both
	Houck's Spur	22.20 miles east Bonners Ferry	4	West	63635	Old Mt. Hope		24	Both
01824	K. V. Farm Spur	24.61 miles east Bonners Ferry	5	West	63605	Dishman	6.52 miles east Spokane	16	East
	Cubdinleton No. 5			4	8 7	Includes Spear		21	West
6918K	Subdivision No. 5	10.10 miles west So. Nelson	ا بر	Dall	11.7	Cubdinisis N 0	35 Commonwealth (1997)		
	Ymir	17.32 miles west So. Nelson	14 12	Both Both	63831	Subdivision No. 9 Manning	5.69 miles west Colfax		W71
62156	Hardy Lbr. Co. Ltd. Spur	19.16 miles west So. Nelson	16	West	63811	Balder	4.76 miles east Rosalia	6	West Both
62154	Boulder Mill	3.29 miles east Salmo	9	Both	63803	Rollins.	2.54 miles east Spring Valley	11	East
		71 HW 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					one oping imoj	^^	
w 3 c	8 mg _sing					s =			